Loading...

Roll over image to zoom in

10ft Cat6 Non-Booted UTP Unshielded Ethernet Network Patch Cable - Plenum CMP-Rated - Gray (TAA Compliant)

For network adapters, hubs, switches, routers, DSL/cable modems, patch panels and other high performance networking applications where plenum cables are required.

5.0
1 Review

Product # : 15268

Connector 1 : (1) RJ-45 Male

Connector 2 : (1) RJ-45 Male

Colors : Grey | Blue | Black

Lengths : 10ft | 1ft | 3ft | 5ft | 7ft | 14ft

+ show all lengths

In Stock, only 2 left

1

Add

Need it shipped today?
Place your order before the timer runs out!

02: 44: 50

print share chat

Product Info | Customer Reviews | Questions & Answers | Distributors | More Choices

Description | Features | Certifications | Specs | Uses

Product Description

Strict building code requirements for cabling in plenum spaces have created installation challenges in settings such as schools, hospitals and other commercial buildings. C2G has expanded its connectivity portfolio to include a line of cables that are ideal for routing through plenum space above dropped ceilings or under raised floors.

Applications include voice/data/video distribution; this cable will handle bandwidth-intensive applications . Meets all Cat6 TIA/EIA standards, and reduces both impedance and structural return loss (SRL) .

Constructed from high quality plenum cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in Gray, Blue and Black to easily color-code your network installation.

Product Features

- Rated for Plenum, in-wall installations
- Cat6 cable with standard RJ45 connectors
- Available in lengths up to 100ft

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Product Certifications

TAA COMPLIANT

Product Specifications

Color :	Grey
Length :	10.00 Foot
Jacket Rating :	Plenum
UPC :	757120152682
Warranty :	Lifetime
Vendor :	C2G
Weight :	0.253 LB

- Conductor: 4-pair (UTP) 23AWG solid copper
- Jacket Rating: CMP - Plenum
- Connectors: 50 micron gold plated RJ45
- Wired: 568B
- Tested to 550MHz
- TIA/EIA-568-C.2
- RoHS Compliant

Product Uses

- 100Base T Ethernet
- 1000Base-T Gigabit Ethernet
- 10GBase-T 10 Gigabit
- Ethernet
- 1000 Mbps ATM
- 622Mbps ATM
- Broadband Video
- POE

Norton SECURED powered by VeriSign

United States | Europe +

Copyright © 2019 C2G. All Rights Reserved

legrand®