




注記

NOTES:

1. 材料(MATERIAL)

ウェハー : ポリアミド, UL94V-0 (色: アイボリー)

WAFER: POLYAMIDE, UL94V-0 (COLOR: IVORY)

ピン: □0.635 黄銅、銅下地錫めっき

PIN: □0.635 BRASS, TIN 5μMIN. OVER COPPER 2.5μMIN. PLATING.

2


6極以上に適合。

TO BE APPLIED FOR 6 CKT. AND ABOVE.

3

5極以下はロック部スリットなし。

NO SLIT IS PROVIDED FOR 5 CKT.AND LESS THAN 5 CKT.



基板取付穴推奨寸法
RECOMMENDED P.C. BOARD HOLE DIM.

1.35	0.85	35	35	22041151	5045-15A	15
1.35	0.85	32.5	32.5	22041141	5045-14A	14
1.35	0.85	30	30	22041131	5045-13A	13
1.35	0.85	27.5	27.5	22041121	5045-12A	12
1.35	0.85	25	25	22041111	5045-11A	11
1.35	0.85	22.5	22.5	22041101	5045-10A	10
1.35	0.85	20	20	22041091	5045-09A	9
1.35	0.85	17.5	17.5	22041081	5045-08A	8
1.35	0.85	15	15	22041071	5045-07A	7
1.35	0.85	12.5	12.5	22041061	5045-06A	6
1.35	0.85	10	10	22041051	5045-05A	5
1.35	0.85	7.5	7.5	22041041	5045-04A	4
1.2	1	5	5	22041031	5045-03A	3
1.2	1	2.5	2.5	22041021	5045-02A	2
(D)	(C)	(B)	(A)	ORDER NO.	ENG. NO.	CKT.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
DIMENSION UNITS mm		SCALE 5:1		CURRENT REV DESC: PLATING DETAILS WAS INCLUDED			molex			
GENERAL TOLERANCES (UNLESS SPECIFIED)										
ANGULAR TOL		± 3.0 °		EC NO: 830929 DRWN: VKAMAK 2025/08/06 CHK'D: VKAMAK 2025/08/07 APPR: SMURUGESAN 2025/08/07 INITIAL REVISION: DRWN: KKOHAMA 2000/03/27 APPR: NUKITA 2013/06/13			MINI-LATCH 2.5 HEADER ASSEMBLY VT WITH LOCK TIN PLATING			
4 PLACES		± 0.4					PRODUCT CUSTOMER DRAWING			
3 PLACES		± 0.4					DOCUMENT NUMBER			
2 PLACES		± 0.4					SD-5045-NA			
1 PLACE		± 0.4					PSD			
0 PLACES		± 0.4		SERIES			DOC PART		REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		A3-SIZE		SHEET NUMBER		
						5045		1 OF 1		
						SEE CHART		GENERAL MARKET		