RAFIX 16 - Toggle switch, square collar, alignable without gaps

1.30.075.041/0104

Only use contact blocks with momentary function.



General information	
Form of collar	square alignable


Dimensions	
Collar dimensions	24.95 x 24.95 mm
Overall height	18.4 mm
Mounting depth	44.7 mm
Mounting hole	16.2 mm
Key grid	25 x 25 mm

Mechanical design	
Mounting	ring nut
Contact function	latching
Contact arrangement	according to contact block
Illumination	no


Mechanical characteristics	
Robustness max.	100 N


Other specifications	
Degree of protection from front side	IP65 (DIN EN 60529)
Operation temperature min.	-25 °C
Ambient temp. operating max. without lamp / LED	+70 °C
Ambient temp. operating max. with lamp /LED	+55 °C
Storage temperature min.	-40 °C
Storage temperature max.	+85 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Operating life (operations)	300,000
ROHS compliant	yes
REACH compliant	yes

Panel cut-out



Technical data are approximate and intended solely for general orientation in the selection of a product.
Subject to modifications and errors. Images and other graphics may only be similar.
For more information, refer to www.rafi.de chapter Imprint / Data Protection.





Technical data are approximate and intended solely for general orientation in the selection of a product.
Subject to modifications and errors. Images and other graphics may only be similar.
For more information, refer to www.rafi.de chapter Imprint / Data Protection.