EVA-M

~25° medium beam



SPECIFICATION:

Dimensions	Ø 35.0
Height	16.4 mm
Fastening	glue
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
EVA-M	Single lens	PMMA	clear		

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C10685_EVA-M	540	90	45	5.8
» Box size: 480 x 280 x 300 mm				

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CITIZEN

LED	CLU7A2/7A3
FWHM / FWTM	22.0° / 44.0°
Efficiency	89 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	MC-E
FWHM / FWTM	22.0°
Efficiency	89 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	MHB-A/B
FWHM / FWTM	25.0° / 50.0°
Efficiency	82 %
Peak intensity	3.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XHP35 HI
FWHM / FWTM	28.0° / 56.0°
Efficiency	78 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XM-L
FWHM / FWTM	24.0°
Efficiency	88 %
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

CREE LEDs

LED	XP-G2
FWHM / FWTM	24.0° / 42.0°
Efficiency	88 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XT-E
FWHM / FWTM	24.0°
Efficiency	%
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	25.0° / 49.0°
Efficiency	85 %
Peak intensity	3.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON M/MX
FWHM / FWTM	26.0°
Efficiency	89 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON MZ
FWHM / FWTM	24.0° / 44.0°
Efficiency	87 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NS9x383
FWHM / FWTM	24.0° / 46.0°
Efficiency	88 %
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NSMx286M
FWHM / FWTM	26.0° / 52.0°
Efficiency	88 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM

LED	Duris S8
FWHM / FWTM	25.0° / 46.0°
Efficiency	86 %
Peak intensity	4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SEOUL SEMICONDUCTOR

LED	Z8Y15
FWHM / FWTM	24.0° / 43.0°
Efficiency	83 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SEOUL SEMICONDUCTOR

LED	Z8Y19
FWHM / FWTM	24.0° / 43.0°
Efficiency	84 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CITIZEN

LED	CLU700/701/702/703
FWHM / FWTM	28.0° / 53.0°
Efficiency	93 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP50.2
FWHM / FWTM	28.0° / 52.0°
Efficiency	95 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XM-L HVW
FWHM / FWTM	26.0°
Efficiency	%
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON 5258
FWHM / FWTM	24.0° / 44.0°
Efficiency	93 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

LUMINUS

LED	CXM-3
FWHM / FWTM	26.0° / 44.0 + 46.0°
Efficiency	94 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMINUS

LED	CXM-4
FWHM / FWTM	26.0° / 48.0°
Efficiency	94 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSCONIQ P 7070
FWHM / FWTM	25.0° / 46.0°
Efficiency	93 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.