

T120R0K2



Article Number: 112-12060

Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Black, 50/pkg

 RoHS

 Download drawing

 Download spec sheet

Base Data

Local Order Number	T120R0K2
Type	T120R
Color	Black (BK)
Features and Benefits	• Heavy duty design to offer higher tensile strength. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	120.0 lbs
Minimum Tensile Strength (Metric)	535.0 N
Length L (Imperial)	15.2 "
Length L (Metric)	387.0 mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3 "
Width W (Metric)	7.6 mm
Bundle Diameter Min. (Imperial)	0.2 "
Bundle Diameter Min. (Metric)	5.0 mm
Bundle Diameter Max. (Imperial)	4.1 "
Bundle Diameter Max. (Metric)	105.0 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	50
Carton Quantity	1000
Weight (Metric)	5.14 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139 MIL 53421
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes