






# FEMALE PLUG M8 STRAIGHT TO MALE PLUG M8 STRAIGHT




NOTES:


RATED VOLTAGE: 3 contacts 60V AC/DC
4 and 5 contacts 30V AC/DC
CURRENT RATING: 3, 4, 5 contacts 3A
PROTECTION CLASS: IP 67 in mated and locked position.
TEMPERATURE: SEE CABLE INFORMATION
INSULATION RESISTANCE: $10^8$ Ω MIN.
MATING CYCLES: MIN. 100
PACKAGING ACCORDING TO PACKAGING SPEC. 1201202000

CONTACTS POSITION FRONT VIEW:

| | 3 CONTACTS | 4 CONTACTS | 5 CONTACTS |
|---|---|---|---|
| FEMALE |  |  |  |
| MALE |  |  |  |

| CONNECTIONS | PIN | WIRE | PIN | WIRE | PIN | WIRE |
|---|---|---|---|---|---|---|
| | 1 | BROWN | 1 | BROWN | 1 | BROWN |
| | 3 | BLUE | 2 | WHITE | 2 | WHITE |
| | 4 | BLACK | 3 | BLUE | 3 | BLUE |
| | | | 4 | BLACK | 4 | BLACK |
| | | | | | 5 | GREY |

CODING ACCORDING TO IEC 61076-2-104



SCALE 1:1

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2

| ITEM | QTY. | DESCRIPTION | MATERIAL | FINISH |
|---|---|---|---|---|
| 11 | 1 | INSERT MALE BLACK | TPU | --- |
| 10 | 3 / 4 / 5 | CONTACT M8 MALE | BRASS | SELECTIVE Au OVER Ni |
| 9 | 1 | SLEEVE | BRASS | NICKEL |
| 8 | 1 | COUPLING NUT M8 MALE | BRASS | NICKEL |
| 7 | 1 | LABEL YELLOW | VINYL | --- |
| | - | PRINTING FOR CABLES Ixx | --- | --- |
| 6 | - | CABLE | SEE SHEET 2 | --- |
| 5 | - | OVERMOULDING BLACK | TPU | --- |
| 4 | 1 | COUPLING NUT M8 FEMALE | BRASS | NICKEL |
| 3 | 1 | INSERT FEMALE BLACK | TPU | --- |
| 2 | 1 | O-RING RED | FKM | --- |
| 1 | 3 / 4 / 5 | CONTACT M8 FEMALE | BRASS | SELECTIVE Au OVER Ni |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| DIMENSION UNITS | SCALE |
|---|---|
| mm | 2:1 |

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | | |
|---|---|---|
| ANGULAR TOL | ± | 1.0 ° |
| 4 PLACES | ± | |
| 3 PLACES | ± | |
| 2 PLACES | ± | 0.05 |
| 1 PLACE | ± | 0.3 |
| 0 PLACES | ± | 0.5 |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: REMOVED OBSOLETED PART NUMBERS AS PER PCN#517104

EC NO: 836952
DRWN: SAMPRS 2025/10/11
CHK'D: GGA 2025/10/16
APPR: GGA 2025/10/16

INITIAL REVISION:
DRWN: JMARSZALEK 2016/09/15
APPR: RSILLER 2017/01/11

molex

CSE M8 M8 XP AC BC FE STR MA STR XM

PRODUCT CUSTOMER DRAWING

| DOCUMENT NUMBER | DOC TYPE | DOC PART | REVISION |
|---|---|---|---|
| 1200878240 | PSD | 000 | A20 |

| THIRD ANGLE PROJECTION | DRAWING | SERIES | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
|---|---|---|---|---|---|
| | A3-SIZE | 120087 | SEE PART LIST | GENERAL MARKET | 1 OF 4 |

| DOCUMENT STATUS | P1 | RELEASE DATE | 2025/10/16 19:09:04 |
|---|---|---|---|

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01

# ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).


OPTIONS


| 4 | 4 | X | 0 | 3 | 0 | X | X | X | X | X | X | X | X |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

- 44=Nano-Change M8x1 Double ended
- Contacts: 3=3 Contacts 4=4 Contacts 5=5 Contacts
- Heads style: 030=Plug Female Straight to Plug Male Straight
- Cable type: See Table
- Units: M=Meter C=Centimeter
- Length Examples: 005=0.5 unit 010=1 unit 100=10 unit
- Overmold color: Blank (Standard)=Black A=Grey / G=Black / Y=Yellow
- Coupling Nut: Blank (Standard)=Knurled Brass Ni Plated 9=Knurled / Hexagonal SW9 Brass Ni Plated
- H= 2 pcs. of I/D Carrier PVC Transparent (Cables Ixx & P82 always with 2 pcs. of I/D Carrier)

COUPLING NUT

FEMALE MALE





## CABLE INFORMATION (for more information see Cable Data Sheet).

| CABLE TYPE | NO. OF WIRES | CROSS SECTION | CABLE JACKET | UL | CSA | STATIC: TEMP. / BENDING RADIUS | DYNAMIC: TEMP. / BENDING RADIUS | DRAG CHAIN | SHIELD |
|---|---|---|---|---|---|---|---|---|---|
| E02 | 3 / 4 / 5 | 0.25 mm² | PVC BLACK | UL 2464/1729 | C22.2 I/II A/B 80°C/300V | -30°C to +80°C, >10xO.D. | -10°C to +80°C, >15xO.D. | - | - |
| H08 | 3 / 4 / 5 | 0.25 mm² | PUR BLACK LS0H | UL 21198/10493 | C22.2 I/II A/B 80°C/300V | -40°C to +80°C, >5xO.D. | -25°C to +80°C, >10xO.D. | 2 000 000 cycles at 20°C, Temp. range +5°C to +60°C | - |
| I02 | 3 / 4 | 0.25 mm² | PVC CEI GREY | - | - | -30°C to +70°C | -5°C to +70°C | - | - |
| P02 | 3 / 4 / 5 | 0.25 mm² | PUR / PVC BLACK | - | - | -30°C to +80°C, >7xO.D. | -5°C to +80°C, >15xO.D. | - | - |
| P82 | 3 | 0.34 mm² | PUR IRR ORANGE | - | - | -50°C to +105°C, >5xO.D. | -40°C to +105°C, >7.5xO.D. | - | - |
| H70 | 5 | 0.25 mm² | PUR BLACK | - | - | -40°C to +80°C, >5xO.D. | -25°C to +80°C, >10xO.D. | 2 000 000 cycles at 20°C, Temp. range +5°C to +60°C | - |

## CABLE LENGTH TOLERANCES

| OVER | UP TO AND INCLUDING | TOLERANCES |
|---|---|---|
| 0 | 305mm | +19mm |
| 305mm | 915mm | +45mm |
| 915mm | 1830mm | +56mm |
| 1830mm | 3660mm | +89mm |
| 3660mm | 7320mm | +165mm |
| 7320mm | 14640mm | +317mm |
| 14640mm | 30500mm | +610mm |
| 30500mm | > | +2% of finished length |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| DIMENSION UNITS | SCALE |
|---|---|
| mm | 2:1 |

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | | |
|---|---|---|
| ANGULAR TOL | ± | 1.0 ° |
| 4 PLACES | ± | |
| 3 PLACES | ± | |
| 2 PLACES | ± | 0.05 |
| 1 PLACE | ± | 0.3 |
| 0 PLACES | ± | 0.5 |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: REMOVED OBSOLETED PART NUMBERS AS PER PCN#517104

EC NO: 836952

DRWN: SAMPRS 2025/10/11

CHK'D: GGA 2025/10/16

APPR: GGA 2025/10/16

INITIAL REVISION:

DRWN: JMARSZALEK 2016/09/15

APPR: RSILLER 2017/01/11

molex

CSE M8 M8 XP AC BC FE STR MA STR XM

PRODUCT CUSTOMER DRAWING

| DOCUMENT NUMBER | DOC TYPE | DOC PART | REVISION |
|---|---|---|---|
| 1200878240 | PSD | 000 | A20 |

| THIRD ANGLE PROJECTION | DRAWING | SERIES | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
|---|---|---|---|---|---|
| | A3-SIZE | 120087 | SEE PART LIST | GENERAL MARKET | 2 OF 4 |

| DOCUMENT STATUS | P1 | RELEASE DATE | 2025/10/16 19:09:04 |
|---|---|---|---|

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01

# PART LIST

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 3P CABLE H08 | | |
| 1200878982 | 443030H08M003H | 0.3m |
| 1200878558 | 443030H08M006 | 0.6m |
| 1200879035 | 443030H08M006H | 0.6m |
| 1200878500 | 443030H08M010 | 1m |
| 1200879036 | 443030H08M010H | 1m |
| 1200878983 | 443030H08M015H | 1.5m |
| 1200878149 | 443030H08M020 | 2m |
| 1200879056 | 443030H08M020H | 2m |
| 1200878540 | 443030H08M020Y | 2m |
| 1200879037 | 443030H08M025H | 2.5m |
| 1200878126 | 443030H08M030 | 3m |
| 1200879090 | 443030H08M035H | 3.5m |
| 1200878998 | 443030H08M030H | 3m |
| 1200878166 | 443030H08M040 | 4m |
| 1200879001 | 443030H08M040H | 4m |
| 1200878984 | 443030H08M045H | 4.5m |
| 1200878127 | 443030H08M050 | 5m |
| 1200878999 | 443030H08M050H | 5m |
| 1200878539 | 443030H08M050Y | 5m |
| 1200878636 | 443030H08M055 | 5.5m |
| 1200878699 | 443030H08M055H | 5.5m |
| 1200879080 | 443030H08M060 | 6m |
| 1200879055 | 443030H08M060H | 6m |
| 1200878808 | 443030H08M065H | 6.5m |
| 1200878985 | 443030H08M065 | 6.5m |
| 1200878986 | 443030H08M075H | 7.5m |
| 1200878626 | 443030H08M080 | 8m |
| 1200879050 | 443030H08M080H | 8m |
| 1200878978 | 443030H08M100 | 10m |
| 1200879081 | 443030H08M120 | 12m |
| 1200879082 | 443030H08M140 | 14m |
| 1200879083 | 443030H08M160 | 16m |
| 1200879084 | 443030H08M180 | 18m |
| 1200879085 | 443030H08M200 | 20m |
| 1200879086 | 443030H08M220 | 22m |
| 1200879087 | 443030H08M240 | 24m |

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 4P CABLE H08 | | |
| 1200878124 | 444030H08M003 | 0.3m |
| 1200878997 | 444030H08M003H | 0.3m |
| 1200878951 | 444030H08C350 | 0.35m |
| 1200878559 | 444030H08M006 | 0.6m |
| 1200879007 | 444030H08M006H | 0.6m |
| 1200878952 | 444030H08C750 | 0.75m |
| 1200878495 | 444030H08M010 | 1m |
| 1200879004 | 444030H08M010H | 1m |
| 1200878987 | 444030H08M015H | 1.5m |
| 1200878356 | 444030H08M020 | 2m |
| 1200879003 | 444030H08M020H | 2m |
| 1200878988 | 444030H08M025H | 2.5m |
| 1200878941 | 444030H08M030 | 3m |
| 1200879010 | 444030H08M030H | 3m |
| 1200879052 | 444030H08M035H | 3.5m |
| 1200879053 | 444030H08M040H | 4m |
| 1200879100 | 444030H08M045H | 4.5m |
| 1200878509 | 444030H08M050 | 5m |
| 1200879054 | 444030H08M050H | 5m |
| 1200879094 | 444030H08M055H | 5.5m |
| 1200879074 | 444030H08M060H | 6m |
| 1200879095 | 444030H08M065H | 6.5m |
| 1200879096 | 444030H08M070H | 7m |
| 1200879103 | 443030H08M070H | 7m |
| 1200879097 | 444030H08M075H | 7.5m |
| 1200879098 | 444030H08M080H | 8m |
| 1200878843 | 444030H08M100 | 10m |
| 1200878844 | 444030H08M250 | 25m |
| 5P CABLE H08 | | |
| 1200878847 | 445030H08M006 | 0.6m |
| 1200271413 | 445030H08M010 | 1m |
| 1200878946 | 445030H08M020 | 2m |
| 1200878980 | 445030H08M030 | 3m |
| 1200878627 | 445030H08M040 | 4m |
| 1200878947 | 445030H08M050 | 5m |

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 3P CABLE E02 | | |
| 1200878272 | 443030E02M002G | 0.2m |
| 1200878273 | 443030E02M003 | 0.3m |
| 1200878576 | 443030E02M003H | 0.3m |
| 1200878809 | 443030E02M0039H | 0.3m |
| 1200875035 | 443030E02M006 | 0.6m |
| 1200878538 | 443030E02M006Y | 0.6m |
| 1200878642 | 443030E02M006H | 0.6m |
| 1200878258 | 443030E02M010 | 1m |
| 1200878643 | 443030E02M010H | 1m |
| 1200878280 | 443030E02M010G | 1m |
| 1200878541 | 443030E02M010Y | 1m |
| 1200878281 | 443030E02M012G | 1.2m |
| 1200878274 | 443030E02M015 | 1.5m |
| 1200878689 | 443030E02M015H | 1.5m |
| 1200878850 | 443030E02M0159H | 1.5m |
| 1200280321 | 443030E02M020 | 2m |
| 1200878535 | 443030E02M020Y | 2m |
| 1200878644 | 443030E02M020H | 2m |
| 1200281282 | 443030E02M025 | 2.5m |
| 1200878275 | 443030E02M025H | 2.5m |
| 1200280343 | 443030E02M030 | 3m |
| 1200878645 | 443030E02M030H | 3m |
| 1200280464 | 443030E02M040 | 4m |
| 1200878537 | 443030E02M040Y | 4m |
| 1200878655 | 443030E02M040H | 4m |
| 1200280462 | 443030E02M050 | 5m |
| 1200878536 | 443030E02M050Y | 5m |
| 1200878276 | 443030E02M050H | 5m |
| 1200878277 | 443030E02M060 | 6m |
| 1200878663 | 443030E02M060H | 6m |
| 1200878494 | 443030E02M070 | 7m |
| 1200878635 | 443030E02M080 | 8m |
| 1200878671 | 443030E02M080H | 8m |
| 1200878278 | 443030E02M100 | 10m |
| 1200878834 | 443030E02M1009H | 10m |
| 1200878279 | 443030E02M150 | 15m |
| 1200878923 | 443030E02M1509H | 15m |

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 4P CABLE E02 | | |
| 1200878346 | 444030E02M003 | 0.3m |
| 1200878574 | 444030E02M003H | 0.3m |
| 1200878347 | 444030E02M005 | 0.5m |
| 1200878665 | 444030E02M005H | 0.5m |
| 1200878348 | 444030E02M006 | 0.6m |
| 1200878577 | 444030E02M006H | 0.6m |
| 1200878810 | 444030E02M0069H | 0.6m |
| 1200878349 | 444030E02M010 | 1m |
| 1200878692 | 444030E02M010H | 1m |
| 1200878828 | 444030E02M0109H | 1m |
| 1200281284 | 444030E02M015 | 1.5m |
| 1200878661 | 444030E02M015H | 1.5m |
| 1200878350 | 444030E02M020 | 2m |
| 1200878693 | 444030E02M020H | 2m |
| 1200878351 | 444030E02M025 | 2.5m |
| 1200878666 | 444030E02M025H | 2.5m |
| 1200878352 | 444030E02M030 | 3m |
| 1200878575 | 444030E02M030H | 3m |
| 1200878811 | 444030E02M0309H | 3m |
| 1200878353 | 444030E02M040 | 4m |
| 1200878354 | 444030E02M050 | 5m |
| 1200878355 | 444030E02M100 | 10m |
| 1200878161 | 444030E02M200 | 20m |
| 1200878658 | 444030E02M250 | 25m |
| 5P CABLE E02 | | |
| 1200878239 | 445030E02M006 | 0.6m |
| 1200878950 | 445030E02M010 | 1m |
| 1200878240 | 445030E02M020 | 2m |
| 1200878241 | 445030E02M050 | 5m |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| DIMENSION UNITS | SCALE |
|---|---|
| mm | 2:1 |

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | | |
|---|---|---|
| ANGULAR TOL | ± | 1.0 ° |
| 4 PLACES | ± | |
| 3 PLACES | ± | |
| 2 PLACES | ± | 0.05 |
| 1 PLACE | ± | 0.3 |
| 0 PLACES | ± | 0.5 |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: REMOVED OBSOLETED PART NUMBERS AS PER PCN#517104

EC NO: 836952
DRWN: SAMPRS 2025/10/11
CHK'D: GGA 2025/10/16
APPR: GGA 2025/10/16

INITIAL REVISION:
DRWN: JMARSZALEK 2016/09/15
APPR: RSILLER 2017/01/11

molex

CSE M8 M8 XP AC BC FE STR MA STR XM

PRODUCT CUSTOMER DRAWING

| DOCUMENT NUMBER | DOC TYPE | DOC PART | REVISION |
|---|---|---|---|
| 1200878240 | PSD | 000 | A20 |

| THIRD ANGLE PROJECTION | DRAWING | SERIES | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
|---|---|---|---|---|---|
| | A3-SIZE | 120087 | SEE PART LIST | GENERAL MARKET | 3 OF 4 |

| DOCUMENT STATUS | P1 | RELEASE DATE | 2025/10/16 19:09:04 |
|---|---|---|---|

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01

# PART LIST

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 3P CABLE P02 | | |
| 1200878292 | 443030P02M003 | 0.3m |
| 1200878141 | 443030P02M006 | 0.6m |
| 1200878140 | 443030P02M010 | 1m |
| 1200878596 | 443030P02M010H | 1m |
| 1200878293 | 443030P02M015 | 1.5m |
| 1200878294 | 443030P02M020 | 2m |
| 1200878295 | 443030P02M025 | 2.5m |
| 1200878296 | 443030P02M030 | 3m |
| 1200878297 | 443030P02M030G | 3m |
| 1200878298 | 443030P02M035 | 3.5m |
| 1200878299 | 443030P02M040 | 4m |
| 1200878233 | 443030P02M050 | 5m |
| 1200878300 | 443030P02M060 | 6m |
| 1200878301 | 443030P02M070 | 7m |
| 1200878234 | 443030P02M100 | 10m |
| 1200878302 | 443030P02M150 | 15m |
| 4P CABLE P02 | | |
| 1200878357 | 444030P02M003 | 0.3m |
| 1200878358 | 444030P02M006 | 0.6m |
| 1200878359 | 444030P02M010 | 1m |
| 1200878360 | 444030P02M020 | 2m |
| 1200878361 | 444030P02M030 | 3m |
| 1200878362 | 444030P02M050 | 5m |
| 1200878812 | 444030P02M100 | 10m |
| 5P CABLE P02 | | |
| 1200870687 | 445030P02M006 | 0.6m |
| 1200281309 | 445030P02M010 | 1m |
| 1200878035 | 445030P02M020 | 2m |
| 1200870688 | 445030P02M030 | 3m |
| 1200878036 | 445030P02M040 | 4m |
| 1200281310 | 445030P02M050 | 5m |
| 1200878037 | 445030P02M100 | 10m |
| 1200878139 | 445030P02M250 | 25m |

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 3P CABLE I02 | | |
| 1200878282 | 443030I02M003 | 0.3m |
| 1200280384 | 443030I02M006 | 0.6m |
| 1200280427 | 443030I02M010 | 1m |
| 1200878283 | 443030I02M015 | 1.5m |
| 1200878284 | 443030I02M020 | 2m |
| 1200878285 | 443030I02M030 | 3m |
| 1200878286 | 443030I02M040 | 4m |
| 1200878287 | 443030I02M050 | 5m |
| 1200878288 | 443030I02M060 | 6m |
| 1200878289 | 443030I02M070 | 7m |
| 1200878290 | 443030I02M100 | 10m |
| 1200878291 | 443030I02M150 | 15m |

| MOLEX P/N | ENGINEERING No. | L[m] |
|---|---|---|
| 5P CABLE H70 | | |
| 1200888155 | 445030H70M020 | 2m |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| DIMENSION UNITS | SCALE |
|---|---|
| mm | 1:1 |

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | | |
|---|---|---|
| ANGULAR TOL | ± | 1.0 ° |
| 4 PLACES | ± | |
| 3 PLACES | ± | |
| 2 PLACES | ± | 0.05 |
| 1 PLACE | ± | 0.3 |
| 0 PLACES | ± | 0.5 |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: REMOVED OBSOLETED PART NUMBERS AS PER PCN#517104

EC NO: 836952
DRWN: SAMPRS 2025/10/11
CHK'D: GGA 2025/10/16
APPR: GGA 2025/10/16

INITIAL REVISION:
DRWN: JMARSZALEK 2016/09/15
APPR: RSILLER 2017/01/11

molex

CSE M8 M8 XP AC BC FE STR MA STR XM


PRODUCT CUSTOMER DRAWING

| DOCUMENT NUMBER | DOC TYPE | DOC PART | REVISION |
|---|---|---|---|
| 1200878240 | PSD | 000 | A20 |







| THIRD ANGLE PROJECTION | DRAWING | SERIES | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
|---|---|---|---|---|---|
| | A3-SIZE | 120087 | SEE PART LIST | GENERAL MARKET | 4 OF 4 |


| DOCUMENT STATUS | P1 | RELEASE DATE | 2025/10/16 19:09:04 |
|---|---|---|---|

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01





| | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| ENTER DESCRIPTION<br>EC NO: WEU2012-0001<br>DRWN:RSCHIEBER 2011/07/06<br>CHKD:REISSNER 2011/07/13<br>APPR:CBURGER 2011/07/20<br>DESCRIPTION | QUALITY SYMBOLS<br>▼=0<br>▽C=0 | GENERAL TOLERANCES (UNLESS SPECIFIED)<br>mm / INCH<br>4 PLACES ± --- / ± ---<br>3 PLACES ± --- / ± ---<br>2 PLACES ± --- / ± .01<br>1 PLACE ± 0.3 / ± ---<br>ANGULAR ±1/2°<br>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | DIMENSION STYLE<br>IN/MM | SCALE<br>4:1 | DESIGN UNITS<br>INCH | THIRD ANGLE PROJECTION | | | | | | |
| REV<br>B | | | DRAWN BY BWOODMAN DATE 18/08/09<br>CHECKED BY RSTONE DATE 18/08/09<br>APPROVED BY JFMURPHY DATE 18/08/09<br>MATERIAL NO. SEE SHEET 3 | TITLE<br>CSE M8 XP MA FE STR<br>PUR PVC UN<br>molex MOLEX INCORPORATED<br>DOCUMENT NO. SD-120028-001<br>SHEET NO. 1 OF 3 | | | | | | | | |
| | | | SIZE C | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | | | |


| FEMALE INSERT FRONT VIEW | | | MALE INSERT FRONT VIEW | | |
|---|---|---|---|---|---|
| 3 POLE | 4 POLE | 5 POLE | 3 POLE | 4 POLE | 5 POLE |
|  |  |  |  |  |  |
| 1 BROWN<br>3 BLUE<br>4 BLACK | 1 BROWN<br>2 WHITE<br>3 BLUE<br>4 BLACK | 1 BROWN<br>2 WHITE<br>3 BLUE<br>4 BLACK<br>5 GREY | 1 BROWN<br>3 BLUE<br>4 BLACK | 1 BROWN<br>2 WHITE<br>3 BLUE<br>4 BLACK | 1 BROWN<br>2 WHITE<br>3 BLUE<br>4 BLACK<br>5 GREY |




SEC Y-Y




SEC Z-Z




SECTION Z-Z
FOR 4-5 PLOE ONLY
[4 POLE SHOWN]

ENTER DESCRIPTION
EC NO: WEU2012-0001
DRWN:RSCHIEBER 2011/07/06
CH'KD:RETISSNER 2011/07/13
APPR:CBURGER 2011/07/20
DESCRIPTION
B
REV

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | mm | INCH |
|---|---|---|
| 4 PLACES | ± --- | ± --- |
| 3 PLACES | ± --- | ± --- |
| 2 PLACES | ± --- | ± .01 |
| 1 PLACE | ± 0.3 | ± --- |
| ANGULAR ±1/2° | | |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: IN/MM
SCALE: 5:1
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

| | | |
|---|---|---|
| DRAWN BY | BWOODMAN | DATE 18/08/09 |
| CHECKED BY | RSTONE | DATE 18/08/09 |
| APPROVED BY | JFMURPHY | DATE 18/08/09 |

TITLE: CSE M8 XP MA FE STR PUR PVC UN

MOLEX INCORPORATED

MATERIAL NO.: SEE SHEET 3
DOCUMENT NO.: SD-120028-001
SHEET NO.: 2 OF 3
SIZE: C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| PART NUMBER | DESCRIPTION | FINISHED LENGTH | MATERIAL |
|---|---|---|---|
| 1200878141 | 443030P02M006 | 0.6M +45MM -0 [1' 11" +1.8" -0] | PUR |
| 1200878140 | 443030P02M010 | 1M +56MM -0 [3' 3" +2.2" -0] | PUR |
| 1200878293 | 443030P02M015 | 1.5M +56MM -0 [4' 11" +2.2" -0] | PUR |
| 1200878294 | 443030P02M020 | 2M +90MM -0 [6' 6" +3.5" -0] | PUR |
| 1200878296 | 443030P02M030 | 3M +90MM -0 [9' 10" +3.5" -0] | PUR |
| 1200878299 | 443030P02M040 | 4M +150MM -0 [13' 1" +6" -0] | PUR |
| 1200878233 | 443030P02M050 | 5M +150MM -0 [16' 4" +6" -0] | PUR |
| 1200878358 | 444030P02M006 | 0.6M +45MM -0 [1' 11" +1.8" -0] | PUR |
| 1200878359 | 444030P02M010 | 1M +56MM -0 [3' 3" +2.2" -0] | PUR |
| 1200878360 | 444030P02M020 | 2M +90MM -0 [6' 6" +3.5" -0] | PUR |
| 1200878361 | 444030P02M030 | 3M +90MM -0 [9' 10" +3.5" -0] | PUR |
| 1200870686 | 444030P02M040 | 4M +150MM -0 [13' 1" +6" -0] | PUR |
| 1200878362 | 444030P02M050 | 5M +150MM -0 [16' 4" +6" -0] | PUR |
| 1200870687 | 445030P02M006 | 0.6M +45MM -0 [1' 11" +1.8" -0] | PUR |
| 1200281309 | 445030P02M010 | 1M +56MM -0 [3' 3" +2.2" -0] | PUR |
| 1200878035 | 445030P02M020 | 2M +90MM -0 [6' 6" +3.5" -0] | PUR |
| 1200870688 | 445030P02M030 | 3M +90MM -0 [9' 10" +3.5" -0] | PUR |
| 1200878036 | 445030P02M040 | 4M +150MM -0 [13' 1" +6" -0] | PUR |
| 1200281310 | 445030P02M050 | 5M +150MM -0 [16' 4" +6" -0] | PUR |
| 1200875035 | 443030E02M006 | 0.6M +45MM -0 [1' 11" +1.8" -0] | PVC |
| 1200878274 | 443030E02M015 | 1.5M +56MM -0 [4' 11" +2.2" -0] | PVC |
| 1200280462 | 443030E02M050 | 5M +150MM -0 [16' 4" +6" -0] | PVC |

| | | | | FEMALE INSERT ASSEMBLY | | | MALE INSERT ASSEMBLY | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | | 3 POLE | 4 POLE | 5 POLE | 3 POLE | 4 POLE | 5 POLE |
| SL.No | DESCRIPTION | MATERIAL | FINISH | QTY | | | QTY | | |
| 1 | CONTACT SOCKET | COPPER ALLOY | GOLD PLATED | 3 | 4 | 5 | | | |
| 2 | O-RING | VITON | RED | 1 | 1 | 1 | | | |
| 3 | COUPLING NUT | BRASS | NICKEL PLATED | | | | | | |
| 4 | LABEL | PLASTIC FILM | BLACK/YELLOW | 1 | 1 | 1 | 1 | 1 | 1 |
| 5 | OVER MOLD | TPE | YELLOW | | | | | | |
| 6 | CABLE, 24 AWG, 3 CONDUCTOR | PUR JACKET | BLACK | 1 | | | 1 | | |
| | CABLE, 24 AWG, 3 CONDUCTOR | PVC JACKET | BLACK | 1 | | | 1 | | |
| | CABLE, 24 AWG, 4 CONDUCTOR | PUR JACKET | BLACK | | 1 | | | 1 | |
| | CABLE, 24 AWG, 5 CONDUCTOR | PUR JACKET | BLACK | | | 1 | | | 1 |
| 7 | INSERT FEMALE 3 POLE | PUR | BLACK | 1 | | | | | |
| | INSERT FEMALE 4 POLE | PUR | BLACK | | 1 | | | | |
| | INSERT FEMALE 5 POLE | PUR | BLACK | | | 1 | | | |
| 8 | STAMP & FORM CONTACT | COPPER ALLOY | GOLD PLATED | | | | 3 | | |
| 9 | SCREW MACHINE CONTACT | COPPER ALLOY | GOLD PLATED | | | | | 4 | 5 |
| 10 | SLEEVE | BRASS | NICKEL PLATED | | | | 1 | 1 | 1 |
| 11 | COUPLING NUT | BRASS | NICKEL PLATED | | | | 1 | 1 | 1 |
| 12 | INSERT MALE 3 POLE | PUR | BLACK | | | | 1 | | |
| | INSERT MALE 4 POLE | PUR | BLACK | | | | | 1 | |
| | INSERT MALE 5 POLE | PUR | BLACK | | | | | | 1 |

| SPECIFICATION |
|---|
| Protection Class - IP67 |
| Voltage Rating - 3 Pole/60V, 4+5 Pole/30V |
| Contact Current Rating - 3 Amps |
| Wires: 0.25mm² PVC/PUR |

ENTER DESCRIPTION
EC NO: WEU2012-0001 2011/07/06
DRWN:RSCHIEBER 2011/07/13
CH'KD:RETISSNER 2011/07/20
APPR:CBURGER
DESCRIPTION
B
REV

QUALITY SYMBOLS
▼=0
Ⓒ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | mm | INCH |
|---|---|---|
| 4 PLACES | ± --- | ± --- |
| 3 PLACES | ± --- | ± --- |
| 2 PLACES | ± --- | ± .01 |
| 1 PLACE | ± 0.3 | ± --- |
| ANGULAR ±1/2° | | |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: IN/MM
SCALE: 5:1
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

| | | |
|---|---|---|
| DRAWN BY | BWOODMAN | DATE 18/08/09 |
| CHECKED BY | RSTONE | DATE 18/08/09 |
| APPROVED BY | JFMURPHY | DATE 18/08/09 |

TITLE: CSE M8 XP MA FE STR PUR PVC UN

molex MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-120028-001
SHEET NO.: 3 OF 3
SIZE: C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION