

## Specification Sheet

Part Number: T18RWPM9M4

Easy and quick insertion ideal for production environment.

Tie "clicks" into place upon final installation signaling installer insertion is complete.

Arrowhead style mount provides low insertion and high extraction force.



1-Piece Cable Tie with Arrowhead Mount with Wings, 4.5"L, 18lb, 0.19 - 0.22" Mtg Hole, PA66, Natural, 1000/pkg

|                |           |
|----------------|-----------|
| Article Number | 126-00603 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | T18RWPM |
|------|---------|

|       |              |
|-------|--------------|
| Color | Natural (NA) |
|-------|--------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | <p>Wing design helps stabilize the tie in high vibration applications.</p> <p>One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution.</p> <p>HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.</p> |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------|
| Short Description | 1-Piece Cable Tie with Arrowhead Mount with Wings, 4.5"L, 18lb, 0.19 - 0.22" Mtg Hole, PA66, Natural, 1000/pkg |
|-------------------|----------------------------------------------------------------------------------------------------------------|

|                  |                 |
|------------------|-----------------|
| Global Part Name | T18RWPM-PA66-NA |
|------------------|-----------------|

|                                     |    |
|-------------------------------------|----|
| Minimum Tensile Strength (Imperial) | 18 |
|-------------------------------------|----|

|                                   |    |
|-----------------------------------|----|
| Minimum Tensile Strength (Metric) | 80 |
|-----------------------------------|----|

|                     |     |
|---------------------|-----|
| Length L (Imperial) | 4.5 |
|---------------------|-----|

|                   |       |
|-------------------|-------|
| Length L (Metric) | 113.0 |
|-------------------|-------|

|                 |           |
|-----------------|-----------|
| Fixation Method | Arrowhead |
|-----------------|-----------|

|                               |      |
|-------------------------------|------|
| Identification Plate Position | none |
|-------------------------------|------|

|                    |    |
|--------------------|----|
| Releasable Closure | No |
|--------------------|----|

|             |              |
|-------------|--------------|
| Tie Closure | plastic pawl |
|-------------|--------------|

|         |                 |
|---------|-----------------|
| Variant | Inside Serrated |
|---------|-----------------|

|                    |     |
|--------------------|-----|
| Width W (Imperial) | 0.1 |
|--------------------|-----|

|                  |     |
|------------------|-----|
| Width W (Metric) | 2.5 |
|------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Min (Imperial) | 0.06 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Min (Metric) | 1.5 |
|------------------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Max (Imperial) | 0.87 |
|--------------------------------|------|

|                              |      |
|------------------------------|------|
| Bundle Diameter Max (Metric) | 22.0 |
|------------------------------|------|

|                                         |               |
|-----------------------------------------|---------------|
| Thickness T (Imperial)                  | 0.043         |
| Thickness T (Metric)                    | 1.1           |
| Height H (Imperial)                     | .23           |
| Height H (Metric)                       | 5.80          |
| Panel Thickness Min (Imperial)          | 0.06          |
| Panel Thickness Max (Imperial)          | 0.13          |
| Panel Thickness Min (Metric)            | 1.52          |
| Panel Thickness Max (Metric)            | 3.2           |
| Mounting Hole Diameter D (Imperial)     | 0.19 - 0.22 " |
| Mounting Hole Diameter D (Metric)       | 4.8 - 5.6 mm  |
| Mounting Hole Diameter D Min (Imperial) | 0.19          |
| Mounting Hole Diameter D Max (Imperial) | 0.22          |
| Mounting Hole Diameter D Max (Metric)   | 5.6           |
| Disc Diameter (Metric)                  | 13.1          |
| Disc Diameter (Imperial)                | 0.5           |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material                      | Polyamide 6.6 (PA66)             |
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| UV Resistant (Yes/No)         | No                               |
| Use Conditions                | For Indoor Use Only              |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL-ZODZ2.E64139                  |
| UL Recognized (US)            | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| Package Quantity (Imperial)   | 1000                             |
| Package Quantity (Metric)     | 1000                             |
| Customs Number                | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)