

126-03504

HellermannTyton

Article Number: 126-03504

Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 8"L, .25"—.28" Mounting Hole, PA66HIRHS, Gray, 1000/pkg



Base Data		
	Local Order Number	T50RTM25E8HM4
	Type	T50RTM25E
	Color	Gray (GY)
	Features and benefits	• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
	Quantity Per	bag
	Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
	GLOBAL PART NAME (auto set)	T50RTM25E-PA66HIRHS-GY
	Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 8"L, .25"—.28" Mounting Hole, PA66HIRHS, Gray, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	222N
	Length L (Imperial)	8.0"
	Length L (Metric)	203.2mm
	Fixation Method	Fir Tree
	Identification Plate Position	none
	Releasable Closure	Yes
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.19"
	Width W (Metric)	4.7mm
	Bundle Diameter Min. (Imperial)	0.06"

126-03504



Product Dimensions	Bundle Diameter Min. (Metric)	1.6mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.8mm
	Disc Diameter (Imperial)	0.5"
	Disc Diameter (Metric)	12.6mm
	Panel Thickness Max. (Imperial)	0.5"
	Panel Thickness Max. (Metric)	13.9mm
	Panel Thickness Min. (Imperial)	0.09"
	Panel Thickness Min. (Metric)	2.3mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.28"
	Mounting Hole Diameter D (Metric)	6.35 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.28"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +212°F (-40°C to +100°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987