

156-00264

HellermannTyton

Article Number: 156-00264



Description: Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag

Base Data		
	Local Order Number	156-00264
	Type	T50SOSSFT6.5E-MDL
	Color	Black (BK)
	Features and benefits	• Arrowhead design makes installation quick and easy by hand. • Ties "clicks" into place upon final installation signaling installer insertion is complete. • Design provides low insertion and high extraction force.
	Quantity Per	bag
	Product Description	Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.
	GLOBAL PART NAME (auto set)	T50SOSSFT6.5E-MDL-PA66HS-BK
	Short Description	Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag
Product Dimensions		
	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	6.3"
	Length L (Metric)	158.8mm
	Fixation Method	Arrowhead
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Outside Serrated
	Width W (Imperial)	0.18"
	Width W (Metric)	4.6mm
	Height H (Imperial)	0.67"
	Bundle Diameter Min. (Imperial)	0.06"

156-00264



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.2"
	Bundle Diameter Max. (Metric)	30.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.07"
	Panel Thickness Max. (Metric)	1.8mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.26"
	Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.26"
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	4000
	Package Quantity (Metric)	4000Pieces
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	1.51kg