
DAISY-MINI-WW

~65° wide beam



SPECIFICATION:

Dimensions	x
Height	0 mm
Fastening	pin, screw, snaps
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
DAISY-MINI-WW	Linear lens	PMMA	clear		
DAISY-MINI-SHD	Shade	PC	black	gloss	
DAISY-MINI-SHD-WHT	Shade	PC	white	gloss	
DAISY-MINI-SHD-MATT	Shade	PC	black	matt	
DAISY-MINI-SHD-WHT-MATT	Shade	PC	white	matt	
DAISY-MINI-SHD-MET	Shade	PC	metal	gloss	
DAISY-MINI-SHD-MET-MATT	Shade	PC	metal	matt	

ORDERING INFORMATION:


Quantities for one set:

Linear lens	1
Shade	1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Component		Qty in box	MOQ	MPQ	Box weight (kg)
F17031_DAISY-MINI-WW » Box size: 398 x 298 x 265 mm	Linear lens	252	252	12	5.9
F17666_DAISY-MINI-SHD-MET » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9
F17667_DAISY-MINI-SHD-MET-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.2
F17033_DAISY-MINI-SHD-WHT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9
F17034_DAISY-MINI-SHD-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.1
F17465_DAISY-MINI-SHD-WHT-MATT » Box size: 398 x 298 x 265 mm	Shade	252	252	4	6.2
F17028_DAISY-MINI-SHD » Box size: 398 x 298 x 265 mm	Shade	252	252	4	5.9

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	J Series 2835
FWHM / FWTM	63.0° / 76.0°
Efficiency	89 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F17667_DAISY-MINI-SHD-MET-MATT






Light distribution files

mal

LED	Opticus Daisy Mini M L28W2
FWHM / FWTM	63.0° / 74.0°
Efficiency	80 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F17034_DAISY-MINI-SHD-MATT






Light distribution files

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	62.0° / 85.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17033_DAISY-MINI-SHD-WHT





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	61.0° / 84.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17465_DAISY-MINI-SHD-WHT-MATT






Light distribution files

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	62.0° / 85.0°
Efficiency	90 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17667_DAISY-MINI-SHD-MET-MATT






Light distribution files

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	61.0° / 82.0°
Efficiency	78 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17028_DAISY-MINI-SHD





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	60.0° / 82.0°
Efficiency	78 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17034_DAISY-MINI-SHD-MATT






Light distribution files

MST Your solutions

LED	LinLED 280x20mm 1100lm 8x0 2C 42V Opt G1
FWHM / FWTM	63.0° / 84.0°
Efficiency	91 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17666_DAISY-MINI-SHD-MET






Light distribution files

seitec

LED	LED-St-L28W2-840-C010-06 (Daisy-Mini)
FWHM / FWTM	60.0° / 87.0°
Efficiency	69 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17028_DAISY-MINI-SHD





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SEITEC

LED	LED-St-L28W2-927-C010-965-C010-07 (Daisy-Mini)
FWHM / FWTM	60.0° / 86.0°
Efficiency	70 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	Tunable White
Required components:	
F17028_DAISY-MINI-SHD	






Light distribution files

TRIDONIC

LED	LLE 20x280mm 750lm 827-865 LV MD ADV1
FWHM / FWTM	60.0° / 82.0°
Efficiency	80 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	Tunable White
Required components:	
F17028_DAISY-MINI-SHD	






Light distribution files

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	63.0° / 94.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17667_DAISY-MINI-SHD-MET-MATT	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	59.0° / 82.0°
Efficiency	79 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17028_DAISY-MINI-SHD






Light distribution files

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	60.0° / 86.0°
Efficiency	69 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17034_DAISY-MINI-SHD-MATT






Light distribution files

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	65.0° / 92.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17666_DAISY-MINI-SHD-MET





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	62.0° / 93.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17033_DAISY-MINI-SHD-WHT






Light distribution files

TRIDONIC

LED	LLE 20x280mm 750lm 840 LV MD ADV1
FWHM / FWTM	62.0° / 92.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
F17465_DAISY-MINI-SHD-WHT-MATT






Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs


LED	J Series 2835
FWHM / FWTM	70.0° / 88.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs


LED	XQ-E HI
FWHM / FWTM	66.0° / 76.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17034_DAISY-MINI-SHD-MATT	



Light distribution files

CREE LEDs

LED	XQ-E HI
FWHM / FWTM	68.0° / 76.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17666_DAISY-MINI-SHD-MET	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS


LED	LUXEON 2835 Architectural
FWHM / FWTM	57.0° / 84.0°
Efficiency	83 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17034_DAISY-MINI-SHD-MATT	



Light distribution files

LUMILEDS


LED	LUXEON 5050 HE
FWHM / FWTM	64.0° / 84.0°
Efficiency	90 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17033_DAISY-MINI-SHD-WHT	



Light distribution files

LUMILEDS

LED	LUXEON 5050 HE
FWHM / FWTM	62.0° / 82.0°
Efficiency	82 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS


LED	LUXEON 5050 HE
FWHM / FWTM	62.0° / 82.0°
Efficiency	83 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17034_DAISY-MINI-SHD-MATT	



Light distribution files

LUMILEDS


LED	LUXEON HL1Z (White)
FWHM / FWTM	60.0° / 70.0°
Efficiency	83 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	66.0° / 78.0°
Efficiency	85 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	Tunable White
Required components:	
F17034_DAISY-MINI-SHD-MATT	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA


LED	NFSWE11A
FWHM / FWTM	58.0° / 74.0°
Efficiency	77 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

NICHIA


LED	NFSx757G
FWHM / FWTM	64.0° / 76.0°
Efficiency	85 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

NICHIA

LED	NFSx757G
FWHM / FWTM	64.0° / 78.0°
Efficiency	90 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17666_DAISY-MINI-SHD-MET	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA


LED	NFSx757G
FWHM / FWTM	64.0° / 78.0°
Efficiency	92 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17033_DAISY-MINI-SHD-WHT	



Light distribution files

OSRAM


LED	Duris E 2835
FWHM / FWTM	64.0° / 78.0°
Efficiency	92 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

OSRAM

LED	OSCONIQ E 3030 (GW QSLPS1.EM)
FWHM / FWTM	62.0° / 74.0°
Efficiency	84 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LM28xB Series
FWHM / FWTM	76.0° / 93.0°
Efficiency	70 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17034_DAISY-MINI-SHD-MATT	



Light distribution files

SAMSUNG


LED	LM28xB Series
FWHM / FWTM	76.0° / 94.0°
Efficiency	77 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17667_DAISY-MINI-SHD-MET-MATT	



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	76.0° / 97.0°
Efficiency	79 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17465_DAISY-MINI-SHD-WHT-MATT	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LM28xB Series
FWHM / FWTM	76.0° / 94.0°
Efficiency	79 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17033_DAISY-MINI-SHD-WHT	



Light distribution files

SAMSUNG


LED	LM28xB Series
FWHM / FWTM	76.0° / 93.0°
Efficiency	70 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	76.0° / 94.0°
Efficiency	77 %
Peak intensity	0.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
F17666_DAISY-MINI-SHD-MET	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LM302D
FWHM / FWTM	64.0° / 76.0°
Efficiency	89 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17465_DAISY-MINI-SHD-WHT-MATT	



Light distribution files


SAMSUNG

LED	LM302D
FWHM / FWTM	64.0° / 76.0°
Efficiency	83 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

LED	SEOUL 3030
FWHM / FWTM	66.0° / 78.0°
Efficiency	85 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17028_DAISY-MINI-SHD	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.