


## PCB terminal block - ZFKDSA 1,5C-5,0-12 - 1729292

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

PCB terminal block, Nominal current: 16 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 12, Connection method: Spring-cage connection, Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: green



The illustration shows the 10-position version

### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Minimum order quantity               | 50 pc     |
| Weight per Piece (excluding packing) | 11.56 GRM |
| Custom tariff number                 | 85369010  |
| Country of origin                    | Poland    |

### Technical data

#### Dimensions

|                |           |
|----------------|-----------|
| Length         | 14.1 mm   |
| Pitch          | 5 mm      |
| Dimension a    | 55 mm     |
| Pin dimensions | 0,7 x 0,7 |
| Pin spacing    | 5.08 mm   |
| Hole diameter  | 1.1 mm    |

#### General

|                             |               |
|-----------------------------|---------------|
| Range of articles           | ZFKDS(A) 1,5C |
| Insulating material group   | I             |
| Rated surge voltage (III/3) | 4 kV          |
| Rated surge voltage (III/2) | 4 kV          |
| Rated surge voltage (II/2)  | 4 kV          |
| Rated voltage (III/3)       | 250 V         |
| Rated voltage (III/2)       | 400 V         |
| Rated voltage (II/2)        | 630 V         |

## PCB terminal block - ZFKDSA 1,5C-5,0-12 - 1729292

### Technical data

#### General

|                                         |                     |
|-----------------------------------------|---------------------|
| Connection in acc. with standard        | EN-VDE              |
| Nominal current $I_N$                   | 16 A                |
| Nominal cross section                   | 1.5 mm <sup>2</sup> |
| Maximum load current                    | 16 A                |
| Insulating material                     | PA                  |
| Solder pin surface                      | Sn                  |
| Inflammability class according to UL 94 | V0                  |
| Internal cylindrical gage               | A 1                 |
| Stripping length                        | 7 mm                |
| Number of positions                     | 12                  |

#### Connection data

|                                                     |                      |
|-----------------------------------------------------|----------------------|
| Conductor cross section AWG/kcmil min.              | 24                   |
| Conductor cross section AWG/kcmil max               | 14                   |
| 2 conductors with same cross section, stranded min. | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max. | 0.5 mm <sup>2</sup>  |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141109 |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121432 |

## PCB terminal block - ZFKDSA 1,5C-5,0-12 - 1729292

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39121432 |
|-------------|----------|