SL2X2

Article number: 181-22019



Images (6)

Certifications & Approvals

RoHS



Base Data

Colour	Black (BK)
GLOBAL PART DESCRIPTION	SL2X2-PVC-BK
Pack Cont.	9.14 m
Package Quantity per	box

Product Dimensions

Fixing Hole Centres (F)	4.0 "
Fixing Hole Centres (F)	101.6 mm
Height (H)	52.6 mm
Length (L)	1.83 m
Width (W)	50.8 mm
Width (W2)	50.8 mm
Width (W3)	10.2 mm
Width (W4)	1.0 "
Width (W4)	25.4 mm
Width (W5)	40.6 mm
Width (W5)	1.6 "
Width (W6)	12.7 mm

Width (W6)	0.5 "

Material and Specifications

CSA Certified	Yes
Flammability	self-extinguishing
Halogenfree	No
Material	Polyvinylchloride (PVC)
Operating Temperature - °C	+50 °C
Specifications	RoHS
Specifications	CSA, EN 50085-1:2005 + A1:2013, EN 50085-2-3_1A, UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes
UL-File Number	E64139

More Information

ETIM 5.0	EC000012
ETIM 6.0	EC000012
UNSPSC Key	39131712

Competences



Wiring ducts and accessories from HelaDuct: optimum protection for cables and fitters.

Discover the advantages of HelaDuct wiring ducts system solutions with its special space-saving shapes: these unique wiring ducts are designed for height and give you more lateral space. They come with blunted edges that protect the cable insulation and make them safer to work with during installation and maintenance. HelaDuct products are used in switch cabinets and switching stations and are very well suited to cables with small cross sections.

Wiring ducts >

Stay in touch with us!

Cable Tie Guns
Connectivity Products
RFID tracking
Cable tie mounts
Thermal Transfer Printer
P-Clamp
Wiring ducts
Cable clips for edges
Cable management high temperature applications

Events

Update: 25/11/2018

You can easily accept or reject the cookies on this site by choosing one of the following links: I accept cookies I refuse cookies - Privacy statement