



DESCRIPTION: 15 POS - HIGH DENSITY - FEMALE - SLIM - RIGHT ANGLE









MATERIAL/FINISH:

SHELL:	SPCC, NICKEL PLATED
BRACKET:	BRASS, NICKEL PLATED
INSULATOR:	PBT OR PA9T, UL 94V-0, BLACK,
PROCESS TEMP:	230°C for 3 seconds (PBT), 2 CYCLES
	260°C for 5 seconds (PA9T), 2 CYCLES
CONTACT:	BRASS, TIN PLATED
	GOLD PLATED - MATING AREA
	BRIGHT TIN - TERMINATING AREA
BOARDLOCK:	COPPER ALLOY, TIN PLATED
RIVET:	COPPER ALLOY, NICKEL PLATED

ELECTRICAL:

RATED CURRENT:	3 AMPS
RATED VOLTAGE:	250 VAC (rms) MAX.
WITHSTANDING VOLTAGE:	500 VAC (rms) FOR 1 Min.
INSULATION RESISTANCE:	1,000 MOhms MIN.
CONTACT RESISTANCE:	25 mOhms Max.
OPERATING TEMPERATURE:	-55° ~ +85° C
TOTAL MATING FORCE:	6.0 Kgf MAX.
TOTAL UNMATING FORCE:	1.2 Kgf MIN.

200-015-2 1 3LYY Y

- SERIES
- No. of POSITIONS
- GENDER
  - 2 = FEMALE
- TERMINATION
  - 1 = PC MOUNT
- SHELL PLATING
  - 3 = NICKEL
- INSULATOR MATERIAL
  - L = PBT
  - R = PA9T
- HARDWARE OPTIONS
  - SEE PAGE 2
- PLATING OPTIONS
  - 7 = GOLD FLASH (MATING AREA) BRIGHT TIN (SOLDER TAILS)
  - 9 = 30u" GOLD (MATING AREA) BRIGHT TIN (SOLDER TAILS)

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.


DRAWN:	M. SIGMON
DATE:	10/26/2016


NorComp

SCALE: NTS	SHEET 1 OF 2	REV 5
DWG NO. 200-015-213LYYY		

DESCRIPTION: 15 POS - HIGH DENSITY - FEMALE - SLIM - RIGHT ANGLE

HARDWARE OPTIONS





RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: M. SIGMON

DATE: 10/26/2016

NorComp

SCALE: NTS

SHEET 2 OF 2

REV 5

DWG NO. 200-015-213LYYY