Extract from the online catalog

CABLE-D 9SUB/B/B/300/KONFEK/S

Order No.: 2305431



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305431

Assembled, shielded circular cable, with D-SUB socket strip, 9-pos. from both sides, cable length: 3 m

Product notes

WEEE/RoHS-compliant since: 06/05/2008

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

GTIN (EAN)	4 046356 011792
Note	Made-to-order
sales group	I682
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 271 (IF-2009)

Technical data

General

Nominal voltage U_N	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	≤ 0.09 Ω/m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Number of positions	9
Number of positions, control side	9
Number of connectors, control side	1
Number of positions, module side	9
Number of connectors, modul side	1
Fixed cable length	3 m
Single wire, cross section	0.25 mm²
AWG	24
External diameter	7.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Certificates / Approvals

Certification	CUL, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg,Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
http://www.phoenixcontact.de

© 2010 Phoenix Contact
Technical modifications reserved;