Extract from the online catalog

CABLE-D15SUB/S/S/200/KONFEK/S

Order No.: 2305619



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305619

Assembled, shielded circular cable, with D-SUB pin strip, 15-pos. from both sides, cable length: 2m

Commercial data	
GTIN (EAN)	4 046356 011952
Note	Made-to-order
sales group	I682
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 271 (IF-2009)

Product notes

WEEE/RoHS-compliant since: 01/23/2007

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Nominal voltage U_N	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	≤ 0.09 Ω/m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Number of positions	15
Number of positions, control side	15
Number of connectors, control side	1
Number of positions, module side	15
Number of connectors, modul side	1
Fixed cable length	2 m
Single wire, cross section	0.25 mm²
AWG	24
External diameter	9 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Certificates / Approvals

Certification	CUL, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg,Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
http://www.phoenixcontact.de

© 2010 Phoenix Contact
Technical modifications reserved;