

• No protruding head to cause injury since head is inverted
• No protruding tie tip to cause injury since the tip is trapped between the tie and the foam
• Tie will not slip on the foam since the head will indent the foam to remain captive
• Wide tie body .350" (8.9mm) for improved aesthetics
• Cannot over-tension tie causing bulges in the foam
• Install by hand or use *PANDUIT* GTH installation tool
• Flexible and easy to handle
• No need to heat weld the ends closed
• No cutoff scrap pieces to handle or pick up
• Strong: 124 lb. (550N) minimum loop tensile strength
• Locking wedge is protected from unlocking and from ultraviolet light exposure
• Weather Resistant Nylon 6.6 - Available in 13 ultraviolet colors (to match the foam) that will last 2-3 times longer than normal pigmented colors

NOTE: Ties are installed with the teeth on the inside against the foam.

Part Number:	IT9115-CUV6
Product Family:	IN-LINE Cable Ties for Playground Applications
Product Line:	IN-LINE Cable Ties
RoHS Compliancy Status:	Compliant
Part Description:	IN-LINE Cable Tie, 15.3", Light-Heavy cross section
Product Type:	Cable Ties
Material:	Ultraviolet (UV) Resistant Nylon 6.6

Color:	UV Dark Blue
CSA Certified:	No
UL Listed (File #E56854):	No
UL Recognized (File #E56854):	No
Length (In.):	15.3
Length (mm):	389
Width (In.):	.350
Width (mm):	8.9
CE Compliant:	Yes
Cross Section:	Light-Heavy
Head Height (In.):	.300
Head Height (mm):	7.6
Head Width (In.):	.556
Head Width (mm):	14.1
Locking Style:	Locking
Material Flammability Rating:	UL94V-2
Max. Bundle Diameter (In.):	4.53
Max. Bundle Diameter (mm):	115
Max. Continuous Use Temperature:	185°F (85°C)

Min. Loop Tensile Strength (Lbs.):	124
Min. Loop Tensile Strength (N):	550
Std. Pkg. UOM:	PK
Thickness (In.):	.065
Thickness (mm):	1.7
Tool:	Hand Installation Recommended
UOM:	PC
Std. Pkg. Qty.:	100
Min. Order Qty.:	100