
A-series
A2C 35 PE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image



Spring connection with PUSH IN Technology
The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

Type	A2C 35 PE
Order No.	2551520000
Version	PE terminal, PUSH IN, 35 mm², 1000 V, Green/yellow
GTIN (EAN)	4050118680201
Qty.	10 pc(s).

A-series
A2C 35 PE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	16 mm	Width (inches)	0.63 inch
Height	101 mm	Height (inches)	3.976 inch
Depth	71.5 mm	Depth (inches)	2.815 inch
Net weight	109.905 g		

Temperatures

Operating temperature range, max.	130 °C	Operating temperature range, min.	-50 °C
Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-60 °C
Continuous operating temp., max.	130 °C		

Material data

Material	Wemid	Colour	Green/yellow
Colour of operational elements	orange	UL 94 flammability rating	V-0

System specifications

Rail	TS 35

Additional technical data

Type of fixing	TS 35	Type of mounting	TS 35

Conductors for clamping (rated connection)

Clamping range, max.	35 mm²	Clamping range, min.	2.5 mm²
Number of connections	2	Stripping length	18 mm
Twin wire-end ferrules, max.	10 mm²	Twin wire-end ferrules, min.	2.5 mm²
Type of connection	PUSH IN	Wire connection cross section AWG, max.	AWG 2
Wire connection cross section AWG, min.	AWG 12	Wire connection cross section, finely stranded, max.	35 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	35 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	2.5 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	35 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	2.5 mm²
Wire connection cross-section, finely stranded, min.	10 mm²	Wire connection cross-section, solid core, max.	35 mm²
Wire connection cross-section, solid core, min.	2.5 mm²		

Rating data

Rated cross-section	35 mm²	Rated voltage	1,000 V
Rated voltage to adjoining terminal	1,000 V	Volume resistance according to IEC 60947-7-x	0.26 mΩ
Power loss in accordance with IEC 60947-7-x	4 W	Rated impulse withstand voltage	8 kV
Pollution severity	3	Surge voltage category	III

A-series
A2C 35 PE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

UL rating data

Certificate No. (cURus)	E60693	Conductor size Factory wiring max. (cURus)	2 AWG
Conductor size Factory wiring min. (cURus)	12 AWG	Conductor size Field wiring max. (cURus)	2 AWG
Conductor size Field wiring min. (cURus)	12 AWG	Voltage size B (cURus)	1000 V
Voltage size C (cURus)	1000 V	Voltage size D (cURus)	600 V

Classifications

ETIM 6.0	EC000901	ETIM 7.0	EC000901
eClass 9.0	27-14-11-41	eClass 9.1	27-14-11-41
eClass 10.0	27-14-11-41		

Approvals

Approvals

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Engineering Data	STEP
User Documentation	StorageConditionsTerminalBlocks

A-series
A2C 35 PE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

