SIEMENS

## Data sheet 3SU1152-6AA40-1AA0-Z Y13



Indicator lights, 22 mm, round, metal, shiny, green, lens, smooth, with holder, LED module with integrated LED 24 V AC/DC, screw terminal, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

| | |
|---|---|
| **product brand name** | SIRIUS ACT |
| **product designation** | Indicator lights |
| **design of the product** | Complete unit |
| **product type designation** | 3SU1 |
| **product line** | Metal, shiny, 22 mm |
| **manufacturer's article number** | |
| ● of supplied LED module | 3SU1401-1BB40-1AA0 |
| ● of the supplied holder | 3SU1550-0AA10-0AA0 |
| ● of supplied repeater | 3SU1051-6AA40-0AA0 |
| **Enclosure** | |
| **number of command points** | 1 |
| **Actuator** | |
| product extension optional light source | Yes |
| **color** | |
| ● of the actuating element | green |
| **material of the actuating element** | plastic |
| **shape of the actuating element** | round |
| **outer diameter of the actuating element** | 29.45 mm |
| **marking of the actuating element** | Any inscription, symbol compliant with ISO7000 and IEC60417 |
| **Front ring** | |
| **product component front ring** | No |
| **Holder** | |
| **material of the holder** | Plastic |
| **Display** | |
| **number of LED modules** | 1 |
| **General technical data** | |
| product component light source | Yes |
| insulation voltage rated value | 320 V |
| **degree of pollution** | 3 |
| **surge voltage resistance rated value** | 4 kV |
| **protection class IP** | IP66, IP67, IP69(IP69K) |
| ● of the terminal | IP20 |
| **degree of protection NEMA rating** | 1, 2, 3, 3R, 4, 4X, 12, 13 |
| **shock resistance** | |
| ● according to IEC 60068-2-27 | sinusoidal half-wave 15g / 11 ms |
| **vibration resistance** | |
| ● according to IEC 60068-2-6 | 10 ... 500 Hz: 5g |
| **reference code according to IEC 81346-2** | P |
| **Substance Prohibitance (Date)** | 10/01/2014 |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **Supply voltage** | |
| type of voltage of the supply voltage of the light source | AC/DC |
| **supply voltage of the light source at AC** | |
| ● at 50 Hz rated value | 24 V |
| ● at 60 Hz rated value | 24 V |
| ● at 60 Hz rated value | 24 ... 24 V |
| **supply voltage of the light source at DC** | |
| ● rated value | 24 V |
| ● rated value | 24 ... 24 V |
| **relative negative tolerance of the supply voltage** | 20 % |
| **relative positive tolerance of the supply voltage** | 20 % |
| **Control circuit/ Control** | |
| **inrush current maximum** | 2 A |
| **Connections/ Terminals** | |
| **type of electrical connection** | other |
| ● of modules and accessories | Screw-type terminal |
| **type of connectable conductor cross-sections** | |
| ● solid with core end processing | 2x (0.5 ... 0.75 mm²) |
| ● solid without core end processing | 2x (1.0 ... 1.5 mm²) |
| ● finely stranded with core end processing | 2x (0.5 ... 1.5 mm²) |
| ● finely stranded without core end processing | 2x (1,0 ... 1,5 mm²) |
| ● at AWG cables | 2x (18 ... 14) |
| **tightening torque of the screws in the bracket** | 1 ... 1.2 N·m |
| tightening torque with screw-type terminals | 0.8 ... 0.9 N·m |
| **Lamp** | |
| **type of light source** | LED |
| **color of the light source** | green |
| **light intensity** | 900 ... 1 800 mcd |
| **Ambient conditions** | |
| **ambient temperature** | |
| ● during operation | -25 ... +70 °C |
| ● during storage | -40 ... +80 °C |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted for all devices behind front panel) |
| **Installation/ mounting/ dimensions** | |
| **fastening method** | front plate mounting |
| ● of modules and accessories | Front plate mounting |
| **height** | 40 mm |
| **width** | 30 mm |
| **shape of the installation opening** | round |
| **mounting diameter** | 22.3 mm |
| **positive tolerance of installation diameter** | 0.4 mm |
| **mounting height** | 11.8 mm |
| **installation width** | 29.5 mm |
| **installation depth** | 49.7 mm |
| **Certificates/ approvals** | |
| **Further information** | |

**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1152-6AA40-1AA0-Z Y13
**Cax online generator**
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1152-6AA40-1AA0-Z Y13
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3SU1152-6AA40-1AA0-Z Y13
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1152-6AA40-1AA0-Z Y13&lang=en

**last modified:** 1/26/2022


Subject to change without notice
© Copyright Siemens