

**HDC MHP 200 PE MAS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Flexible**

The four module sizes make for individual plug solutions that save a huge amount of space. The smaller pitch translates into an optimised design too.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Power module               |
| Order No.  | <a href="#">2748260000</a> |
| Type       | HDC MHP 200 PE MAS         |
| GTIN (EAN) | 4050118890891              |
| Qty.       | 2 pc(s).                   |

## HDC MHP 200 PE MAS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 34 mm   | Depth (inches)  | 1.339 inch |
| Height     | 54.6 mm | Height (inches) | 2.15 inch  |
| Width      | 29.2 mm | Width (inches)  | 1.15 inch  |
| Net weight | 89.5 g  |                 |            |

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

## Environmental Product Compliance

|            |                |      |                                  |
|------------|----------------|------|----------------------------------|
| REACH SVHC | Lead 7439-92-1 | SCIP | fa505316-3e43-4ad0-930c-360dfdbe |
|------------|----------------|------|----------------------------------|

## General data

|                           |               |                    |      |
|---------------------------|---------------|--------------------|------|
| Material                  | Polycarbonate | Number of poles    | 1    |
| Plugging cycles           | ≥ 500         | Pollution severity | 3    |
| Required plug-in slots    | 2             | Type               | Male |
| UL 94 flammability rating | V-0           |                    |      |

## Version

|                                    |                    |                               |                        |
|------------------------------------|--------------------|-------------------------------|------------------------|
| Conductor cross-section, max.      | 70 mm <sup>2</sup> | Conductor cross-section, min. | 25 mm <sup>2</sup>     |
| Stripping length, rated connection | 16 mm              | Type of connection            | Axial screw connection |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002312    | ETIM 7.0    | EC002312    |
| ETIM 8.0    | EC002312    | ECLASS 9.0  | 27-44-02-92 |
| ECLASS 9.1  | 27-44-02-18 | ECLASS 10.0 | 27-44-02-92 |
| ECLASS 11.0 | 27-44-02-92 | ECLASS 12.0 | 27-44-02-92 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                                             |                                            |
|---------------------------------------------|--------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's declaration</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>            |
| User Documentation                          | <a href="#">Manual Axial Screw</a>         |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>   |

## HDC MHP 200 PE MAS

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

