P-Channel JFETs

2N5460 SST5460
2N5461 SST5461
2N5462 SST5462

PRODUCT SUMMARY				
Part Number	$V_{GS(off)}$ (V)	$V_{(BR)GSS}$ Min (V)	g_{fs} Min (mS)	I_{DSS} Min (mA)
2N/SST5460	0.75 to 6	40	1	–1
2N/SST5461	1 to 7.5	40	1.5	–2
2N/SST5462	1.8 to 9	40	2	–4

FEATURES

- High Input Impedance
- Very Low Noise
- High Gain: A_V = 80 @ 20 μA
- Low Capacitance: 1.2 pF Typical

BENEFITS

- Low Signal Loss/System Error
- High System Sensitivity
- High-Quality Low-Level Signal Amplification

APPLICATIONS


- Low-Current, Low-Voltage Amplifiers
- High-Side Switching
- Ultrahigh Input Impedance Pre-Amplifiers

DESCRIPTION

The 2N/SST5460 series are p-channel JFETs designed to provide all-around performance in a wide range of amplifier and analog switch applications.

The 2N series, TO-226AA (TO-92), and SST series, TO-236 (SOT-23), plastic packages provide low cost options, and are available in tape-and-reel for automated assembly, (see Packaging Information).


TO-226AA
(TO-92)



2N5460
2N5461
2N5462

Top View

TO-236
(SOT-23)



SST5460 (B0)*
SST5461 (B1)*
SST5462 (B2)*

*Marking Code for TO-236

Top View

ABSOLUTE MAXIMUM RATINGS

Gate-Drain Voltage . . . . . 40 V
Gate-Source Voltage . . . . . 40 V
Gate Current . . . . . –10 mA
Storage Temperature . . . . . –65 to 150°C
Operating Junction Temperature . . . . . –55 to 150°C

Lead Temperature ($^1/_{16}$" from case for 10 sec.) . . . . . 300°C
Power Dissipation[a] . . . . . 350 mW

Notes
a. Derate 2.8 mW/°C above 25°C

SPECIFICATIONS (T_A = 25°C UNLESS OTHERWISE NOTED)


Parameter	Symbol	Test Conditions		Typ[a]	Limits 2N/SST5460 Min	2N/SST5460 Max	2N/SST5461 Min	2N/SST5461 Max	2N/SST5462 Min	2N/SST5462 Max	Unit
Static											
Gate-Source Breakdown Voltage	$V_{(BR)GSS}$	I_G = 10 μA , V_{DS} = 0 V		55	40		40		40		V
Gate-Source Cutoff Voltage	$V_{GS(off)}$	V_{DS} = –15 V, I_D = –1 μA			0.75	6	1	7.5	1.8	9	V
Saturation Drain Current[b]	I_{DSS}	V_{DS} = –15 V, V_{GS} = 0 V			–1	–5	–2	–9	–4	–16	mA
Gate Reverse Current	I_{GSS}	V_{GS} = 20 V, V_{DS} = 0 V		0.003		5		5		5	nA
			T_A = 100°C	0.0003		1		1		1	μA
Gate Operating Current	I_G	V_{DG} = –20 V, I_D = –0.1 mA		3							pA
Drain Cutoff Current	$I_{D(off)}$	V_{DS} = –15 V, V_{GS} = 10 V		–5							pA
Gate-Source Voltage	V_{GS}	V_{DS} = –15 V	I_D = –0.1 mA	1.3	0.5	4					V
			I_D = –0.2 mA	2.3			0.8	4.5			V
			I_D = –0.4 mA	3.8					1.5	6	V
Gate-Source Forward Voltage	$V_{GS(F)}$	I_G = –1 mA , V_{DS} = 0 V		–0.7							V
Dynamic											
Common-Source Forward Transconductance	g_{fs}	V_{DS} = –15 V, V_{GS} = 0 V f = 1 kHz			1	4	1.5	5	2	6	mS
Common-Source Output Conductance	g_{os}					75		75		75	μS
Common-Source Reverse Transfer Capacitance	C_{iss}	V_{DS} = –15 V, V_{GS} = 0 V f = 1 MHz	2N	4.5		7		7		7	pF
			SST	4.5							pF
Common-Source Reverse Transfer Capacitance	C_{rss}			1.2							pF
Common-Source Output Capacitance	C_{oss}		2N	1.5		2		2		2	pF
			SST	1.5							pF
Equivalent Input Noise Voltage	$\overline{e}_n$	V_{DS} = –15 V, V_{GS} = 0 V f = 100 Hz	2N	15		115		115		115	nV/√Hz
			SST	15							nV/√Hz
Noise Figure	NF	V_{DS} = –15 V, V_{GS} = 0 V f = 100 Hz, R_G = 1 MΩ BW = 1 Hz	2N	0.2		2.5		2.5		2.5	dB
			SST	0.2							dB

Notes
a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
b. Pulse test: PW ≤ 300 μs duty cycle ≤ 2%.


PSCIB

TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)


Drain Current and Transconductance vs. Gate-Source Cutoff Voltage




On-Resistance and Output Conductance vs. Gate-Source Cutoff Voltage




Output Characteristics




Output Characteristics



Output Characteristics




Output Characteristics




TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)


Transfer Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate Leakage Current



Transconductance vs. Gate-Source Voltage




Transconductance vs. Gate-Source Voltage




TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)


Circuit Voltage Gain vs. Drain Current




Common-Source Forward Transconductance vs. Drain Current




Common-Source Input Capacitance vs. Gate-Source Voltage




Common-Source Reverse Feedback Capacitance vs. Gate-Source Voltage



Equivalent Input Noise Voltage vs. Frequency



Output Conductance vs. Drain Current



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.