
2SC5419

Silicon NPN triple diffusion planar type

For low-frequency output amplification



■ Features

- High collector-emitter voltage (Base open) V_{CEO}
- High transition frequency f_T
- Allowing supply with the radial taping

■ Absolute Maximum Ratings $T_a = 25°C$

Parameter	Symbol	Rating	Unit
Collector-base voltage (Emitter open)	V_{CBO}	300	V
Collector-emitter voltage (Base open)	V_{CEO}	300	V
Emitter-base voltage (Collector open)	V_{EBO}	7	V
Collector current	I_C	70	mA
Peak collector current	I_{CP}	100	mA
Collector power dissipation *	P_C	1	W
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	−55 to +150	°C

Note) *: Copper plate at the collector is more than 1 cm^2 in area, 1.7 mm in thickness

■ Electrical Characteristics $T_a = 25°C \pm 3°C$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Collector-emitter voltage (Base open)	V_{CEO}	I_C = 100 µA, I_B = 0	300			V
Emitter-base voltage (Collector open)	V_{EBO}	I_E = 1 µA, I_C = 0	7			V
Collector-emitter cutoff current (Base open)	I_{CEO}	V_{CE} = 120 V, I_B = 0			1	µA
Forward current transfer ratio *	h_{FE}	V_{CE} = 10 V, I_C = 5 mA	30		220	—
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C = 50 mA, I_B = 5 mA			1.2	V
Transition frequency	f_T	V_{CB} = 10 V, I_E = −10 mA, f = 200 MHz	50			MHz
Collector output capacitance (Common base, input open circuited)	C_{ob}	V_{CB} = 10 V, I_E = 0, f = 1 MHz			10	pF


Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.
2. *: Rank classification

Rank	P	Q	R
h_{FE}	30 to 100	60 to 150	100 to 220


Maintenance/Discontinued

Maintenance/discontinued type includes following four Product lifecycle stage.
Maintenance type
Planned maintenance type
Discontinued typed
Planned discontinued type
Please visit following URL and check latest information.
http://www.semicon.panasonic.co.jp/en/


P_C — T_a




I_C — V_{CE}




I_C — V_{BE}




I_C — I_B




$V_{CE(sat)}$ — I_C




I_B — V_{BE}



h_{FE} — I_C



C_{ob} — V_{CB}



Maintenance/ Discontinued
This product is discontinued. For alternative type, please refer to our Product lifecycle page or contact us. Planned discontinued type: 2SC5419 Planned discontinued period: 2010 Recommended alternative type: 2SC5419A For more information about discontinued type, please refer to following URL about latest information. Please visit to following URL: http://industrial.panasonic.com/ac/e/semicon/

Request for your special attention and precautions in using the technical information and semiconductors described in this book

(1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.

(2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.

(3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
- Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
- Any applications other than the standard applications intended.

(4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.

(5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.

(6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.

(7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.

Maintenance/Discontinued
Maintenance/Discontinued includes following our product's life cycle stage.
planed maintenance type
maintenance type
planed discontinued type
discontinued type
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/