2SK3372G

Silicon N-Channel Junction FET

For impedance conversion in low frequency
For electret capacitor microphone

■ Features

- High mutual conductance g_m
- Low noise voltage NV

■ Package

- Code
  SSSMini3-F2
- Pin Name
  1: Drain
  2: Source
  3: Gate

■ Marking Symbol: 1H

■ Absolute Maximum Ratings $T_a = 25°C$

Parameter	Symbol	Rating	Unit
Drain-source voltage (Gate open)	V_{DSO}	20	V
Gate-drain voltage (Source open)	V_{GDO}	20	V
Drain-source current (Gate open)	I_{DSO}	2	mA
Gate-drain current (Source open)	I_{GDO}	2	mA
Gate-source current (Drain open)	I_{GSO}	2	mA
Power dissipation	P_D	100	mW
Operating ambient temperature	T_{opr}	−20 to +80	°C
Storage temperature	T_{stg}	−55 to +125	°C


■ Electrical Characteristics $T_a = 25°C \pm 3°C$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain current *1	I_D	V_{DS} = 2.0 V, R_D = 2.2 kΩ ± 1%	100		470	μA
Drain-source current	I_{DSS}	V_{DS} = 2.0 V, R_D = 2.2 kΩ ± 1%, V_{GS} = 0	107		460	μA
Mutual conductance	g_m	V_D = 2.0 V, V_{GS} = 0, f = 1 kHz	660	1 600		μS
Noise voltage	NV	V_D = 2.0 V, R_D = 2.2 kΩ ± 1% C_O = 5 pF, A-Curve			4	μV
Voltage gain	G_{V1}	V_D = 2.0 V, R_D = 2.2 kΩ ± 1% C_O = 5 pF, e_G = 10 mV, f = 1 kHz	−7.5	−4.7		dB
	G_{V2}	V_D = 12 V, R_D = 2.2 kΩ ± 1% C_O = 5 pF, e_G = 10 mV, f = 1 kHz	−4.0	−1.5		
	G_{V3}	V_D = 1.5 V, R_D = 2.2 kΩ ± 1% C_O = 5 pF, e_G = 10 mV, f = 1 kHz	−8.0	−5.0		
	$\Delta\lvert G_V.f \rvert$ *2	V_D = 2.0 V, R_D = 2.2 kΩ ± 1% C_O = 5 pF, e_G = 10 mV, f = 1 kHz to 70 Hz		0	1.7	
Voltage gain difference	$\lvert G_{V2} - G_{V1} \rvert$		0		4.0	dB
	$\lvert G_{V1} - G_{V3} \rvert$		0		1.7	


Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.
2. *1: I_D is assured for I_{DSS}.
*2: $\Delta\lvert G_V.f \rvert$ is assured for AQL 0.065%. (The measurement method is used by source-grounded circuit.)

Maintenance/Discontinued
Discontinued includes following four Product lifecycle stage.
Maintenance/Discontinued maintenance type
Discontinued typed
Discontinued Type
Please check following URL about latest information.
http://www.semicon.panasonic.co.jp/en/


P_D — T_a




I_D — V_{DS}




I_D — V_{GS}



$|Y_{fs}|$ — V_{GS}




$|Y_{fs}|$ — I_D



Maintenance/Discontinued
Discontinued includes following four Product lifecycle stage.
planed maintenance type
maintenance type
planed discontinued type
discontinued typed
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/

SSSMini3-F2

Unit: mm



Maintenance/ Discontinued
Maintenance/Discontinued includes following four Product lifecycle stage.
planed maintenance type
maintenance type
planed discontinued typed
discontinued type
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/

Request for your special attention and precautions in using the technical information and semiconductors described in this book

(1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.

(2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.

(3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
- Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
- Any applications other than the standard applications intended.

(4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.

(5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.

(6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.

(7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.

Maintenance/Discontinued
Maintenance/Discontinued includes following Products
planed maintenance type
maintenance type
planed discontinued type
discontinued type
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/