



Number of contacts

Mounting height

9–37
50



Standard Versions

Stamped solder pins, angled with grounding board locks

Identification		No. of contacts	Part number	
D-Sub	Performance levels Explanations see page 05.04 Other performance levels on request		Performance level 3	Performance level 2
	Male connector metal shell with dimples			
			2.84 mm pitch	2.84 mm pitch
			2.54 mm pitch	2.54 mm pitch
		9	09 65 163 781 . 1)	09 65 163 681 . 1)
		15	09 65 263 781 . 1)	09 65 263 681 . 1)
		25	09 65 363 781 . 1)	09 65 363 681 . 1)
		37	09 65 463 781 . 1)	09 65 463 681 . 1)
		9	09 65 162 781 .	09 65 162 681 .
		15	09 65 262 781 .	09 65 262 681 .
		25	09 65 362 781 .	09 65 362 681 .
		37	09 65 462 781 .	09 65 462 681 .
	Female connector metal shell			
			2.84 mm pitch	2.84 mm pitch
			2.54 mm pitch	2.54 mm pitch
		9	09 66 153 761 . 1)	09 66 153 661 . 1)
		15	09 66 253 761 . 1)	09 66 253 661 . 1)
		25	09 66 353 761 . 1)	09 66 353 661 . 1)
		37	09 66 453 761 . 1)	09 66 453 661 . 1)
		9	09 66 152 761 .	09 66 152 661 .
		15	09 66 252 761 .	09 66 252 661 .
		25	09 66 352 761 .	09 66 352 661 .
		37	09 66 452 761 .	09 66 452 661 .
		50	09 66 552 761 . 1)	09 66 552 661 . 1)
	Please insert digit for flange thread or fitted female screw locks			
	Ø 3.1 mm hole ▶ 0 ¹⁾			
	M3 ▶ 1			
	4-40 UNC ▶ 2			
	fitted screw locks 4-40 UNC ▶ 3			