Features

- Small diameter
- Wide resistance range
- Good resolution
- Linear tapers
- Cermet element

Additional Information

Click these links for more information:

PRODUCT SELECTOR | TECHNICAL LIBRARY | INVENTORY | SAMPLES | CONTACT

3862 – 1/2 ″ Diameter Single-Turn Panel Control

Initial Electrical Characteristics[1]

Standard Resistance Range	1K ohms to 1 megohm
Total Resistance Tolerance	(A Taper) ±10 % (H Taper) ±5%
Independent Linearity	±5 %
Absolute Minimum Resistance	2 ohms maximum
Effective Electrical Angle	260 ° ±10 °
Contact Resistance Variation	±3 % or 6 ohms (whichever is greater)
Dielectric Withstanding Voltage (MIL-STD-202, Method 301)	
Sea Level	750 VAC minimum
70,000 Feet	350 VAC minimum
Insulation Resistance (500 VDC)	1,000 megohms minimum
Power Rating (Voltage Limited by Power Dissipation or 350 VAC, Whichever is Less)	
+70 °C	1 watt
+125 °C	0 watt
Theoretical Resolution	Essentially infinite

Environmental Characteristics[1]

Operating Temperature Range	-40 °C to +125 °C
Storage Temperature Range	-65 °C to +125 °C
Temperature Coefficient Over Storage Temperature Range	±150 ppm/°C
Vibration	20 G
Total Resistance Shift	±2 % maximum
Voltage Ratio Shift	±6 % maximum
Shock	50 G
Total Resistance Shift	±2 % maximum
Voltage Ratio Shift	±6 % maximum
Load Life	1,000 hours
Total Resistance Shift	±3 % maximum
Rotational Life, No Load	
(C & N Bushings)	50,000 cycles
(E & T Bushings)	1,000 cycles
Total Resistance Shift	±5 % maximum
Contact Resistance Variation	±3 % or 6 ohms (whichever is greater)
Moisture Resistance (MIL-STD-202, Method 106, Condition B)	
Total Resistance Shift	±2 % maximum
Insulation Resistance (500 VDC)	100 megohms minimum
Salt Spray	MIL-STD-202, Method 101, Condition A
IP Rating	IP 40

Mechanical Characteristics[1]

Stop Strength	33 N-cm (3 lb.-in.) maximum
Mechanical Angle	295 ° ±3 °
Torque	
Starting and Running	3.53 N-cm (5 oz.-in.) maximum
Mounting (Torque on Bushing)	1.7-2.0 N-m (15-18 lb.-in.) maximum
Shaft Locking Torque with Locking Bushings	14.12 N-cm (20 oz.-in.)
Weight (Single Section)	25 grams maximum
Terminals	Printed circuit pins or J-Hooks
Soldering Condition	Recommended hand soldering using Sn85/Ag5 no clean solder, 0.025 ″ wire diameter Maximum temperature 399 °C (750 °F) for 3 seconds. No wash process to be used with no clean flux. Part can be wave soldered at 260 °C (500 °F) for 5 seconds, no wash process with no clean flux.
Marking	Manufacturer's trademark, wiring diagram, date code, resistance, manufacturer's part number
Ganging	1 cup maximum
Hardware	One lockwasher (H-37-1) and one mounting nut (H-38-1) is shipped with each potentiometer; locking bushing versions are shipped with one additional locking nut (H-38-3).

[1] ELECTRICAL SPECIFICATIONS TESTED AT 250 RPM, AT ROOM AMBIENT: +25 °C NOMINAL.

WARNING
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Product Dimensions

PCB LAYOUT



PANEL LAYOUT



3862E/T



3862C/N



Shaft End Detail
3862



PC PIN TERMINAL



J-HOOK TERMINAL





DIMENSIONS: MM / (INCHES)

Hardware

LOCKWASHER H-37-1



NUT H-38-1



LOCKING NUT H-38-3



DIMENSIONS: MM / (INCHES)



Date Code Description



Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

How to Order 3862 Series Panel Controls

BOURNS®



SHAFT TYPE (FMS) & DIAMETER		BUSHINGS
12	**3/8 ” (9.53 mm) L X 1/8 ” (3.18 mm) D**	C
16	**1/2 ” (12.7 mm) L x 1/8 ” (3.18 mm) D**	C
20	5/8 ” (15.88 mm) L x 1/8 ” (3.18 mm) D	C, E, N, T
28	7/8 ” (22.20 mm) L X 1/8 ” (3.18 mm) D	C, E, N, T

Consult factory for lengths not shown.

BUSHING	
C	**Plain 1/4 ” (6.35 mm) D x 1/4 ” (6.35 mm) L**
E	Locking 1/4 ” (6.35 mm) D x 1/2 ” (12.7 mm) L
N	Plain 1/4 ” (6.35 mm) D x 3/8 ” (9.53 mm) L
T	Locking 1/4 ” (6.35 mm) D x 3/8 ” (9.53 mm) L

MODEL	
3862	**1/2 ” (12.7 mm) D Single-Turn Cermet**

TERMINAL STYLE AND SHAFT TYPE	
1	Solder Lugs, Plain End
2	**Solder Lugs, Slotted End**
3	Solder Lugs, Flatted Shaft
5	PC Pins, Plain End
6	PC Pins, Slotted End
7	PC Pins, Flatted End

RESISTANCE CODE/VALUE (IN OHMS)	
(102)	**1K**
(252)	2.5K
(502)	**5K**
(103)	**10K**
(253)	25K
(503)	**50K**
(104)	**100K**
(254)	250K
(504)	500K
(105)	1M

ELEMENT TAPER/TOLERANCE	
A	**Linear ±10 %**
H	Linear ±5 %

RoHS IDENTIFIER	
L	**Compliant**

Boldface features are Bourns standard options. All others are available with higher minimum order quantities.

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com
Europe: Tel: +36 88 885 877 • Email: eurocus@bourns.com
Mexico: Tel: +52 614 478 0400 • Email: mexicus@bourns.com
The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com
www.bourns.com

REV. 04/25

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Legal Disclaimer Notice

BOURNS®

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."

- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automate Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.

- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.

- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: https://www.bourns.com/legal/disclaimers-terms-and-policies
PDF: https://www.bourns.com/docs/Legal/disclaimer.pdf