





SEC:A−A

CONDUCTOR: [26AWG(0.12X12)BARE COPPER]X4C
INSULATION: (PP6331 ID: 0.95-1.0)X4C
JACKET: PVC NOUL 80P(Flexible material)
BLACK
RED
GREEN
YELLOW

NOTE FOR PLUG:
MATERIAL: HOUSING-POLYCARBONATE, CLEAR.
TERMINAL-0.36[.014] THICK PHOSPHOR BRONZE.
THICK GOLD IN LOCALIZED GOLD PLATE.
AREA, GOLD FLASH OVER THE REMAINDER.
OVER 2.54um[.000100] THICK NICKEL
UNDERPLATE.

TERMINATION:

P1	P2	COLOR
1	1	BLACK
2	2	RED
3	3	GREEN
4	4	YELLOW

PART NO	DRAWING NO	BUYER COLOR	VENDOR COLOR	RETRACTED LENGTH ("L3")	CUSTOMER Accepted ("L2")	CUT LENGTH "L1"
522-26-4400-SV-0005F	A	Silver	S49-1 LIGHT	330±30	5.0FT-5.75FT	2300-2400
522-26-4400-SV-0007F	B	Silver	S49-1 LIGHT	470±30	7.0FT-8.05FT	3000-3200
522-26-4400-SV-0010F	C	Silver	S49-1 LIGHT	630±50	10.0FT-11.5FT	4300-4500
522-26-4400-SV-0012F	D	Silver	S49-1 LIGHT	800±50	12.0FT-13.8FT	5200-5400
522-26-4400-SV-0014F	E	Silver	S49-1 LIGHT	850±50	14.0FT-16.1FT	5800-6000
522-26-4400-SV-0025F	F	Silver	S49-1 LIGHT	1900±50	25.0FT-28.75FT	10800-11000

REVISE	VERSION	BASIS	CONTENTS

CnC Tech, LLC
Industrial Cable and Connector Technology

IDRAWING NO: 671-328		CUSTOMER: L-671
ITEM NO: 4C COILD CORD P+P PLUG		UNIT: mm
DATE: 2012-02-20		ISSUE (A/0)
DRAWN:	QE:	QA:
SALES DEPT:	SALES MANAGER:	