

Number of contacts

9–37



SMT stamped solder pins, angled with grounding dies

Identification		No. of contacts	Part number	
Performance levels Explanations see page 05.184 Other performance levels on request			Performance level 3	Performance level 2
Male connector metal shell with dimples	9	09 55 166 78 .. 741	09 55 166 68 .. 741	
	15	09 55 266 78 .. 741	09 55 266 68 .. 741	
	25	09 55 366 78 .. 741	09 55 366 68 .. 741	
	37	09 55 466 78 .. 741	09 55 466 68 .. 741	
Female connector metal shell	9	09 55 156 76 .. 741	09 55 156 66 .. 741	
	15	09 55 256 76 .. 741	09 55 256 66 .. 741	
	25	09 55 356 76 .. 741	09 55 356 66 .. 741	
	37	09 55 456 76 .. 741	09 55 456 66 .. 741	
Packaging: 160 pieces on a reel				
Please insert digit for flange thread or fitted female screw locks				
M3 ▶ 15				
4-40 UNC ▶ 16				
non-removable				
fitted screw locks M3 ▶ 19				
non-removable				
fitted screw locks 4-40 UNC ▶ 20				
Samples				
Male connector metal shell with dimples	9	If performance level 3 is required please order as substitute performance level 2	09 55 166 68 .. 333	
	15		09 55 266 68 .. 333	
	25		09 55 366 68 .. 333	
	37		09 55 466 68 .. 333	
Female connector metal shell	9		09 55 156 66 .. 333	
	15		09 55 256 66 .. 333	
	25		09 55 356 66 .. 333	
	37		09 55 456 66 .. 333	
Packaging 9, 15 contacts: 5 samples 25, 37 contacts: 3 samples				
Please insert digit for flange thread or fitted female screw locks				
4-40 UNC ▶ 16				
non-removable				
fitted screw locks 4-40 UNC ▶ 20				