





NOTES 1. 材質
MATERIAL
ハウジング：ガラス入りPPS、茶色、UL94V-0
HOUSING:POLYPHENYLENE SULFIDE, GLASS FILLED, BROWN, UL94V-0
ターミナル：銅合金（t=0.2）、ニッケルメッキ下地1.5マイクロメートル以上
TERMINAL: COPPER ALLOY, UNDER-PLATING: NICKEL 1.5 MICROMETER MIN.
接点部：金メッキ 0.25マイクロメートル以上
CONTACT AREA: GOLD 0.25 MICROMETER MIN.
半田付け部：錫メッキ1.0マイクロメートル以上
SOLDER TAIL AREA: TIN 1.0 MICROMETER MIN.
ネール：リン青銅(t=0.2)、ニッケルメッキ下地1.0マイクロメートル以上
NAIL: PHOSPHOR BRONZE, UNDER-PLATING: NICKEL 1.0 MICROMETER MIN.
錫メッキ1.0マイクロメートル以上
TIN 1.0 MICROMETER MIN.
吸着カバー：ステンレス（t=0.2）
VACUUM COVER: STAINLESS STEEL

2. テールのバラツキ寸法
TAIL COPLANARITY
テール平坦度は、0.1ミリ以下とする。
TAILS COPLANARITY TO BE 0.1 MILLIMETER MAX.

無し WITHOUT	66.47	65.37	62.865	70.37	53627-2074	-	200
	60.12	59.02	56.515	64.02	53627-1874	-	180
	53.77	52.67	50.165	57.67	53627-1674	53627-1675	160
	47.42	46.32	43.815	51.32	53627-1474	-	140
	41.07	39.97	37.465	44.97	53627-1274	-	120
	34.72	33.62	31.115	38.62	53627-1074	-	100
	31.55	30.45	27.94	35.45	53627-0974	-	90
	28.37	27.27	24.765	32.27	53627-0874	-	80
有り WITH	25.2	24.1	21.59	29.1	53627-0774	-	70
	22.02	20.92	18.415	25.92	53627-0674	-	60
	18.85	17.75	15.24	22.75	53627-0574	-	50
	15.67	14.57	12.065	19.57	53627-0474	-	40
	12.5	11.4	8.89	16.4	53627-0374	-	30
	9.32	8.22	5.715	13.22	53627-0274	-	20
ハウジングロック HSG LOCK	D	C	B	A	エンボス梱包 EMBOSSED PACKAGE	スティック梱包 STICK PACKAGE	極数 CKT
					オーダー番号 ORDER NO.		

GENERAL TOLERANCES (UNLESS SPECIFIED)			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			CURRENT REV DESC:			<div>molex</div>			
DIMENSION UNITS			SCALE									
mm			-									
GENERAL TOLERANCES (UNLESS SPECIFIED)												
10 UNDER			± 0.2									
10 OVER 30 UNDER			± 0.25									
30 OVER			± 0.3									
ANGULAR ± 3 °												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS												



嵌合高さ一覧 Stacking Height variation			
	6	52885 series	55091 series
	7		53625 series
	8		53647 series
	9		53649 series
○	10		53627 series
	12	52901 series	55091 series
	13		53625 series
	14		53647 series
	15		53649 series
○	16		53627 series
本図製品該当高さ Height Application	嵌合高さ E Stacking Height	リセプタクル Receptacle	プラグ Plug

55091 series
53625 series
53647 series
53649 series
53627 series
Plug



52885 series
52901 series
Receptacle

GENERAL TOLERANCES (UNLESS SPECIFIED)		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:				molex			
10 UNDER	± 0.2	DIMENSION UNITS	SCALE	EC NO: 627249 DRWN: JFURUKAWA 2019/11/08 CHK'D: HSHIMOYAMA 2019/11/14 APPR: SHOSHIKAWA 2020/01/13 INITIAL REVISION: DRWN: YSAKIYAMA 2004/03/15 APPR: MSASAO 2004/03/16				0.635 PITCH B/B CONN. PLUG HSG COVER ASSY -LEAD FREE-			
10 OVER 30 UNDER	± 0.25	mm	-					PRODUCT CUSTOMER DRAWING			
30 OVER	± 0.3	GENERAL TOLERANCES (UNLESS SPECIFIED)						DOCUMENT NUMBER			
ANGULAR ± 3 °		ANGULAR TOL ± 30 °						SD-53627-001			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		4 PLACES ± 0.2		THIRD ANGLE PROJECTION				PSD			
		3 PLACES ± 0.25		DRAWING				001			
		2 PLACES ± 0.3		SERIES				F			
		1 PLACE ±		MATERIAL NUMBER				SEE CHART			
		0 PLACES ±		CUSTOMER				GENERAL MARKET			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		A3-SIZE				2 OF 2			



DOCUMENT STATUS	P1	RELEASE DATE	2020/01/13	17:10:35
-----------------	----	--------------	------------	----------

FORMAT: master-B-prod-A3
REVISION: 14
DATE: 2018/01/18


20 ~ 140CKT



160CKT




180, 200CKT



NOTES

- 製品番号 53627-**72 の詳細寸法については SD-53627-001 を参照下さい。
IN THE PACKAGE , PART NO. 53627-**72 DETAILED DIMENSIONS , SEE SD-53627-001.
- 梱包数量 : 700個/リール
NUMBER OF CONNECTORS : 700 PCS/REEL
- リードテープ長さ
LEAD TAPE LENGTH



- 材料
MATERIAL
キャリアテープ : ポリプロピレン (PP) : 20 ~ 140, 200 極
ポリスチレン (PS) : 160, 180 極


CARRIER TAPE : POLYPROPYLENE (PP) : 20 ~ 140, 200CKT
POLYSTYRENE (PS) : 160, 180CKT

トップテープ : PET, PE, PEF
TOP TAPE : PET, PE, PEF

リール : 紙 : 20 ~ 140 極
ポリスチレン : 160 ~ 200 極

REEL : CARD BOARD : 20 ~ 140, 200CKT
POLYSTYRENE : 160, 180CKT

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex			
DIMENSION UNITS	SCALE			EMBSTP PKG FOR 0.635 B/B PLUG HSG ASSY (H=10) -LEAD FREE-			
mm	-			PRODUCT CUSTOMER DRAWING			
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 175909					
ANGULAR TOL ± 30°		DRWN: RMIYAMOTO		2018/03/16			
4 PLACES ± 0.2		CHK'D: KSASAKI		2018/05/01			
3 PLACES ± 0.25		APPR: RTAKEUCHI		2018/05/01			
2 PLACES ± 0.3		INITIAL REVISION:					
1 PLACE ±		DRWN: YSAKIYAMA		2004/03/15			
0 PLACES ±		APPR: MSASAO		2004/03/16			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES	
				A3-SIZE		53627	
				MATERIAL NUMBER		CUSTOMER	
				SEE CHART		GENERAL MARKET	
				DOCUMENT NUMBER		DOC TYPE	
				SD-53627-002		PSD	
				DOC PART		REVISION	
				001		C	
				SHEET NUMBER			
				1 OF 3			



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex			
DIMENSION UNITS		SCALE		EMBSTP PKG FOR 0.635 B/B PLUG HSG ASSY (H=10) -LEAD FREE-			
mm		-		PRODUCT CUSTOMER DRAWING			
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 175909		DOCUMENT NUMBER			
ANGULAR TOL $\pm 30^\circ$		DRWN: RMIYAMOTO 2018/03/16		DOC TYPE			
4 PLACES ± 0.2		CHK'D: KSASAKI 2018/05/01		DOC PART			
3 PLACES ± 0.25		APPR: RTAKEUCHI 2018/05/01		REVISION			
2 PLACES ± 0.3		INITIAL REVISION:		SD-53627-002			
1 PLACE $\pm$		DRWN: YSAKIYAMA 2004/03/15		PSD			
0 PLACES $\pm$		APPR: MSASAO 2004/03/16		001			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		C			
		DRAWING		SHEET NUMBER			
		A3-SIZE		2 OF 3			
		SERIES		GENERAL MARKET			
		53627		SEE CHART			
		MATERIAL NUMBER					
		CUSTOMER					

