Circuit Board Indicators
Panel Mount Indicators
Solid State Lighting
Traffic Signals
Vehicle Lighting
Rail
Obstruction Lighting
Hazardous Area Lighting
Heliport Lighting

how to purchase
sales contacts
stock check

search
Product Line Search
Please select a Product Line to search.
Circuit Board Indicators
find

Part # / Text Search
Part No.:
Text Search:
search

quick links
Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# **5530131310F**	3 mm Lens
Description	3 mm Bi-Level CBI
Package Options	50 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Bi-Level Housing
Configuration	3 mm Lens
Viewing	Right Angle
Viewing Angle	45
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp	260Â° for 5 sec
Operating Temp	-25 to +85° C
Storage Temp	-30 to +100° C

RoHS /pB Free
view PDF

Distributor Stock Check

Check stock with our distributors now.
5530131310F
check stock

Operating Characteristics

LED Position	Found in position(s): 1	Found in position(s): 2
Color	Yellow	Red
Lamp Type	Single Color	Single Color
LED Type	Standard Efficiency	Standard Efficiency
Intensity Min (mcd)	2.2	3.6
Intensity Typ (mcd)	6.3	10.0
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)		
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)	60	60
Backlighting		
Pitch Between Vertical		
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

Copyright 2006 Dialight. All rights reserved | Privacy Policy