SIEMENS

# Data sheet for Line reactor

**MLFB-Ordering data** **6SE6400-3CC03-5CB3**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

## Rated data

### Input

| | |
|---|---|
| **Number of phases** | 1 AC |
| **Line voltage** | 200 ... 240 V |

### Output

| | |
|---|---|
| **Rated current** | 29.5 A |

## Mechanical data

### Dimensions

| | |
|---|---|
| **Width** | 185.0 mm (7.3 in) |
| **Height** | 245.0 mm (9.7 in) |
| **Depth** | 50.0 mm (2.0 in) |
| **Degree of protection** | IP20 / UL open type |
| **Net weight** | 3.0 kg (6.7 lb) |

## Connections

### Line side

| | |
|---|---|
| **Version** | screw-type terminal |
| **Conductor cross-section** | 2.50 ... 10.00 mm² (14 ... 8 AWG) |

### Load side

| | |
|---|---|
| **Version** | Pigtail |
| **Conductor cross-section** | 8.00 mm² (10 AWG) |
| **Cable length** | 0.49 m (1.61 ft) |

### PE connection

| | |
|---|---|
| **Version** | M5 stud |

## Standards

| | |
|---|---|
| **Compliance with standards** | cURus |

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.