TECHNICAL SPECIFICATIONS


D-Sub Hood:

Material:	Zinc, Black Plated
Operating Temperature:	-40°C to +120°C
Cable Entry:	Top Entry
Thumbscrews:	UNC 4-40 (Standard) M2,5 or M3 on request
Cable O.D:	Up to 11,5mm

Male D-Sub Solder Cup:

Insulator:	PBT, Black, UL94 V-0
Shell:	Steel, Tin Plated
Contact pins:	Copper Alloy
Stamped & Formed Pins Machined Contact Pins:	Class 3, 100 inserts min. Class 1, 500 inserts min.
Contact Plating:	Selective Gold over Nickel
Operating Temperature:	-55°C to +105°C
Withstanding voltage:	1000V for 1 minute
Insulator resistance:	1000MΩ min.





Features:

- Available in sizes 9-15-25-37
- Excellent EMI Shielding
- Re-openable
- Strain relief inserts ensure a secure termination
- Black Full Metal Jackscrew as standard

Size DTZK	Dim A	Dim B	Dim C
9-way	31,0	39,5	15,0
15-way	39,5	41,5	15,0
25-way	53,5	48,5	15,0
37-way	71,0	53,0	15,0

Ordering information - Black Insulator:

Size:	P/N - Kitted:	Class 3 - 100 inserts min.
9-way	6355-0101-01	DTZK09-BK-DBP-K
15-way	6355-0101-02	DTZK15-BK-DBP-K
25-way	6355-0101-03	DTZK25-BK-DBP-K
37-way	6355-0101-04	DTZK37-BK-DBP-K

Size:	P/N - Kitted:	Class 1 - 500 inserts min.
9-way	6355-0101-21	DTZK09-BK-DMP-K
15-way	6355-0101-22	DTZK15-BK-DMP-K
25-way	6355-0101-23	DTZK25-BK-DMP-K
37-way	6355-0101-24	DTZK37-BK-DMP-K

Ordering information - White Insulator:

Size:	P/N - Kitted:	Class 3 - 100 inserts min.
9-way	6355-8101-01	DTZK09-BK-DBP-W-K
15-way	6355-8101-02	DTZK15-BK-DBP-W-K
25-way	6355-8101-03	DTZK25-BK-DBP-W-K
37-way	6355-8101-04	DTZK37-BK-DBP-W-K

Size:	P/N - Kitted:	Class 1 - 500 inserts min.
9-way	6355-8101-21	DTZK09-BK-DMP-W-K
15-way	6355-8101-22	DTZK15-BK-DMP-W-K
25-way	6355-8101-23	DTZK25-BK-DMP-W-K
37-way	6355-8101-24	DTZK37-BK-DMP-W-K