


- Easily snaps onto 35mm DIN-rail
- Panel mountable
- 15A or 20A versions
- Easy to wire
- Available with ground fault current interrupt (GFCI) or standard duplex outlets
- Option for visual indication of power included with GFCI
- NEMA rated enclosure with UL94 VO flammability rating
- UL508A and cULus approved

Weidmüller

DIN-Rail Receptacle

Dimensional Drawing



15 Amp Duplex



15 Amp GFCI



Technical data

Voltage
Current
Operating Frequency
Dielectric Voltage
Current Interrupting
Trip Level
Termination Wire Size
Terminal Torque
Temperature:
Operating
Storage
Material Listing
Enclosure Cover, Flammability
Enclosure Base, Flammability
Spring

125 VAC
15A
50 - 60 Hz
Withstands 2000V per UL498
Full rated current
N/A
#20 - #10 AWG solid or stranded
7 lb.-in. (.79 Nm)
-35°C to 60°C
-25°C to 80°C
PBT/polycarbonate blend, UL94 rating V0 @ .63mm
Polyamide 6/6 30% GF, UL94 rating V0 @ .63mm
Stainless Steel

125 VAC
15A
50 - 60 Hz
Withstands 1500V per UL498
10 kA
5±1 mA
#20 - #10 AWG solid or stranded
7 lb.-in. (.79 Nm)
-35°C to 60°C
-25°C to 80°C
PBT/polycarbonate blend, UL94 rating V0 @ .63mm
Polyamide 6/6 30% GF, UL94 rating V0 @ .63mm
Stainless Steel

Approvals/Certifications

Description
TUL 508A (file # E223801)
cULus
UL498
NEMA WD-6
NEMA 5-15R

Description
TUL 508A (file # E223801)
cULus
UL 943
NEMA WD-6
NEMA 5-15R


Ordering data

Type	Part No.
DRAC DP 15	6720005421

Type	Part No.
DRAC GF 15	6720005422

DIN-Rail Receptacle

Dimensional Drawing



20 Amp Duplex



20 Amp GFCI



Technical data

Voltage	125 VAC	125 VAC
Current	20A	20A
Operating Frequency	50 - 60 Hz	50 - 60 Hz
Dielectric Voltage	Withstands 2000V per UL498	Withstands 1500V per UL498
Current Interrupting	Full rated current	10 kA
Trip Level	N/A	5±1 mA
Termination Wire Size	#20 - #10 AWG solid or stranded	#20 - #10 AWG solid or stranded
Terminal Torque	7 lb.-in. (.79 Nm)	7 lb.-in. (.79 Nm)
Temperature:		
Operating	-35°C to 60°C	-35°C to 60°C
Storage	-25°C to 80°C	-25°C to 80°C
Material Listing		
Enclosure Cover, Flammability	PBT/polycarbonate blend, UL94 rating V0 @ .63mm	PBT/polycarbonate blend, UL94 rating V0 @ .63mm
Enclosure Base, Flammability	Polyamide 6/6 30% GF, UL94 rating V0 @ .63mm	Polyamide 6/6 30% GF, UL94 rating V0 @ .63mm
Spring	Stainless Steel	Stainless Steel

Approvals/Certifications

	Description	Description
	TUL 508A (file # E223801)	TUL 508A (file # E223801)
	cULus	cULus
	UL498	UL 943
	NEMA WD-6	NEMA WD-6
	NEMA 5-15R	NEMA 5-15R

Ordering data

	Type	Part No.	Type	Part No.
	DRAC DP 20	6720005420	DRAC GF 20	6720005423

