FAIRCHILD SEMICONDUCTOR™

November 1999
Revised November 2000

74LVTH646
Low Voltage Octal Transceiver/Register with 3-STATE Outputs

General Description

The LVTH646 consists of registered bus transceiver circuits, D-type flip-flops, and control circuitry providing multiplexed transmission of data directly from the input bus or from the internal storage registers. Data on the A or B bus will be loaded into the respective registers on the LOW-to-HIGH transition of the appropriate clock pin (CPAB or CPBA). (See Functional Description)

The LVTH646 data inputs include bushold, eliminating the need for external pull-up resistors to hold unused inputs.

The bus transceivers are designed for low-voltage (3.3V) V_{CC} applications, but with the capability to provide a TTL interface to a 5V environment. The LVTH646 is fabricated with an advanced BiCMOS technology to achieve high speed operation similar to 5V ABT while maintaining low power dissipation.

Features


- Input and output interface capability to systems at 5V V_{CC}
- Bushold data inputs eliminate the need for external pull-up resistors to hold unused inputs
- Live insertion/extraction permitted
- Power Up/Down high impedance provides glitch-free bus loading
- Outputs source/sink –32 mA/+64 mA
- Functionally compatible with the 74 series 646
- Latch-up performance exceeds 500 mA
- ESD performance:
  - Human-body model > 2000V
  - Machine model > 200V
  - Charged-device model > 1000V

Ordering Code:


Order Number	Package Number	Package Description
74LVTH646WM	M24B	24-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300 Wide
74LVTH646MTC	MTC24	24-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide

Devices also available in Tape and Reel. Specify by appending letter suffix "X" to the ordering code.

Logic Symbols




IEEE/IEC



© 2000 Fairchild Semiconductor Corporation

Connection Diagram



Pin Descriptions

Pin Names	Description
A_0–A_7	Data Register A Inputs
	Data Register A Outputs
B_0–B_7	Data Register B Inputs
	Data Register B Outputs
CPAB, CPBA	Clock Pulse Inputs
SAB, SBA	Transmit/Receive Inputs
$\overline{OE}$	Output Enable Input
DIR	Direction Control Input

Truth Table


(Note 1)

Inputs						Data I/O		Function
$\overline{OE}$	DIR	CPAB	CPBA	SAB	SBA	A_0–A_7	B_0–B_7	
H	X	H or L	H or L	X	X	Input	Input	Isolation
H	X	↑	X	X	X			Clock A_n Data into A Register
H	X	X	↑	X	X			Clock B_n Data into B Register
L	H	X	X	L	X	Input	Output	A_n to B_n—Real Time (Transparent Mode)
L	H	↑	X	L	X			Clock A_n Data into A Register
L	H	H or L	X	H	X			A Register to B_n (Stored Mode)
L	H	↑	X	H	X			Clock A_n Data into A Register and Output to B_n
L	L	X	X	X	L	Output	Input	B_n to A_n—Real Time (Transparent Mode)
L	L	X	↑	X	L			Clock B_n Data into B Register
L	L	X	H or L	X	H			B Register to A_n (Stored Mode)
L	L	X	↑	X	H			Clock B_n Data into B Register and Output to A_n

H = HIGH Voltage Level L = LOW Voltage Level X = Immaterial ↑ = LOW-to-HIGH Transition

Note 1: The data output functions may be enabled or disabled by various signals at the $\overline{OE}$ and DIR inputs. Data input functions are always enabled; i.e., data at the bus pins will be stored on every LOW-to-HIGH transition of the appropriate clock inputs.

Logic Diagram




Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Functional Description

In the transceiver mode, data present at the HIGH impedance port may be stored in either the A or B register or both. The select (SAB, SBA) controls can multiplex stored and real-time. The examples below demonstrate the four fundamental bus-management functions that can be performed.


The direction control (DIR) determines which bus will receive data when $\overline{OE}$ is LOW. In the isolation mode ($\overline{OE}$ HIGH), A data may be stored in one register and/or B data may be stored in the other register. When an output function is disabled, the input function is still enabled and may be used to store and transmit data. Only one of the two busses, A or B, may be driven at a time.

Real-Time Transfer
Bus B to Bus A




$\overline{OE}$	DIR	CPAB	CPBA	SAB	SBA
L	L	X	X	X	L

Real-Time Transfer
Bus B to Bus A




$\overline{OE}$	DIR	CPAB	CPBA	SAB	SBA
L	H	X	X	L	X

Transfer Storage
Data to A or B



$\overline{OE}$	DIR	CPAB	CPBA	SAB	SBA
L	L	X	H or L	X	H
L	H	H or L	X	H	X

Storage



$\overline{OE}$	DIR	CPAB	CPBA	SAB	SBA
L	H	⌐	X	L	X
L	L	X	⌐	X	L
H	X	⌐	X	X	X
H	X	X	⌐	X	X

Absolute Maximum Ratings(Note 2)

Symbol	Parameter	Value	Conditions	Units
V_{CC}	Supply Voltage	−0.5 to +4.6		V
V_I	DC Input Voltage	−0.5 to +7.0		V
V_O	DC Output Voltage	−0.5 to +7.0	Output in 3-STATE	V
		−0.5 to +7.0	Output in HIGH or LOW State (Note 3)	V
I_{IK}	DC Input Diode Current	−50	V_I < GND	mA
I_{OK}	DC Output Diode Current	−50	V_O < GND	mA
I_O	DC Output Current	64	$V_O > V_{CC}$ Output at HIGH State	mA
		128	$V_O > V_{CC}$ Output at LOW State	
I_{CC}	DC Supply Current per Supply Pin	±64		mA
I_{GND}	DC Ground Current per Ground Pin	±128		mA
T_{STG}	Storage Temperature	−65 to +150		°C

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Units
V_{CC}	Supply Voltage	2.7	3.6	V
V_I	Input Voltage	0	5.5	V
I_{OH}	HIGH Level Output Current		−32	mA
I_{OL}	LOW Level Output Current		64	
T_A	Free-Air Operating Temperature	−40	85	°C
$\Delta t/\Delta V$	Input Edge Rate, V_{IN} = 0.8V–2.0V, V_{CC} = 3.0V	0	10	ns/V

Note 2: Absolute Maximum continuous ratings are those values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute maximum rated conditions is not implied.

Note 3: I_O Absolute Maximum Rating must be observed.

DC Electrical Characteristics

Symbol	Parameter		V_{CC} (V)	T_A = −40°C to +85°C		Units	Conditions
				Min	Max		
V_{IK}	Input Clamp Diode Voltage		2.7		−1.2	V	I_I = −18 mA
V_{IH}	Input HIGH Voltage		2.7–3.6	2.0		V	$V_O \le 0.1V$ or
V_{IL}	Input LOW Voltage		2.7–3.6		0.8		$V_O \ge V_{CC} - 0.1V$
V_{OH}	Output HIGH Voltage		2.7–3.6	V_{CC} − 0.2		V	I_{OH} = −100 µA
			2.7	2.4		V	I_{OH} = −8 mA
			3.0	2.0		V	I_{OH} = −32 mA
V_{OL}	Output LOW Voltage		2.7		0.2	V	I_{OL} = 100 µA
			2.7		0.5	V	I_{OL} = 24 mA
			3.0		0.4	V	I_{OL} = 16 mA
			3.0		0.5	V	I_{OL} = 32 mA
			3.0		0.55	V	I_{OL} = 64 mA
$I_{I(HOLD)}$	Bushold Input Minimum Drive		3.0	75		µA	V_I = 0.8V
				−75		µA	V_I = 2.0V
$I_{I(OD)}$	Bushold Input Over-Drive		3.0	500		µA	(Note 4)
	Current to Change State			−500		µA	(Note 5)
I_I	Input Current		3.6		10	µA	V_I = 5.5V
		Control Pins	3.6		±1	µA	V_I = 0V or V_{CC}
		Data Pins	3.6		−5	µA	V_I = 0V
					1	µA	$V_I = V_{CC}$
I_{OFF}	Power Off Leakage Current		0		±100	µA	$0V \le V_I$ or $V_O \le 5.5V$
$I_{PU/PD}$	Power up/down 3-STATE		0–1.5V		±100	µA	V_O = 0.5V to 3.0V
	Output Current						V_I = GND or V_{CC}
I_{OZL}	3-STATE Output Leakage Current		3.6		−5	µA	V_O = 0.0V
I_{OZH}	3-STATE Output Leakage Current		3.6		5	µA	V_O = 3.6V
I_{OZH}+	3-STATE Output Leakage Current		3.6		10	µA	$V_{CC} < V_O \le 5.5V$
I_{CCH}	Power Supply Current		3.6		0.19	mA	Outputs HIGH
I_{CCL}	Power Supply Current		3.6		5	mA	Outputs LOW
I_{CCZ}	Power Supply Current		3.6		0.19	mA	Outputs Disabled
I_{CCZ}+	Power Supply Current		3.6		0.19	mA	$V_{CC} \le V_O \le 5.5V$
							Outputs Disabled
ΔI_{CC}	Increase in Power Supply Current		3.6		0.2	mA	One Input at V_{CC} − 0.6V
	(Note 6)						Other Inputs at V_{CC} or GND

Note 4: An external driver must source at least the specified current to switch from LOW-to-HIGH.

Note 5: An external driver must sink at least the specified current to switch from HIGH-to-LOW.

Note 6: This is the increase in supply current for each input that is at the specified voltage level rather than V_{CC} or GND.

Dynamic Switching Characteristics (Note 7)

Symbol	Parameter	V_{CC} (V)	T_A = 25°C			Units	Conditions
			Min	Typ	Max		C_L = 50 pF, R_L = 500Ω
V_{OLP}	Quiet Output Maximum Dynamic V_{OL}	3.3		0.8		V	(Note 8)
V_{OLV}	Quiet Output Minimum Dynamic V_{OL}	3.3		−0.8		V	(Note 8)

Note 7: Characterized in SOIC package. Guaranteed parameter, but not tested.

Note 8: Max number of outputs defined as (n). n−1 data inputs are driven 0V to 3V. Output under test held LOW.

AC Electrical Characteristics

Symbol	Parameter		$T_A = -40°C$ to $+85°C$, $C_L = 50$ pF, $R_L = 500\Omega$				Units
			$V_{CC} = 3.3V \pm 0.3V$		$V_{CC} = 2.7V$		
			Min	Max	Min	Max	
f_{MAX}	Maximum Clock Frequency		150		150		MHz
t_{PLH}	Propagation Delay Data to Output		1.8	5.7	1.8	6.3	ns
t_{PHL}	Clock to A or B		1.8	5.0	1.8	5.6	
t_{PLH}	Propagation Delay Data to Output		1.3	4.6	1.3	5.0	ns
t_{PHL}	Data to A or B		1.3	4.6	1.3	5.3	
t_{PLH}	Propagation Delay Data to Output		1.5	5.5	1.5	6.5	ns
t_{PHL}	SBA or SAB to A or B		1.5	5.5	1.5	6.3	
t_{PZH}	Output Enable Time		1.1	5.7	1.1	6.8	ns
t_{PZL}	$\overline{OE}$ to A or B		1.1	6.3	1.1	7.3	
t_{PHZ}	Output Disable Time		1.9	5.7	2.3	6.1	ns
t_{PLZ}	$\overline{OE}$ to A or B		1.6	5.5	2.3	5.9	
t_{PZH}	Output Enable Time		1.3	6.1	1.3	6.7	ns
t_{PZL}	DIR to A or B		1.3	6.7	1.3	7.7	
t_{PHZ}	Output Disable Time		1.5	6.2	1.5	7.1	ns
t_{PLZ}	DIR to A or B		1.5	5.6	1.5	6.3	
t_W	Pulse Duration	Clock HIGH or LOW	3.3		3.3		ns
t_S	Setup Time	A or B Before Clock, Data HIGH	1.2		1.5		ns
		A or B Before Clock, Data LOW	1.6		2.2		
t_H	Hold Time	A or B after Clock	0.8		0.8		ns
t_{OSHL}	Output to Output Skew (Note 9)			1.0		1.0	ns
t_{OSLH}				1.0		1.0	


Note 9: Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t_{OSHL}) or LOW-to-HIGH (t_{OSLH}).

Capacitance (Note 10)

Symbol	Parameter	Conditions	Typical	Units
C_{IN}	Input Capacitance	$V_{CC} = 0V$, $V_I = 0V$ or V_{CC}	4	pF
$C_{I/O}$	Input/Output Capacitance	$V_{CC} = 3.0V$, $V_O = 0V$ or V_{CC}	8	pF


Note 10: Capacitance is measured at frequency f = 1 MHz, per MIL-STD-883B, Method 3012.

Physical Dimensions inches (millimeters) unless otherwise noted



24-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300 Wide
Package Number M24B

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



24-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC24

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com