


DESCRIPTION: FEMALE - SOLDER CUP - MACHINED - ECONOMY - IP67



WILL ACCEPT
26-20 AWG WIRE





DIMENSIONS(mm)						
SIZE	$A^{+0.39}_{-0.39}$	$B^{+0.25}_{-0.25}$	$C^{+0.25}_{-0.25}$	$D^{+0.25}_{-0.34}$	$E^{+0.38}_{-0.38}$	$F^{+0.25}_{-0.25}$
9	30.81	24.99	16.33	7.90	12.55	10.80
15	39.19	33.32	24.66	7.90	12.55	10.80
25	53.04	47.04	38.38	7.90	12.55	10.80

SPECIFICATIONS:

MATERIALS:

INSULATOR:	GLASS-FILLED NYLON THERMOPLASTIC, UL94 V-0
PROCESS TEMP:	260°C
CONTACTS:	GOLD PLATED BRASS
SHELL:	NICKEL PLATED STEEL
SEALING MATERIAL:	F04 FLEXIBLE ADHESIVE

ELECTRICAL:

RATED CURRENT:	5A
WORKING VOLTAGE:	250VAC
INSULATION RESISTANCE:	1000 MOhms MIN.
CONTACT RESISTANCE:	15 mOhms MAX.

ENVIRONMENT:

OPERATING TEMPERATURE:	-55°C TO +125°C

MEETS IP67 STANDARDS
(SEE PAGE 2 FOR SEALING DETAILS)

772-EYY-20YRYY1

SERIES
POSITIONS
- 09
- 15
- 25

GENDER
- 2 = FEMALE

TERMINATION
- 0 = SOLDER CUP

SHELL PLATING
- 3 = NICKEL

HARDWARE OPTIONS
- 00 = NO HARDWARE
- 01 = 0.065" CLINCH NUT, BOARD SIDE

PLATING OPTIONS
- 1 = GOLD FLASH

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: C. SMITH

DATE: 03/26/2009

NorComp

SCALE: NTS


SHEET 1 OF 2


REV 9

DWG NO. 772-EYY-20YRYY1

DESCRIPTION: FEMALE - SOLDER CUP - MACHINED - ECONOMY - IP67

SEALING PROCESS






DETAIL A-A

HARDWARE OPTION

01X ..... 0.065" (BOARD SIDE)



RoHS COMPLIANT

UNITS = inch

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:	DATE:
C. SMITH	03/26/2009

NorComp

SCALE:	SHEET	OF	REV
NTS	2	2	9

DWG NO. 772-EYY-20YRYY1