




SPECIFICATIONS:

MATERIALS:
HOUSING: PBT, UL94 V-0, BLACK
CONTACTS: GOLD PLATED BRASS
NUT: SEE P/N KEY BELOW
SHELL: SEE P/N KEY BELOW
ORING: NBR, BLACK


ELECTRICAL:
RATED CURRENT: 3A
RATED VOLTAGE: 60V
INSULATION RESISTANCE: 100 MOhms MIN.
CONTACT RESISTANCE: 10 mOhms MAX.
MAX WIRE AWG: 24 AWG

ENVIRONMENT:
OPERATING TEMPERATURE: -40°C TO +85°C
WATER PROOF: IP66/IP67 (SEE NOTE BELOW)

WIRE AWG MAX: 22AWG (Ø0.88mm ID)



WHEN MATING WITH NORCOMP CONNECTORS, ONLY AN IP66 RATING CAN BE ACHIEVED IN MATING AREA BETWEEN CONNECTORS. CONNECTOR IS OTHERWISE IP67 AND MAY BE FULLY IP67 IF MATED WITH COMPETITOR PARTS.



854-004-103RLSY

1 = GOLD FLASH
4 = 10u" GOLD

03 = BRASS/NICKEL (B/N) SHELL & NUT
0S = (B/N) SHELL & STAINLESS STEEL NUT
SS = STAINLESS STEEL SHELL & NUT

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: M. SIGMON
DATE: 03/04/2016

UNITS = inch [mm] DO NOT SCALE FROM DRAWING

NorComp

SCALE: NTS
SHEET 1 OF 1
REV 9
DWG NO. 854-004-103RLSY