
RoHS Compliant

VERSION	DESCRIPTION	DATE
1.0	New Release	2017/3/30



PART NO	DRAWING NO	CABLE LENGTH "L"	COLOR
913S-2-5-00100-PL	671-457-A	1000±100	Yellow
913S-2-5-00200-PL	671-457-B	2000±100	Yellow
913S-2-5-00300-PL	671-457-C	3000±100	Yellow
913S-2-5-00500-PL	671-457-D	5000±100	Yellow
913S-2-5-00700-PL	671-457-E	7000±100	Yellow
913S-2-5-01000-PL	671-457-F	10000±100	Yellow
913S-2-5-01500-PL	671-457-G	15000±100	Yellow
913S-2-5-02000-PL	671-457-H	20000±100	Yellow
913S-2-5-02500-PL	671-457-I	25000±100	Yellow

NOTES:

Insertion loss < 0.3 dB

Return loss > 50 dB

No.	Description
6	Dust Cover
5	Shrinkage Tube
4	1/2 Code
3	ST SM Connector (Metal housing Yellow boot)
2	LC SM Duplex Connector (Blue housing White boot)
1	2.0mm,Duplex,SM-9/125 G652D, OFNP, Optical Fiber Cable(Yellow)

CnC Tech, LLC

Industrial Cable and Connector Technology

	TITLE	Patch Cord, LC-ST,SM-9/125 G652D, Duplex, OFNP, yellow, 2.0mm, xxM			
UNIT mm	P/N	above	DRAWN BY		
unless otherwise stated Tolerances mm XXX.XX ±0.3 XX.XX ±0.2 X.XX ±0.1 angular ±2°	Customer P/N	913S-2-5-0xxxx-PL	CHECK BY		
	SIZE A4 / SCALE Free	PAGE 1/1	APPROVAL BY		