

4G/3G/2G External Weatherproof Patch Antenna



APAMS-103

Request Samples



Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

Description

This weatherproof 4G/3G/2G external patch antenna delivers robust cellular connectivity across 698 - 960 MHz and 1710 - 2700 MHz bands. Housed in a low-profile 78 x 25 x 3.8 mm IP67-rated enclosure, it achieves a high peak gain of 7 dBi with 68% total efficiency for extended range and reliable performance in harsh environments. Supporting LTE-M, NB-IoT, and LTE CAT 1 through CAT 20, this RoHS-compliant, MSL Level 1 antenna features customizable cable and connector options. It is ideal for smart home networking, telecommunications, and traffic monitoring applications requiring durable outdoor installation.



Features

- Frequency Range: 698 - 960 / 1710 - 2700 MHz
- Low Profile with Size 78 x 25 x 3.8 mm
- High Peak Gain up to 7 dBi
- Total Efficiency: 68 %
- Custom Cable Length Options Available
- [RoHS Compliant](#) | [MSL Level 1](#)

Applications

- LTE-M, Cat M, Cat M1, NB-IoT
- LTE CAT 1 up to CAT 20 Supported
- Smart Home Networking
- Networking & Telecommunication
- Traffic Control and Monitoring

Ordering Information

Part Number	Description	Connector Option
APAMS-103	4G/3G/2G External Weatherproof Patch Antenna with 2000 mm RG-174 cable length & SMA(M) connectors	SMA(M)
APAMS-103-1	4G/3G/2G External Weatherproof Patch Antenna with 1000 mm RG-174 cable length & SMA(M) connectors	SMA(M)

Note: Other options not listed may be available upon request via [Abracon online support](#)



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 07-21-26

ABRACON IS
ISO9001-2015
CERTIFIED

**APAMS-103**

Request Samples



Check Inventory

**78 x 25 x 3.8 mm****RoHS Compliant****MSL Level = 1****Electrical Specification**

Parameters	Typ.		Units
Frequency	698 - 960	1710 - 2700	MHz
Return Loss (Typ.)	< -5.8	< -9.6	dB
VSWR (Typ.)	≤ 3.1	≤ 2.0	:1
Peak Gain ⁽¹⁾	4.3	7.0	dBi
Maximum Total Efficiency ⁽¹⁾	68	49	%
Average Total Efficiency ⁽¹⁾	50	40	%
Minimum Total Efficiency ⁽¹⁾	38	35	%
Polarization	Linear		-
Impedance	50		Ω
Input Power	5		W

Please note: All measurement data is based on the standard configuration (conducted in free space unless otherwise specified).

Mechanical Specification

Parameter	Specification
Antenna Dimension	78 x 25 x 3.8 mm
Housing Material	ABS (Black)
Mounting Type	Adhesive Mount
RF Cable Type	RG-174
RF Cable Length ⁽¹⁾	1000 mm / 2000 mm
RF Connector	SMA (Male)

(1): Fully customizable RF Cable length

Environmental Specification

Parameter	Specification
Operating Temperature	-45°C to +85°C
Storage Temperature	-45°C to +85°C
RoHS Compliance	Yes
Relative Humidity	Up to 95%



APAMS-103

Request Samples







Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

Product Dimensions



Parameters	Description
L1	1000 mm / 2000 mm
Cable Type	RG174
Connector	SMA (M)
Housing	Black
Mounting Type	Adhesive Tab

Unit: inches [mm]



APAMS-103

Request Samples




Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

Measurement Setup





APAMS-103

Request Samples





Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

Reflection Characteristics – Return Loss & VSWR (with 1 m cable length)





APAMS-103

Request Samples




Check Inventory




78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

LTE Radiation Characteristics – Peak Gain & Efficiency (with 1 m cable length)

Peak Gain



Total Efficiency (%)





APAMS-103

Request Samples




Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

LTE Radiation Characteristics – 3D & 2D Pattern (with 1 m cable length)

3D & 2D Pattern @ 698 MHz





APAMS-103

Request Samples




Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

3D & 2D Pattern @ 900 MHz





APAMS-103

Request Samples




Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

3D & 2D Pattern @ 1710 MHz





APAMS-103

Request Samples




Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

3D & 2D Pattern @ 2600 MHz



4G/3G/2G External Weatherproof Patch Antenna



APAMS-103

Request Samples



Check Inventory



78 x 25 x 3.8 mm
RoHS Compliant
MSL Level = 1

Packaging

Each 475 x 215 x 215 mm size carton includes 100 pieces of antenna.



ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf ('COTS'), which are designed, intended, and validated for use in commercial, industrial, and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 07-21-26

ABRACON IS
ISO9001-2015
CERTIFIED