

ASD10H

ISOLATED AND REGULATED 10-WATT OPEN FRAME DC/DC CONVERTER

The isolated and regulated 10-watt open-frame DC/DC converter is a cutting-edge solution for your power supply requirements. This converter boasts a wide 4:1 input range of 9 to 36V or 18 to 75V options available, catering to a variety of voltage needs. Its high efficiency and regulated outputs ensure stable and consistent power delivery, while the 1500VDC isolation provides a layer of safety and protection. The converter also features an integral finned heatsink, enhancing heat dissipation and overall performance. Trust in this converter for optimal functionality and reliability in all your power supply applications.



HOW TO ORDER

ASD10H-12S3

- OUTPUT VOLTAGE
  - 3 = 3.3 VDC
  - 5 = 5 VDC
  - 9 = 9 VDC
  - 12 = 12 VDC
  - 15 = 15 VDC
- NUMBER OF OUTPUTS
  - S = SINGLE OUTPUT
  - D = DOUBLE OUTPUT
- INPUT RANGE VOLTAGE
  - 12 = 9–36 VDC
  - 48 = 18–75 VDC
- H: OPEN FRAME
- OUTPUT POWER: 10W
- FAMILY: ASD SERIES

FEATURES

DC INPUT WIDE 4:1
Nominal: 12VDC 48VDC
Range: 9-36VDC 18-75VDC

OUTPUT RANGE
10 Watts Output

OPERATING TEMPERATURE
-25 to +71°C(FL)


SAFETY APPROVALS
UL60950-1 2nd ed./ CAN/CSA C22.2 60950-1 2nd ed.

SHOCK/VIBRATION
MIL-STD 810°C

HIGH EFFICIENCY

ISOLATION
1500VDC (48V)

INTEGRAL FINNED HEATSINK



ASD10H


ISOLATED AND REGULATED 10-WATT OPEN FRAME DC/DC CONVERTER

PARAMETERS	ASD10H
INPUT SPECIFICATIONS	
Input Voltage, Nominal	12VDC 48VDC
Input Voltage Ranges	9-36 18-75 VDC
Input Surge Voltage	50V (12V Models), * 100V (48V Models), * 10 mS duration, min.
OUTPUT SPECIFICATIONS	
Voltage and Current	See Selection Chart
Preset Accuracy	Singles: +/- 3% max. Duals: +/- 4% max.
Cross Regulation (Duals)	5-8% typ.
Load Regulation	singles: +/- 0.5%
20% - FL	duals: +/-1%, +/-3% (5V mod)
Line Regulation	singles: +/- 0.5% duals: +/- 1%
Minimum Load	5% of Full Load
Ripple/Noise (Pk-Pk, typ)	(Note 1)
Single 3.3V	150mV
Single 5V	100mV (12Vin), 150mV (48Vin)
Single 9,12V	50mV (12Vin), 100mV (48Vin)
Single 15V	50mV
Dual 5V	150mV
Dual 12, 15V	100mV
Overvoltage Protection	Clamp, 130-150%*
Short Circuit Protection	Clamp, need to release load*

All specifications are typical at nominal input, full load, and 25°C unless otherwise noted

* These are stress ratings. Exposure of the devices to any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than the standard operating conditions is neither warranted nor implied.

GENERAL SPECIFICATIONS	
On/Off Control	(Ref to - Input pin) Logic "1"/Open=ON Logic "0"/GND=OFF
Shutdown Idle Current	15mA
Input-Out Isolation	1500VDC (48V) 500 VDC (12V)
In/Out Capacitance	1000 pF
Efficiency at nom. Input	12V: 72%-81%, typ. 48V: 77%-82%, typ.



ASD10H


ISOLATED AND REGULATED 10-WATT OPEN FRAME DC/DC CONVERTER

PARAMETERS	ASD10H
ENVIRONMENTAL SPECIFICATIONS	
Oper. Temperature	-25 to +71°C(FL)
Storage Temperature	-40 to +125°C *
Maximum Case Temp	110°C *
MTBF	1,000,000 Hrs Mil Std 217, 25°C
Shock/Vibration	To MIL-STD 810°C
Safety UL/cUL	UL60950-1 2nd ed./ CAN/CSA C22.2 60950-1 2nd ed.
PHYSICAL SPECIFICATIONS	
Heatsink Material	Aluminum
Construction	Open Frame
Weight	0.57 oz, (16g)

NOTES


1. Ripple & Noise are measured by using a 20MHz bandwidth oscilloscope and terminating the output with a 47uF electrolytic capacitor paralleled with a 0.1uF ceramic capacitor

MECHANICAL DIMENSION



Pin#	Single Outputs	Dual Outputs
1	+ Input	+ Input
2	- Input	- Input
3	+ Output	+ Output
4	N / A	Common
5	- Output	- Output
6	Control	Control

TOLERANCES : .XX ± 0.5mm(0.02in)
: .XXX ± 0.25mm(0.01in)



ASD10H

ISOLATED AND REGULATED 10-WATT OPEN FRAME DC/DC CONVERTER

MODEL NUMBER	OUTPUT VOLTAGE	OUTPUT AMPS	INPUT RANGE
Single Output			
ASD10H-12S3	3.3 VDC	2.5	9-36 VDC
ASD10H-48S3	3.3 VDC	2.5	18-75 VDC
ASD10H-12S5	5 VDC	2	9-36 VDC
ASD10H-48S5	5 VDC	2	18-75 VDC
ASD10H-12S9	9 VDC	1.1	9-36 VDC
ASD10H-48S9	9 VDC	1.1	18-75 VDC
ASD10H-12S12	12 VDC	0.83	9-36 VDC
ASD10H-48S12	12 VDC	0.83	18-75 VDC
ASD10H-12S15	15 VDC	0.67	9-36 VDC
ASD10H-48S15	15 VDC	0.67	18-75 VDC
Dual Output			
ASD10H-12D5	+/-5 VDC	+/-1	9-36 VDC
ASD10H-48D5	+/-5 VDC	+/-1	18-75 VDC
ASD10H-12D12	+/-12 VDC	+/-0.42	9-36 VDC
ASD10H-48D12	+/-12 VDC	+/-0.42	18-75 VDC
ASD10H-12D15	+/-15 VDC	+/-0.33	9-36 VDC
ASD10H-48D15	+/-15 VDC	+/-0.33	18-75 VDC

OUTPUT DERATING CURVE

