
ADSANTEC
Ultra High-Speed Mixed Signal ASICs

Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505

Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com

ASNT5131-PQC
DC-17*Gbps* Limiting Amplifier

- Broadband (DC-17*Gbps*) limiting amplifier
- Exhibits low jitter and limited temperature variation over industrial temperature range
- 100*MHz* of bandwidth for the amplitude adjustment tuning port
- Ideal for high speed proof-of-concept prototyping
- Fully differential CML input interfaces
- Fully differential CML output interface with adjustable SE amplitude from 0*V* to 1.0*V*
- Single +5.0*V* or -5.0*V* power supply
- Power consumption: 500*mW*
- Fabricated in SiGe for high performance, yield, and reliability
- Standard MLF/QFN 24-pin package



Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505
Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com

DESCRIPTION




Fig. 1. Functional Block Diagram

The temperature stable ASNT5131-PQC SiGe IC provides extremely low jitter broadband signal amplitude control capability, and is intended for use in high-speed measurement / test equipment. The IC shown in Fig. 1 can process a high-speed data signal dp/dn and deliver a high-speed data output signal qp/qn with its output signal amplitude controlled by tuning ports tp/tn.

The part's I/O's support the CML logic interface with on chip 50*Ohm* termination to vcc and may be used differentially, AC/DC coupled, single-ended, or in any combination (see also POWER SUPPLY CONFIGURATION). In the DC-coupling mode, the input signal's common mode voltage should comply with the specifications shown in ELECTRICAL CHARACTERISTICS. In the AC-coupling mode, the input termination provides the required common mode voltage automatically. The differential DC signaling mode is recommended for optimal performance.

POWER SUPPLY CONFIGURATION

The part can operate with either negative supply (vcc = 0.0*V* = ground and vee = −5.0*V*), or positive supply (vcc = +5.0*V* and vee = 0.0*V* = ground). In case of the positive supply, all I/Os need AC termination when connected to any devices with 50*Ohm* termination to ground. Different PCB layouts will be needed for each different power supply combination.

All the characteristics detailed below assume vcc = 0.0*V* and vee = -5.0*V*.

Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505
Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com

ABSOLUTE MAXIMUM RATINGS

Caution: Exceeding the absolute maximum ratings shown in Table 1 may cause damage to this product and/or lead to reduced reliability. Functional performance is specified over the recommended operating conditions for power supply and temperature only. AC and DC device characteristics at or beyond the absolute maximum ratings are not assumed or implied. All min and max voltage limits are referenced to ground.

Table 1. Absolute Maximum Ratings

Parameter	Min	Max	Units
Supply Voltage (vee)		-5.5	*V*
Power Consumption		0.55	*W*
RF Input Voltage Swing (SE)		1.0	*V*
Case Temperature		+90	*ºC*
Storage Temperature	-40	+100	*ºC*
Operational Humidity	10	98	%
Storage Humidity	10	98	%

TERMINAL FUNCTIONS

TERMINAL			DESCRIPTION
Name	**No.**	**Type**	
High-Speed I/Os			
dp	20	CML input	Differential high-speed signal inputs with internal SE 50*Ohm* termination to vcc.
dn	22		
qp	10	CML output	Differential high-speed signal outputs with internal SE 50*Ohm* termination to vcc. Require external SE 50*Ohm* termination to vcc.
qn	8		
tp	4	CML input	Differential output amplitude control signal with internal 2*KOhm* termination to vcc.
tn	14		
Supply and Termination Voltages			
Name	**Description**		**Pin Number**
vcc	Positive power supply (+5.0*V* or 0)		1, 2, 3, 5, 7, 9, 11, 13, 15, 16, 17, 19, 21, 23
vee	Negative power supply (0*V* or -5.0*V*)		6, 12, 18, 24

Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505

Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com

ELECTRICAL CHARACTERISTICS

PARAMETER	MIN	TYP	MAX	UNIT	COMMENTS
General Parameters					
vee	-4.7	-5.0	-5.3	*V*	±6%
vcc		0.0		*V*	External ground
*I*vee		100		*mA*	
Power consumption		500		*mW*	
Junction temperature	-40	25	125	*°C*	
HS Input Data (dp/dn)					
Frequency	DC		17	*Gbps*	
Swing	0.05		1.0	*V*	Differential or SE, p-p
CM Voltage Level	vcc-0.8		vcc	*V*	Must match for both inputs
HS Output Data (qp/qn)					
Frequency	DC		17	*Gbps*	
Logic "1" level		vcc		*V*	
Logic "0" level	vcc-1.0	vcc-0.5	vcc	*V*	With external 50*Ohm* DC termination, and full range of tp/tn control signal
Rise/Fall times	15	17	19	*ps*	20%-80%
Output Jitter			1	*ps*	Peak-to-peak
Duty cycle	45	50	55	*%*	
Tuning port (tp/tn)					
Bandwidth	DC		100	*MHz*	
Swing		vcc-0.5		*V*	Differential
CM Voltage Level	vcc-0.5		vcc	*V*	Must match for both inputs

PACKAGE INFORMATION


The chip die is housed in a standard 24-pin QFN package shown in Fig. 2. It is recommended that the center heat slug located on the back side of the package is soldered to the vee plain that is ground for the positive supply or power for the negative supply.

The part's identification label is ASNT5131-PQC. The first 8 characters of the name before the dash identify the bare die including general circuit family, fabrication technology, specific circuit type, and part version while the 3 characters after the dash represent the package's manufacturer, type, and pin out count.

This device complies with the Restriction of Hazardous Substances (RoHS) per 2011/65/EU for all ten substances.

Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505

Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com



SYMBOL	MILLIMETERS		INCHS	
	MIN	MAX	MIN	MAX
A, V	0.80	1.00	0.032	0.040
A, W	0.70	0.80	0.027	0.032
A1	0.00	0.05	0.000	0.002
A3	0.20 REF		0.008 REF	
b	0.18	0.30	0.007	0.012
D	4.00 BSC		0.158 BSC	
D2	2.50	2.80	0.098	0.110
E	4.00 BSC		0.158 BSC	
E2	2.50	2.80	0.098	0.110
e	0.50 BSC		0.050 BSC	
K	0.20	–	0.008	–
L	0.30	0.50	0.012	0.020
L1	0.03	0.15	0.001	0.006
θ	0°	12°	0°	12°

NOTES:
1. PACKAGE CONFORMS TO JEDEC MO-220, V/WGGD-6
2. L/F MATERIAL : OLIN 194 HH or FH COPPER THICKNESS : 0.20±0.008
3. PLATING : 1.27um MIN. Ni, 0.25um MIN. Pd, 0.076um MIN. Au
4. OPTIONAL PLATING: 1.27um MIN. Ni, 0.25um MIN. Pd.
5. DIM AND TOL CONFORM TO ASME Y14.5M-1994
6. ALL DIM ARE IN MM, ⌖ IS IN DEG
7. DIM b APPLIES TO METALLIZIED TERMINAL AND IS MEASURED BETWEEN 0.15mm AND 0.30mm FROM TIP.
8. PACKAGE MAY HAVE PULL BACK (L1) MAYBE PRESENT. L MINUS L1 TO BE EQUAL TO OR GREATER THAN 0.3mm.

ALL INFORMATION CONTAINED HEREON IS THE PROPERTY OF PROMEX, INC. AND IS CONSIDERED PROPRIETARY AND SUBJECT TO RETURN UPON DEMAND. ACCEPTANCE AND RETENTION HEREOF SIGNIFIES AGREEMENT BY THE RECIPIENT THAT THE INFORMATION WILL NOT BE DISCLOSED TO OTHERS NOR USED CONTRAY TO THE INTEREST OF PROMEX, INC. WITHOUT PRIOR WRITTEN PERMISSION.

MATERIAL: OLIN C194 Cu
FINISH:
CONTRACT NO.
DRAWN WAYNE LOUIE 11/03
CHECK WAYNE LOUIE 11/03
DESIGN WAYNE LOUIE 11/03
DESIGN ACTIVITY
CUSTOMER
USED ON: GENERAL USE
PROMEX 3075 Oakmead Village Drive Santa Clara, CA 95051
TITLE: QFN-4mm, 24LD PACKAGE OUTINE
SIZE A | DWG NO. 235-00039_QPO | REV A
CAGE CODE: 3FY32 | FILE NAME: 235-00039_QPO.dwg | SHEET 1 or 1

Fig. 2. QFN 24-Pin Package Drawing (All Dimensions in mm)

Advanced Science And Novel Technology Company, Inc.
2790 Skypark Drive Suite 112, Torrance, CA 90505

Offices: 310-530-9400 / Fax: 310-530-9402
www.adsantec.com

REVISION HISTORY

Revision	Date	Changes
5.1.2	04-2020	Updated Package Information
5.0.2	07-2019	Updated Letterhead
5.0.1	03-2013	Corrected title Revised package pin out drawing Revised functional block diagram Revised description Added power supply configuration Added absolute maximum ratings Revised terminal functions Revised electrical characteristics Added package information and mechanical drawing Format correction
4.0	02-2008	Revised electrical characteristics section Revised packaging information section
3.0	06-2007	Revised electrical characteristics section
2.0	04-2007	Revised terminal functions section
1.0	01-2007	First release