

[illegible]

	1	2	3	4	5	6	7																																																																																										
A	Female ④							A																																																																																									
B								B																																																																																									
C	15,26,44,62 Positions							C																																																																																									
D	78 Positions							D																																																																																									
E	78 Positions							E																																																																																									
F	78 Positions							F																																																																																									
G	RoHS compliant Unit: mm File No.: E198287 <table><tr><td>Scale</td><td>Free</td><td>⑦</td><td>Correct the male terminal on page 1</td><td>11.07.2024</td><td>Peter</td><td></td><td>Date</td><td>Name</td><td colspan="2" rowspan="3">Description: D-Sub Connector Female 180° THT #4-40UNC Nut</td></tr><tr><td>TOLERANCE</td><td></td><td>⑥</td><td>Add the miss dimension</td><td>24.08.2022</td><td>Daniel</td><td>Drawn</td><td>22.11.2019</td><td>Carson</td></tr><tr><td>X.</td><td>±0.38</td><td>⑤</td><td>Add the dimension tolerance</td><td>30.03.2022</td><td>Peter</td><td>Approved</td><td>11.07.2024</td><td>Peter</td></tr><tr><td>X.X</td><td>±0.25</td><td>④</td><td>Add page 3~8</td><td>22.11.2019</td><td>Carson</td><td></td><td></td><td></td><td colspan="2">ASSMANN WSW-No. A-HD x xx PP/Z-UNC1</td></tr><tr><td>X.XX</td><td>±0.13</td><td>③</td><td>Add solder temperature</td><td>15.04.2019</td><td>Xavier</td><td colspan="3" rowspan="3"></td><td colspan="2">Drawing-No.</td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Correct the dimensioning of "H"</td><td>27.10.2016</td><td>Amy</td><td colspan="2">ASS 4896 CO</td></tr><tr><td>X.°</td><td>±3°</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td></tr><tr><td>X.X°</td><td>±1.0°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td colspan="2">rev07</td></tr><tr><td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td colspan="2">Sheet 4/8</td></tr></table>							Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Female 180° THT #4-40UNC Nut		TOLERANCE		⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson	X.	±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter	X.X	±0.25	④	Add page 3~8	22.11.2019	Carson				ASSMANN WSW-No. A-HD x xx PP/Z-UNC1		X.XX	±0.13	③	Add solder temperature	15.04.2019	Xavier				Drawing-No.		DIM	TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy	ASS 4896 CO		X.°	±3°	Id.	Modification	Date	Name	Customer-No.		X.X°	±1.0°								rev07		Angle	TOL								Sheet 4/8		G
Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Female 180° THT #4-40UNC Nut																																																																																								
TOLERANCE		⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson																																																																																									
X.	±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter																																																																																									
X.X	±0.25	④	Add page 3~8	22.11.2019	Carson				ASSMANN WSW-No. A-HD x xx PP/Z-UNC1																																																																																								
X.XX	±0.13	③	Add solder temperature	15.04.2019	Xavier				Drawing-No.																																																																																								
DIM	TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy				ASS 4896 CO																																																																																								
X.°	±3°	Id.	Modification	Date	Name				Customer-No.																																																																																								
X.X°	±1.0°								rev07																																																																																								
Angle	TOL								Sheet 4/8																																																																																								
H								H																																																																																									
	1	2	3	4	5	6	7																																																																																										

NOTES:


MATERIAL

- 1.Insulator Material:Glass-filled thermoplastic PBT,UL94V-0
- 2.Contact Material:Copper alloy, Gold flash selective gold
- 3.Shell: Steel, 100u" Tin over 50u" Min Copper
- 4.Clinch Nut: Brass, 100u" min Nickel Plated


ELECTRICAL

- 1.Current Rating : 3AMP
- 2.Voltage Rating : 250V AC/rms 60Hz
- 3.Contact Resistance: 20mΩ Max at 100 mA DC
- 4.Insulation Resistance: 1000MΩ at 500 VDC
- 5.Withstand Voltage: 1000V AC/rms 60Hz for 1 minute
- 6.Operating Temperature:-55°C+105°C
- 7.Solder Temperature: 220°C 5s max.


P.C.B LAYOUT PATTERN



15 POSITION FEMALE



26,44,62 POSITION FEMALE



78 POSITION MALE/FEMALE

Dimensions

Positions	A	B	D	E	F	G	H
15	30.81	24.99	16.33	2.29	19.20	1.145	7.04
26	39.20	33.30	24.70	2.29	27.70	1.145	6.88
44	53.05	47.04	38.40	2.29	41.10	1.145	6.88
62	69.40	63.50	54.80	2.41	57.30	1.205	7.00

		1	2	3	4	5	6	7																																										
A	Male ④ 15,26,44,62 Positions	NOTES: MATERIAL 1.Insulator Material:Glass-filled thermoplastic PBT,UL94V-0 2.Contact Material:Copper alloy, Gold flash selective gold 3.Shell: Steel, 100u" Tin over 50u" Min Copper 4.Clinch Nut: Brass, Nickel Plated ELECTRICAL 1.Current Rating : 3AMP 2.Voltage Rating : 250V AC/rms 60Hz 3.Contact Resistance: 20mΩ Max at 100 mA DC 4.Insulation Resistance: 1000MΩ at 500 VDC 5.Withstand Voltage: 500V AC/rms 60Hz for 1 minute 6.Operating Temperature:-55°C+105°C 7.Solder Temperature: 220°C 5s max. Order Code: A-HD x xx PP/Z-UNC2 Contact style: F - Female, S - Male No. of Contacts: 15 / 26 / 44 / 62 / 78 Standard: Quality class III								A																																								
B										B																																								
C										C																																								
D		78 Positions P.C.B LAYOUT PATTERN 15 POSITION MALE 26,44,62 POSITION MALE 78 POSITION MALE/FEMALE								D																																								
E		Dimensions <table><tr><th>Positions</th><th>A</th><th>B</th><th>C</th><th>E</th><th>F</th><th>G</th><th>H</th></tr><tr><td>15</td><td>30.81</td><td>24.99</td><td>16.92</td><td>2.29</td><td>19.20</td><td>1.145</td><td>7.04</td></tr><tr><td>26</td><td>39.20</td><td>33.30</td><td>25.25</td><td>2.29</td><td>27.70</td><td>1.145</td><td>6.88</td></tr><tr><td>44</td><td>53.05</td><td>47.04</td><td>38.96</td><td>2.29</td><td>41.10</td><td>1.145</td><td>6.88</td></tr><tr><td>62</td><td>69.40</td><td>63.50</td><td>55.42</td><td>2.41</td><td>57.30</td><td>1.205</td><td>7.00</td></tr></table>								Positions	A	B	C	E	F	G	H	15	30.81	24.99	16.92	2.29	19.20	1.145	7.04	26	39.20	33.30	25.25	2.29	27.70	1.145	6.88	44	53.05	47.04	38.96	2.29	41.10	1.145	6.88	62	69.40	63.50	55.42	2.41	57.30	1.205	7.00	E
Positions		A	B	C	E	F	G	H																																										
15	30.81	24.99	16.92	2.29	19.20	1.145	7.04																																											
26	39.20	33.30	25.25	2.29	27.70	1.145	6.88																																											
44	53.05	47.04	38.96	2.29	41.10	1.145	6.88																																											
62	69.40	63.50	55.42	2.41	57.30	1.205	7.00																																											
F									F																																									
G	RoHS compliant Unit: mm File No.: E198287		Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Male 180° THT #4-40UNC Nut	G																																					
TOLERANCE			⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson																																									
X.			±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter																																								
H			X.X	±0.25	④	Add page 3~8	22.11.2019	Carson					ASSMANN WSW-No. A-HD x xx PP/Z-UNC2	Drawing-No. ASS 4896 CO rev07 Customer-No. Sheet 5/8	H																																			
X.XX		±0.13	③	Add solder temperature	15.04.2019	Xavier																																												
DIM		TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy																																												
X.°		±3°	Id.	Modification	Date	Name																																												
X.X°		±1.0°																																																
Angle		TOL																																																

	1	2	3	4	5	6	7																																									
A	Female							A																																								
B	NOTES: MATERIAL 1.Insulator Material:Glass-filled thermoplastic PBT,UL94V-0 2.Contact Material:Copper alloy, Gold flash selective gold 3.Shell: Steel, 100u" Tin over 50u" Min Copper 4.Clinch Nut: Brass, 100u" min Nickel Plated ELECTRICAL 1.Current Rating : 3AMP 2.Voltage Rating : 250V AC/rms 60Hz 3.Contact Resistance: 20mΩ Max at 100 mA DC 4.Insulation Resistance: 1000MΩ at 500 VDC 5.Withstand Voltage: 1000V AC/rms 60Hz for 1 minute 6.Operating Temperature:-55°C+105°C 7.Solder Temperature: 220°C 5s max.							B																																								
C								C																																								
D	P.C.B LAYOUT PATTERN							D																																								
E	15 POSITION FEMALE 26,44,62 POSITION FEMALE 78 POSITION MALE/FEMALE							E																																								
F	Dimensions <table><tr><th>Positions</th><th>A</th><th>B</th><th>D</th><th>E</th><th>F</th><th>G</th><th>H</th></tr><tr><td>15</td><td>30.81</td><td>24.99</td><td>16.33</td><td>2.29</td><td>19.20</td><td>1.145</td><td>7.04</td></tr><tr><td>26</td><td>39.20</td><td>33.30</td><td>24.70</td><td>2.29</td><td>27.70</td><td>1.145</td><td>6.88</td></tr><tr><td>44</td><td>53.05</td><td>47.04</td><td>38.40</td><td>2.29</td><td>41.10</td><td>1.145</td><td>6.88</td></tr><tr><td>62</td><td>69.40</td><td>63.50</td><td>54.80</td><td>2.41</td><td>57.30</td><td>1.205</td><td>7.00</td></tr></table>							Positions	A	B	D	E	F	G	H	15	30.81	24.99	16.33	2.29	19.20	1.145	7.04	26	39.20	33.30	24.70	2.29	27.70	1.145	6.88	44	53.05	47.04	38.40	2.29	41.10	1.145	6.88	62	69.40	63.50	54.80	2.41	57.30	1.205	7.00	F
Positions	A	B	D	E	F	G	H																																									
15	30.81	24.99	16.33	2.29	19.20	1.145	7.04																																									
26	39.20	33.30	24.70	2.29	27.70	1.145	6.88																																									
44	53.05	47.04	38.40	2.29	41.10	1.145	6.88																																									
62	69.40	63.50	54.80	2.41	57.30	1.205	7.00																																									
G	RoHS compliant Unit: mm File No.: E198287		Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Female 180° THT #4-40UNC Nut		G																																		
			TOLERANCE	⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson																																						
			X.	±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter	ASSMANN WSW-No. A-HD x xx PP/Z-UNC2																																				
			X.X	±0.25	④	Add page 3~8	22.11.2019	Carson				Drawing-No.																																				
			X.XX	±0.13	③	Add solder temperature	15.04.2019	Xavier				ASS 4896 CO																																				
			DIM	TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy				rev07																																				
			X.°	±3°	Id.	Modification	Date	Name				Customer-No.																																				
			X.X°	±1.0°									Sheet 6/8																																			
			Angle	TOL																																												
	1	2	3	4	5	6	7																																									

	1	2	3	4	5	6	7																																									
A	Male ④							A																																								
B								B																																								
C								C																																								
D	⑤							D																																								
E	P.C.B LAYOUT PATTERN 15 POSITION MALE 26,44,62 POSITION MALE 78 POSITION MALE/FEMALE							E																																								
F	Dimensions <table><tr><th>Positions</th><th>A</th><th>B</th><th>C</th><th>E</th><th>F</th><th>G</th><th>H</th></tr><tr><td>15</td><td>30.81</td><td>24.99</td><td>16.92</td><td>2.29</td><td>19.20</td><td>1.145</td><td>7.04</td></tr><tr><td>26</td><td>39.20</td><td>33.30</td><td>25.25</td><td>2.29</td><td>27.70</td><td>1.145</td><td>6.88</td></tr><tr><td>44</td><td>53.05</td><td>47.04</td><td>38.96</td><td>2.29</td><td>41.10</td><td>1.145</td><td>6.88</td></tr><tr><td>62</td><td>69.40</td><td>63.50</td><td>55.42</td><td>2.41</td><td>57.30</td><td>1.205</td><td>7.00</td></tr></table>							Positions	A	B	C	E	F	G	H	15	30.81	24.99	16.92	2.29	19.20	1.145	7.04	26	39.20	33.30	25.25	2.29	27.70	1.145	6.88	44	53.05	47.04	38.96	2.29	41.10	1.145	6.88	62	69.40	63.50	55.42	2.41	57.30	1.205	7.00	F
Positions	A	B	C	E	F	G	H																																									
15	30.81	24.99	16.92	2.29	19.20	1.145	7.04																																									
26	39.20	33.30	25.25	2.29	27.70	1.145	6.88																																									
44	53.05	47.04	38.96	2.29	41.10	1.145	6.88																																									
62	69.40	63.50	55.42	2.41	57.30	1.205	7.00																																									
G	RoHS compliant Unit: mm File No.: E198287		Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Male 180° THT #4-40UNC Nut	G																																			
TOLERANCE			⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson																																							
X.			±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter																																						
X.X			±0.25	④	Add page 3~8	22.11.2019	Carson				ASSMANN WSW-No. A-HD x xx PP/Z-UNC3	H																																				
X.XX			±0.13	③	Add solder temperature	15.04.2019	Xavier				Drawing-No.																																					
DIM			TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy				ASS 4896 CO	rev07																																				
X.°			±3°	Id.	Modification	Date	Name				Customer-No.	Sheet 7/8																																				
X.X°			±1.0°																																													
Angle		TOL																																														
	1	2	3	4	5	6	7																																									

	1	2	3	4	5	6	7																																									
A	Female ④ ⑤ ⑥ ⑦							A																																								
B	NOTES: MATERIAL 1. Insulator Material: Glass-filled thermoplastic PBT, UL94V-0 2. Contact Material: Copper alloy, Gold flash selective gold 3. Shell: Steel, 100u" Tin over 50u" Min Copper 4. Boardlock: Brass, Tin Plated ELECTRICAL 1. Current Rating : 3AMP 2. Voltage Rating : 250V AC/rms 60Hz 3. Contact Resistance: 20mΩ Max at 100 mA DC 4. Insulation Resistance: 1000MΩ at 500 VDC 5. Withstand Voltage: 500V AC/rms 60Hz for 1 minute 6. Operating Temperature: -55°C+105°C 7. Solder Temperature: 220°C 5s max.							B																																								
C								C																																								
D	P.C.B LAYOUT PATTERN 15 POSITION FEMALE 26,44,62 POSITION FEMALE 78 POSITION MALE/FEMALE							D																																								
E	Dimensions <table><tr><th>Positions</th><th>A</th><th>B</th><th>D</th><th>E</th><th>F</th><th>G</th><th>H</th></tr><tr><td>15</td><td>30.81</td><td>24.99</td><td>16.33</td><td>2.29</td><td>19.20</td><td>1.145</td><td>7.04</td></tr><tr><td>26</td><td>39.20</td><td>33.30</td><td>24.70</td><td>2.29</td><td>27.70</td><td>1.145</td><td>6.88</td></tr><tr><td>44</td><td>53.05</td><td>47.04</td><td>38.40</td><td>2.29</td><td>41.10</td><td>1.145</td><td>6.88</td></tr><tr><td>62</td><td>69.40</td><td>63.50</td><td>54.80</td><td>2.41</td><td>57.30</td><td>1.205</td><td>7.00</td></tr></table>							Positions	A	B	D	E	F	G	H	15	30.81	24.99	16.33	2.29	19.20	1.145	7.04	26	39.20	33.30	24.70	2.29	27.70	1.145	6.88	44	53.05	47.04	38.40	2.29	41.10	1.145	6.88	62	69.40	63.50	54.80	2.41	57.30	1.205	7.00	E
Positions	A	B	D	E	F	G	H																																									
15	30.81	24.99	16.33	2.29	19.20	1.145	7.04																																									
26	39.20	33.30	24.70	2.29	27.70	1.145	6.88																																									
44	53.05	47.04	38.40	2.29	41.10	1.145	6.88																																									
62	69.40	63.50	54.80	2.41	57.30	1.205	7.00																																									
F								F																																								
G	RoHS compliant Unit: mm File No.: E198287		Scale	Free	⑦	Correct the male terminal on page 1	11.07.2024	Peter		Date	Name	Description: D-Sub Connector Female 180° THT #4-40UNC Nut		G																																		
			TOLERANCE		⑥	Add the miss dimension	24.08.2022	Daniel	Drawn	22.11.2019	Carson																																					
			X.	±0.38	⑤	Add the dimension tolerance	30.03.2022	Peter	Approved	11.07.2024	Peter																																					
			X.X	±0.25	④	Add page 3~8	22.11.2019	Carson				ASSMANN WSW-No. A-HD x xx PP/Z-UNC3																																				
			X.XX	±0.13	③	Add solder temperature	15.04.2019	Xavier																																								
			DIM	TOL	②	Correct the dimensioning of "H"	27.10.2016	Amy																																								
			X.°	±3°	Id.	Modification	Date	Name																																								
			X.X°	±1.0°																																												
H			Angle	TOL								Customer-No.	Sheet 8/8	H																																		
	1	2	3	4	5	6	7																																									