


- Material:**
- Insulator: Glass Filled Thermoplastic PBT, UL94V-0
 - Contact plating: Copper alloy over Nickel
 - Shell: SPCC
 - Clinch Nut: Brass, Nickel plated
 - Boardlock: Brass, Tin plated
- Electrical:**
- Contact Resistance: 20mΩ Max @1A DC
 - Insulation Resistance: 1,000MΩ @500V DC
 - Dielectric Withstanding Voltage: 1,000V AC/rms 60Hz for 1 minute
- ①
- Current rating: **3 Amp**
 - Voltage rating: 250V AC/rms 60Hz

①

Positions	A	B	D	E
9	30.81	24.99	16.33	11.08
15	39.20	33.30	24.70	19.39
25	53.05	47.04	38.40	33.24
37	69.40	63.50	54.80	49.86



RoHS compliant
Unit: mm

Scale	Free						Customer-No.
TOLERANCE							
X.	±0.38				Drawn	23.05.2013	Wilson
X.X	±0.25				Approved	05.06.2013	Winnie
X.XX	±0.13						
DIM	TOL	①	Update				
X. °	±3°					05.06.2013	Winnie
X.X°	±1°	①	Drawn			23.05.2013	Wilson
Angle	TOL	Id.	Modification	Date	Name		

ASSMANN
WSW components

ASSMANN WSW-No.
ADFXXA-KG-TxxB5

Drawing-No.
ASS 5750 CO

Replace

rev01

Sheet