

	1	2	3	4	5	6	7																																																																										
A	LENGTH								A																																																																								
B									B																																																																								
C	Order Code: ① A-MCSP-80XXX : color Grey ④② Order lengths in meter: 0.3,0.5,1,2,3,5,7,10,15,20,30 ④② Order lengths in meter: 0.3,0.5,1,2,3,5,7,10,15,20,30 Order color:(R)Red,(Y)Yellow (G)Green,(B)Blue ⑥② TOLERANCE <table><thead><tr><th>Length(meter)</th><th>Max-M</th><th>Min-M</th></tr></thead><tbody><tr><td>0.3</td><td>+0.03</td><td>-0.025</td></tr><tr><td>0.5</td><td>+0.03</td><td>-0.025</td></tr><tr><td>1</td><td>+0.04</td><td>-0.035</td></tr><tr><td>2</td><td>+0.06</td><td>-0.06</td></tr><tr><td>3</td><td>+0.09</td><td>-0.09</td></tr><tr><td>5</td><td>+0.15</td><td>-0.15</td></tr><tr><td>7</td><td>+0.21</td><td>-0.21</td></tr><tr><td>10</td><td>+0.3</td><td>-0.3</td></tr><tr><td>15</td><td>+0.45</td><td>-0.45</td></tr><tr><td>20</td><td>+0.6</td><td>-0.6</td></tr><tr><td>30</td><td>+0.9</td><td>-0.9</td></tr></tbody></table> ③⑦ ③⑦								Length(meter)	Max-M	Min-M	0.3	+0.03	-0.025	0.5	+0.03	-0.025	1	+0.04	-0.035	2	+0.06	-0.06	3	+0.09	-0.09	5	+0.15	-0.15	7	+0.21	-0.21	10	+0.3	-0.3	15	+0.45	-0.45	20	+0.6	-0.6	30	+0.9	-0.9	C																																				
Length(meter)	Max-M	Min-M																																																																															
0.3	+0.03	-0.025																																																																															
0.5	+0.03	-0.025																																																																															
1	+0.04	-0.035																																																																															
2	+0.06	-0.06																																																																															
3	+0.09	-0.09																																																																															
5	+0.15	-0.15																																																																															
7	+0.21	-0.21																																																																															
10	+0.3	-0.3																																																																															
15	+0.45	-0.45																																																																															
20	+0.6	-0.6																																																																															
30	+0.9	-0.9																																																																															
D	PIN ASSIGNMENT <table><thead><tr><th>P1</th><th>P2</th></tr></thead><tbody><tr><td>1</td><td>1 WHITE/ORANGE</td></tr><tr><td>2</td><td>2 ORANGE</td></tr><tr><td>3</td><td>3 WHITE/GREEN</td></tr><tr><td>4</td><td>4 BLUE</td></tr><tr><td>5</td><td>5 WHITE/BLUE</td></tr><tr><td>6</td><td>6 GREEN</td></tr><tr><td>7</td><td>7 WHITE/BROWN</td></tr><tr><td>8</td><td>8 BROWN</td></tr><tr><td>S</td><td>S Drain wire</td></tr></tbody></table> ③⑦ ③⑦								P1	P2	1	1 WHITE/ORANGE	2	2 ORANGE	3	3 WHITE/GREEN	4	4 BLUE	5	5 WHITE/BLUE	6	6 GREEN	7	7 WHITE/BROWN	8	8 BROWN	S	S Drain wire	D																																																				
P1	P2																																																																																
1	1 WHITE/ORANGE																																																																																
2	2 ORANGE																																																																																
3	3 WHITE/GREEN																																																																																
4	4 BLUE																																																																																
5	5 WHITE/BLUE																																																																																
6	6 GREEN																																																																																
7	7 WHITE/BROWN																																																																																
8	8 BROWN																																																																																
S	S Drain wire																																																																																
E	Electrical 100% short,open,miswire test								E																																																																								
F	⑦⑤ <table><thead><tr><th>NO</th><th>PART NO</th><th>DESCRIPTION</th><th>QTY</th><th>UNIT</th></tr></thead><tbody><tr><td>⑦⑤</td><td>④</td><td>AL-Foil</td><td>Double-sided conductive aluminum foil</td><td>2</td><td>PCS</td></tr><tr><td>⑦⑤</td><td>③</td><td>mold</td><td>PVC,65P</td><td>AR</td><td>G</td></tr><tr><td>⑦⑤</td><td>②</td><td>plug</td><td>8P8C plating gold 3U" with metal shield</td><td>2</td><td>PCS</td></tr><tr><td>⑦⑤</td><td>①</td><td>cable</td><td>CAT5E F/UTP (26AWG*1P)*4+D+A+PVC, OD:5.2±0.2mm</td><td>AR</td><td>M</td></tr></tbody></table>								NO	PART NO	DESCRIPTION	QTY	UNIT	⑦⑤	④	AL-Foil	Double-sided conductive aluminum foil	2	PCS	⑦⑤	③	mold	PVC,65P	AR	G	⑦⑤	②	plug	8P8C plating gold 3U" with metal shield	2	PCS	⑦⑤	①	cable	CAT5E F/UTP (26AWG*1P)*4+D+A+PVC, OD:5.2±0.2mm	AR	M	F																																											
NO	PART NO	DESCRIPTION	QTY	UNIT																																																																													
⑦⑤	④	AL-Foil	Double-sided conductive aluminum foil	2	PCS																																																																												
⑦⑤	③	mold	PVC,65P	AR	G																																																																												
⑦⑤	②	plug	8P8C plating gold 3U" with metal shield	2	PCS																																																																												
⑦⑤	①	cable	CAT5E F/UTP (26AWG*1P)*4+D+A+PVC, OD:5.2±0.2mm	AR	M																																																																												
G	RoHS compliant Unit:: mm <table><thead><tr><th>Scale</th><th>FREE</th><th>⑦</th><th>Change the plant</th><th>12.04.2022</th><th>Luca</th><th>Date</th><th>Name</th><th>Customer-No.</th></tr></thead><tbody><tr><td>TOLERANCE</td><td></td><td>⑥</td><td>Clarify the tolerance</td><td>23.08.2018</td><td>Segal</td><td>Drawn</td><td>Joanna</td><td></td></tr><tr><td>X.</td><td>±X</td><td>⑤</td><td>Add "CAT5E"</td><td>20.10.2017</td><td>Stephon</td><td>Approved</td><td>Luca</td><td>ASSMANN WSW-No.</td></tr><tr><td>X.X</td><td>±X</td><td>④</td><td>Add length for 20M and 30M</td><td>20.09.2017</td><td>Fred</td><td></td><td></td><td>A-MCSP-80XXX/X</td></tr><tr><td>X.XX</td><td>±X</td><td>③</td><td>remove mark on the mould</td><td>29.06.2016</td><td>Joanna</td><td></td><td></td><td>Drawing-No.</td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Add length for 300mm</td><td>18.05.2015</td><td>Joanna</td><td></td><td></td><td>ASS 7425 CA</td></tr><tr><td>ANGLE</td><td>±X°</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td>rev07</td></tr><tr><td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Sheet</td></tr></tbody></table>								Scale	FREE	⑦	Change the plant	12.04.2022	Luca	Date	Name	Customer-No.	TOLERANCE		⑥	Clarify the tolerance	23.08.2018	Segal	Drawn	Joanna		X.	±X	⑤	Add "CAT5E"	20.10.2017	Stephon	Approved	Luca	ASSMANN WSW-No.	X.X	±X	④	Add length for 20M and 30M	20.09.2017	Fred			A-MCSP-80XXX/X	X.XX	±X	③	remove mark on the mould	29.06.2016	Joanna			Drawing-No.	DIM	TOL	②	Add length for 300mm	18.05.2015	Joanna			ASS 7425 CA	ANGLE	±X°	Id.	Modification	Date	Name			rev07	Angle	TOL							Sheet	G
Scale	FREE	⑦	Change the plant	12.04.2022	Luca	Date	Name	Customer-No.																																																																									
TOLERANCE		⑥	Clarify the tolerance	23.08.2018	Segal	Drawn	Joanna																																																																										
X.	±X	⑤	Add "CAT5E"	20.10.2017	Stephon	Approved	Luca	ASSMANN WSW-No.																																																																									
X.X	±X	④	Add length for 20M and 30M	20.09.2017	Fred			A-MCSP-80XXX/X																																																																									
X.XX	±X	③	remove mark on the mould	29.06.2016	Joanna			Drawing-No.																																																																									
DIM	TOL	②	Add length for 300mm	18.05.2015	Joanna			ASS 7425 CA																																																																									
ANGLE	±X°	Id.	Modification	Date	Name			rev07																																																																									
Angle	TOL							Sheet																																																																									
H	ASSMANN WSW components								H																																																																								
	1	2	3	4	5	6	7	CAB0507																																																																									