
Ultra-Low Phase Jitter LVCMOS SMD Clock Oscillator



7.0 x 5.0 x 1.4mm

ASVMX-25.000MHz-5ABC

ESD Sensitive | **RoHS/RoHS II compliant**

Moisture Sensitivity Level – MSL 3

FEATURES:

- 25MHz LVCMOS
- Typical phase noise: 100fs (Integration range: 1.875MHz-20MHz)
- ±50ppm total frequency stability over -40°C to +85°C temperature range
- Industry standard 6-Pin 7 x 5mm LGA package

APPLICATIONS:

- Communications
- Backplane reference clock
- SERDES reference clock
- FPGA

KEY ELECTRICAL SPECIFICATIONS

Item	Minimum	Maximum	Unit	Condition
Supply Voltage	-0.3	+3.6	V	
Storage Temp.	-55	+125	°C	
Lead Temp.(soldering, 10s)		+260	°C	
ESD (HBM)		2	kV	

VDD = 2.375 - 3.63V, TA = -40°C to +85°C, outputs terminated with 50 Ohms to VDD /2.(1)

Parameters		Minimum	Typical	Maximum	Units	Notes
Frequency			25.000		MHz	
Operating Temperature (T_A)		-40		+85	°C	
Overall Frequency Stability (2)		-50		+50	ppm	
Supply Voltage (V_{DD})		+2.375		+3.63	V	
Supply Current (I_{DD})				95	mA	
Output Logic Level	V_{OH}	V_{DD} – 0.8			V	
	V_{OL}			0.6	V	
Input Logic Level	V_{IH}	2		V_{DD} + 0.3	V	
	V_{IL}	-0.3		0.8	V	
Start-up Time				20	ms	
Rise Time (Tr)		100		500	ps	No load 20% to 80%
Fall Time (Tf)		100		500		
Duty Cycle		45		55	%	
Phase Noise	Integration Range: 12kHz to 20MHz		220		fsRMS	
	Integration Range: 1.875MHz to 20MHz		100			

Notes:

1. Guaranteed after thermal equilibrium
2. Inclusive of initial accuracy, temperature drift, aging, shock, vibration from -40°C to +85°C.


PART IDENTIFICATION

ASVMX-25.000MHz -5ABC - ☐

Packing
Blank: Bulk or Tube
T: Tape & Reel (1k/reel)

2 Faraday, Suite# B | Irvine | CA 92618 **Revised: 04.29.15**
Ph. 949.546.8000 | Fax. 949.546.8001
Visit www.abracon.com for Terms and Conditions of Sale

Ultra-Low Phase Jitter LVCMOS SMD Clock Oscillator




7.0 x 5.0 x 1.4mm

ASVMX-25.000MHz-5ABC

RoHS/RoHS II compliant


OUTLINE DIMENSION



Ref.	Min.	Nom.	Max.
A	1.260	1.330	1.400
A1	0.190	0.230	0.270
A2	1.070	1.100	1.130
D	4.900	5.000	5.100
D1		3.700 BSC	
E	6.900	7.000	7.100
E1		5.080 BSC	
b	1.050	1.100	1.150
c	1.350	1.400	1.450
e		2.540 BSC	
f	0.050	0.100	0.150
k	0.210	0.260	0.310
m	1.090	1.140	1.190
n		36	

Dimensional Tolerance	
aaa	0.100
bbb	0.070


Recommended Land Pattern



Dimensions: mm

2 Faraday, Suite# B | Irvine | CA 92618 **Revised: 04.29.15**
Ph. 949.546.8000 | Fax. 949.546.8001
Visit www.abracon.com for Terms and Conditions of Sale

Ultra-Low Phase Jitter LVCMOS SMD Clock Oscillator




7.0 x 5.0 x 1.4mm

ASVMX-25.000MHz-5ABC


RoHS/RoHS II compliant

PIN CONFIGURATION



Pin #	Pin Name	Pin Type	Pin Level	Pin Function
1	OE	I, SE	LVCMOS	Output Enable, disables output to tri-state. 0 = Disabled, 1= Enabled, 50k Ω Pull-up
2	DNC			Make no connection, leave floating
3	GND	PWR		Power Supply Ground
4	Q	O, SE	LVCMOS	Clock Output
5	DNC			Make no connection, leave floating
6	VDD	PWR		Power Supply

REFLOW PROFILE




Parameters	Specifications
Average Ramp-up Rate	3℃ /second max.
Pre-Heat Temp 150 – 200℃	60 – 180 second
Temp > 217℃	60 – 150 second
Time @ Peak Temperature	20 – 40 second
Peak Temperature	260℃ + 0℃ / -5℃
Ramp-down Rate	-6℃ / second max.
Time 25℃ to Peak Temp.	8 minutes max.

Ultra-Low Phase Jitter LVCMOS SMD Clock Oscillator

ASVMX-25.000MHz-5ABC

RoHS/RoHS II compliant




7.0 x 5.0 x 1.4mm

TAPE & REEL


T= Tape & Reel, 1000pcs/reel. Reel Size = 7-inch Reel

MSL-3 packaging applies to –T option.



Blank = Bulk or Tube (43pcs/tube)

MSL-3 packaging applies to MOQ=43 units (tube)



Dimensions: mm

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.