BDX53B, BDX53C (NPN), BDX54B, BDX54C (PNP)

Plastic Medium-Power Complementary Silicon Transistors

These devices are designed for general−purpose amplifier and low−speed switching applications.

Features

- High DC Current Gain −
  h_{FE} = 2500 (Typ) @ I_C = 4.0 Adc
- Collector Emitter Sustaining Voltage − @ 100 mAdc
  $V_{CEO(sus)}$ = 80 Vdc (Min) − BDX53B, 54B
  = 100 Vdc (Min) − BDX53C, 54C
- Low Collector−Emitter Saturation Voltage −
  $V_{CE(sat)}$ = 2.0 Vdc (Max) @ I_C = 3.0 Adc
  = 4.0 Vdc (Max) @ I_C = 5.0 Adc
- Monolithic Construction with Built−In Base−Emitter Shunt Resistors
- These Devices are Pb−Free and are RoHS Compliant*

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage BDX53B, BDX54B BDX53C, BDX54C	V_{CEO}	 80 100	Vdc
Collector−Base Voltage BDX53B, BDX54B BDX53C, BDX54C	V_{CB}	 80 100	Vdc
Emitter−Base Voltage	V_{EB}	5.0	Vdc
Collector Current − Continuous − Peak	I_C	8.0 12	Adc
Base Current	I_B	0.2	Adc
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	65 0.48	W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	70	°C/W
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	1.92	°C/W

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor®


www.onsemi.com

DARLINGTON
8 AMPERE
COMPLEMENTARY SILICON
POWER TRANSISTORS
80−100 VOLTS, 65 WATTS



TO−220
CASE 221A
STYLE 1

MARKING DIAGRAM & PIN ASSIGNMENT



BDX5xy = Device Code
x = 3 or 4
y = B or C
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

© Semiconductor Components Industries, LLC, 2014




Figure 1. Power Derating

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Sustaining Voltage (Note 1) (I_C = 100 mAdc, I_B = 0)	BDX53B, BDX54B BDX53C, BDX54C	$V_{CEO(sus)}$	 80 100	 − −	Vdc
Collector Cutoff Current (V_{CE} = 40 Vdc, I_B = 0) (V_{CE} = 50 Vdc, I_B = 0)	 BDX53B, BDX54B BDX53C, BDX54C	I_{CEO}	 − −	 0.5 0.5	mAdc
Collector Cutoff Current (V_{CB} = 80 Vdc, I_E = 0) (V_{CB} = 100 Vdc, I_E = 0)	 BDX53B, BDX54B BDX53C, BDX54C	I_{CBO}	 − −	 0.2 0.2	mAdc
ON CHARACTERISTICS (Note 1)					
DC Current Gain (I_C = 3.0 Adc, V_{CE} = 3.0 Vdc)		h_{FE}	750	−	−
Collector−Emitter Saturation Voltage (I_C = 3.0 Adc, I_B = 12 mAdc)		$V_{CE(sat)}$	− −	2.0 4.0	Vdc
Base−Emitter Saturation Voltage (I_C = 3.0 Adc, I_C = 12 mA)		$V_{BE(sat)}$	−	2.5	Vdc
DYNAMIC CHARACTERISTICS					
Small−Signal Current Gain (I_C = 3.0 Adc, V_{CE} = 4.0 Vdc, f = 1.0 MHz)		h_{fe}	4.0	−	−
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz)	 BDX53B, 53C BDX54B, 54C	C_{ob}	 − −	 300 200	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.




Figure 2. Switching Time Test Circuit




Figure 3. Switching Times




Figure 4. Thermal Response




Figure 5. Active−Region Safe Operating Area

There are two limitations on the power handling ability of a transistor average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation, i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} < 150°C$. $T_{J(pk)}$ may be calculated from the data in Figure 4. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 6. Small-Signal Current Gain




Figure 7. Capacitance

NPN
BDX53B, 53C

PNP
BDX54B, 54C




Figure 8. DC Current Gain




Figure 9. Collector Saturation Region




Figure 10. “On” Voltages




Figure 11. Temperature Coefficients




Figure 12. Collector Cut−Off Region



Figure 13. Darlington Schematic


ORDERING INFORMATION

Device	Package	Shipping†
BDX53BG	TO−220 (Pb−Free)	50 Units / Rail
BDX53CG	TO−220 (Pb−Free)	50 Units / Rail
BDX54BG	TO−220 (Pb−Free)	50 Units / Rail
BDX54CG	TO−220 (Pb−Free)	50 Units / Rail

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

PACKAGE DIMENSIONS

TO−220
CASE 221A−09
ISSUE AH



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.415	9.66	10.53
C	0.160	0.190	4.07	4.83
D	0.025	0.038	0.64	0.96
F	0.142	0.161	3.61	4.09
G	0.095	0.105	2.42	2.66
H	0.110	0.161	2.80	4.10
J	0.014	0.024	0.36	0.61
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

ON Semiconductor and the ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

BDX53B/D