BG18B

5-4000 MHz Cascadable InGaP HBT Gain Block

Device Features

- OIP3 = 31.5 dBm @ 1900 MHz
- Gain = 18.5 dB @ 1900 MHz
- Output P1 dB = 18.9 dBm @ 1900 MHz
- Patented temperature compensation
- Patented Over Voltage Protection Circuit
- RoHS2-compliant SOT-89 SMT package




Product Description

BeRex's BG18B is a high performance InGaP/ GaAs HBT MMIC amplifier is internally matched to 50 Ohms and uses a patented ***temperature compensation*** circuit to provide stable current over the operating temperature range without the need for external components and a patented ***over voltage protection*** circuit to protect a internal device. The BG18B is designed for high linearity gain block applications that require excellent gain flatness. It is packaged in a RoHS2-compliant with SOT-89 surface mount package.

Applications

- Base station Infrastructure/RFID
- Commercial/Industrial/Military wireless system

Applications Circuit



*C1, C2, C3 =100 pF ± 5%; C4 = 1000 pF ± 5%; C5 = 10uF; L1 = 33nH ±5%

*C1,C2 = 10nF; L1 = 10uH for IF Bandwidth

*Optimum value of L1 may vary with board design.

*L1:10nH, C1&C2:22pF for 3.5GHz Application.

Electrical Specifications

Device performance _ measured on a BeRex evaluation board at 25°C, Vc=5V, 50 Ω system.

Parameter	Conditions	Min	Typ	Max	Unit
Operational Frequency Range		5		4000	MHz
Test Frequency			1900		MHz
Gain		17.0	18.5		dB
Input Return Loss			-16.5		dB
Output Return Loss			-20.5		dB
Output IP3	7 dBm / tone , Δf=1 MHz	28.5	31.5		dBm
Output P1dB		17.9	18.9		dBm
Noise Figure			3.4		dB

Recommended Operating Conditions

Parameter	Min	Typ	Max	Unit
Bandwidth	5		4000	MHz
I_c @ (V_c = 5V)	58	72	86	mA
V_c	3.5	5.0	5.25	V
dG/dT		-0.004		dB/°C
R_{TH}		50		°C/W
Operating Case Temperature	-40		+85	°C

Electrical specifications are measured at specified test conditions.

Specifications are not guaranteed over all recommended operating conditions.

Absolute Maximum Ratings

Parameter	Rating	Unit
Storage Temperature	-55 to +155	°C
Junction Temperature	+170	°C
Supply Voltage	+6.0	V
Supply Current	160	mA
Input RF Power	23	dBm

Operation of this device above any of these parameters may result in permanent damage.

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

Typical Performance (Vc = 5V, Ic = 72mA, T = 25°C)

Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	22.0	21.6	21.2	20.7	20.3	18.5	18.3	17.5	15.1
S11	dB	-13.6	-14.7	-17.2	-11.6	-15.6	-16.5	-16.7	-17.0	-13.5
S22	dB	-8.1	-10.9	-13.8	-18.8	-33.1	-20.5	-20.2	-18.3	-8.2
P1	dBm	18.9	19.1	19.2	18.8	19.0	18.9	18.6	17.8	15.8
OIP3	dBm	35.0	35.5	34.0	35.0	34.0	31.5	31.0	30.5	27.0
NF	dB	3.4	3.4	3.4	3.6	3.4	3.2	3.4	3.4	4.6

Typical Performance (Vc = 4.7V, Ic = 60mA, T = 25°C)

Freq	MHz	70	500	900	1900	2140	2450
S21	dB	22.0	20.7	20.1	18.5	18.0	17.1
S11	dB	-7.0	-17.0	-21.0	-32.0	-32.0	-21.0
S22	dB	-13.0	-20.0	-21.0	-17.0	-16.0	-14.0
P1	dBm	17.8	17.9	17.5	17.1	17.7	16.2
OIP3	dBm	33.5	34.0	32.0	31.0	31.0	29.5
NF	dB	3.4	3.6	3.4	3.2	3.4	3.4

Typical Performance (Vc = 4.5V, Ic = 53mA, T = 25°C)

Freq	MHz	70	500	900	1900	2140	2450
S21	dB	21.7	20.5	20.1	18.4	18.1	17.4
S11	dB	-12.0	-19.0	-20.0	-16.0	-15.0	-14.0
S22	dB	-7.6	-17.0	-20.0	-29.0	-35.0	-22.0
P1	dBm	14.1	16.8	16.5	16.2	16.8	15.7
OIP3	dBm	31.5	32.0	30.5	29.5	30.5	29.0
NF	dB	3.3	3.7	3.3	3.2	3.3	3.4

Typical Performance (Vc = 4.0V, Ic = 38mA, T = 25°C)


Freq	MHz	70	500	900	1900	2140	2450
S21	dB	21.3	20.1	19.5	18.0	17.6	16.7
S11	dB	-11.0	-16.0	-17.0	-15.0	-14.0	-13.0
S22	dB	-7.0	-15.0	-17.0	-24.0	-39.0	-24.0
P1	dBm	13.5	13.1	12.7	12.8	14.0	14.1
OIP3	dBm	26.0	26.0	24.5	24.5	26.0	25.5
NF	dB	3.0	3.7	3.3	3.2	3.3	3.4

Typical Performance (Vc = 3.5V, Ic = 24mA, T = 25°C)


Freq	MHz	70	500	900	1900	2140	2450
S21	dB	19.2	18.4	17.9	16.7	16.6	16.0
S11	dB	-8.5	-11.3	-11.0	-11.0	-10.0	-11.0
S22	dB	-5.3	-10.8	-12.0	-16.0	-20.0	-27.0
P1	dBm	8.3	6.7	6.0	6.4	9.1	12.3
OIP3	dBm	19.0	18.0	16.5	15.5	17.0	17.0
NF	dB	3.0	3.5	3.2	3.2	3.3	3.5

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

V-I Characteristics



BeRex SOT89 Evaluation Board




*Dielectric constant _ 4.2 *RF pattern width 52mil *31mil thick FR4 PCB

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

Typical Device Data

S-parameters (Vc=5V, Ic=72mA, T=25°C)




S-Parameter

(Vdevice = 5.0V, Icc = 72mA, T = 25 °C, calibrated to device leads)


Freq [MHz]	S11 [Mag]	S11 [Ang]	S21 [Mag]	S21 [Ang]	S12 [Mag]	S12 [Ang]	S22 [Mag]	S22 [Ang]
100	0.428	-164.2	15.400	163.1	0.052	19.3	0.379	-39.5
500	0.530	159.5	10.896	144.5	0.075	3.7	0.130	-78.5
1000	0.500	135.9	10.390	123.2	0.069	-3.6	0.041	-144.7
1500	0.470	111.7	9.798	97.1	0.078	-5.7	0.094	105.3
2000	0.368	96.3	8.552	73.2	0.077	-18.8	0.169	64.4
2500	0.316	75.6	8.780	49.6	0.080	-19.4	0.246	39.7
3000	0.228	73.4	7.821	16.6	0.083	-32.9	0.316	17.6
3500	0.219	67.9	5.976	-7.7	0.079	-36.5	0.379	-11.3
4000	0.229	61.0	4.805	-27.6	0.084	-45.7	0.448	-37.4

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

WCDMA 4FA 2140 -60dBc




WCDMA 6FA 2140 -60dBc



Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex


ACLR




Typical Performance

Vc=5V, Ic=72mA, T=25°C)

Pin-Pout-Gain




900MHz





1900 MHz


Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex


OIP3


















Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

ACPR











Gain Flatness



Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

Package Outline Dimension



NOTE:
1. DIMENSIONS IN MILLIMETERS.

2. DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.5mm PER END. DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.5mm PER SIDE.

3. DIMENSIONS D AND E1 ARE DETERMINED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.

4. DATUMS A, B AND D TO BE DETERMINED 0.18mm FROM THE LEAD TIP.


5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.

SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.40	1.50	1.60	
A1	0.00	--	0.10	
b	0.38	0.42	0.48	
b1	0.48	0.52	0.58	
b2	1.79	1.82	1.87	
c	0.40	0.42	0.46	
D	4.40	4.50	4.70	2,3
E	3.70	4.00	4.30	
E1	2.40	2.50	2.70	2,3
E2	0.80	1.00	1.20	
E3	0.40	0.50	0.60	
e	1.50 TYP.			
θ	4° TYP.			
R	0.15 TYP.			
R1	--	--	0.20	

SYMBOL	TOLERANCE OF FORM AND POSITION	NOTE
aaa	0.15	
bbb	0.20	
ccc	0.10	
ddd	0.10	

Suggested PCB Land Pattern and PAD Layout


PCB Land Pattern



Note : All dimension _ millimeters


PCB lay out _ on BeRex website

PCB Mounting



Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex


Package Marking



YY = Year, WW = Working Week,
XX = Wafer No.

Tape & Reel

SOT89



Packaging information:

Tape Width (mm): 12

Reel Size (inches): 7

Device Cavity Pitch (mm): 8

Devices Per Reel: 1000

Lead plating finish

100% Tin Matte finish

(All BeRex products undergoes a 1 hour, 150 degree C, Anneal bake to eliminate thin whisker growth concerns.)

MSL / ESD Rating

ESD Rating:	Class 1C
Value:	**Passes <2000V**
Test:	Human Body Model (HBM)
Standard:	JEDEC Standard JESD22-A114
MSL Rating:	**Level 1 at +260°C convection reflow**
Standard:	JEDEC Standard J-STD-020



Proper ESD procedures should be followed when handling this device.

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex

RoHS Compliance

This part is compliant with Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) Directive 2011/65/EU as amended by Directive 2015/863/EU.
This product also is compliant with a concentration of the Substances of Very High Concern (SVHC) candidate list which are contained in a quantity of less than 0.1%(w/w) in each components of a product and/or its packaging placed on the European Community market by the BeRex and Suppliers.

NATO CAGE code:

2	N	9	6	F

Specifications and information are subject to change without notice. BeRex is a trademark of BeRex.
All other trademarks are the property of their respective owners. © 2021 BeRex