BLF7G27L-90P; BLF7G27LS-90P

Power LDMOS transistor

Rev. 3 — 1 September 2015

AMPLEON

Product data sheet

1. Product profile

1.1 General description

90 W LDMOS power transistor for base station applications at frequencies from 2500 MHz to 2700 MHz.

Table 1. Typical performance

Typical RF performance at T_{case} = 25 °C in a common source class-AB production test circuit.

Mode of operation	f	I_{Dq}	V_{DS}	$P_{L(AV)}$	G_p	η_D	$ACPR_{885k}$	$ACPR_{5M}$
	(MHz)	(mA)	(V)	(W)	(dB)	(%)	(dBc)	(dBc)
IS-95	2500 to 2700	720	28	16	18.5	29	–46[1]	-
Single carrier W-CDMA	2500 to 2700	720	28	25	18.5	35	-	–36[2]

[1] Single carrier IS-95 with pilot, paging, sync and 6 traffic channels (Walsh codes 8 - 13). PAR = 9.7 dB at 0.01 % probability on the CCDF. Channel bandwidth is 1.2288 MHz.

[2] 3GPP; test model 1; 64 DPCH; PAR = 7.2 dB at 0.01 % probability on CCDF. Channel bandwidth is 3.84 MHz.

1.2 Features and benefits





- Excellent ruggedness
- High efficiency
- Low R_{th} providing excellent thermal stability
- Designed for broadband operation (2500 MHz to 2700 MHz)
- Lower output capacitance for improved performance in Doherty applications
- Designed for low memory effects providing excellent pre-distortability
- Internally matched for ease of use
- Integrated ESD protection
- Compliant to Directive 2002/95/EC, regarding Restriction of Hazardous Substances (RoHS)

1.3 Applications

- RF power amplifiers for W-CDMA base stations and multi carrier applications in the 2500 MHz to 2700 MHz frequency range

2. Pinning information

Table 2. Pinning

Pin	Description		Simplified outline	Graphic symbol
BLF7G27L-90P (SOT1121A)				
1	drain1			
2	drain2			
3	gate1			
4	gate2			
5	source	[1]		
BLF7G27LS-90P (SOT1121B)				
1	drain1			
2	drain2			
3	gate1			
4	gate2			
5	source	[1]		

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BLF7G27L-90P	-	flanged LDMOST ceramic package; 2 mounting holes; 4 leads	SOT1121A
BLF7G27LS-90P	-	earless flanged LDMOST ceramic package; 4 leads	SOT1121B

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	65	V
V_{GS}	gate-source voltage		−0.5	+13	V
I_D	drain current		-	18	A
T_{stg}	storage temperature		−65	+150	°C
T_j	junction temperature		-	225	°C

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-c)}$	thermal resistance from junction to case	T_{case} = 80 °C; P_L = 16 W	0.4	K/W

6. Characteristics

Table 6. Characteristics

T_j = 25 °C; per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	V_{GS} = 0 V; I_D = 0.6 mA	65	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	V_{DS} = 10 V; I_D = 60 mA	1.5	1.8	2.3	V
I_{DSS}	drain leakage current	V_{GS} = 0 V; V_{DS} = 28 V	-	-	1.4	μA
I_{DSX}	drain cut-off current	V_{GS} = $V_{GS(th)}$ + 3.75 V; V_{DS} = 10 V	9.6	11.5	-	A
I_{GSS}	gate leakage current	V_{GS} = 11 V; V_{DS} = 0 V	-	-	150	nA
g_{fs}	forward transconductance	V_{DS} = 10 V; I_D = 60 mA	-	0.53	-	S
$R_{DS(on)}$	drain-source on-state resistance	V_{GS} = $V_{GS(th)}$ + 3.75 V; I_D = 2100 mA	-	0.24	-	Ω

7. Test information

Table 7. Functional test information

Mode of operation: 1-carrier N-CDMA, single carrier IS-95 with pilot, paging, sync and 6 traffic channels (Walsh codes 8 - 13). PAR = 9.7 dB at 0.01 % probability on the CCDF, channel bandwidth is 1.2288 MHz; f_1 = 2500 MHz; f_2 = 2700 MHz; RF performance at V_{DS} = 28 V; I_{Dq} = 720 mA; T_{case} = 25 °C; 2 sections combined unless otherwise specified; in a class-AB production test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$P_{L(AV)}$	average output power		-	16	-	W
G_p	power gain	$P_{L(AV)}$ = 16 W	17	18.5	-	dB
RL_{in}	input return loss	$P_{L(AV)}$ = 16 W	-	−15	-	dB
η_D	drain efficiency	$P_{L(AV)}$ = 16 W	25	29	-	%
$ACPR_{885k}$	adjacent channel power ratio (885 kHz)	$P_{L(AV)}$ = 16 W	-	−46	−41	dBc


7.1 Ruggedness in class-AB operation

The BLF7G27L-90P and BLF7G27LS-90P are capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions: V_{DS} = 28 V; I_{Dq} = 720 mA; P_L = 90 W (CW); f = 2500 MHz.

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

7.2 Single carrier IS-95

Single carrier IS-95 with pilot, paging, sync and 6 traffic channels (Walsh codes 8 - 13). PAR = 9.7 dB at 0.01 % probability on the CCDF. Channel bandwidth is 1.2288 MHz.




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 1. Single carrier IS-95 power gain as a function of output power; typical values



V_{DS} = 28 V; I_{Dq} = 720 mA.


(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 2. Single carrier IS-95 drain efficiency as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 3. Single carrier IS-95 ACPR at 885 kHz as a function of output power; typical values




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 4. Single carrier IS-95 ACPR at 1980 kHz as a function of output power; typical values




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 5. Single carrier IS-95 peak-to-average power ratio as a function of output power; typical values



V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz


(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 6. Single carrier IS-95 peak output power as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

7.3 Pulsed CW




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 7. Pulsed CW power gain as a function of output power; typical values



V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz


(3) f = 2700 MHz

Fig 8. Pulsed CW drain efficiency as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

7.4 Single carrier W-CDMA

3GPP; test model 1; 64 DPCH; PAR = 7.2 dB at 0.01 % probability on CCDF. Channel bandwidth is 3.84 MHz.




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 9. Single carrier W-CDMA power gain as a function of output power; typical values



V_{DS} = 28 V; I_{Dq} = 720 mA.


(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 10. Single carrier W-CDMA drain efficiency as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 11. Single carrier W-CDMA ACPR at 5 MHz as a function of output power; typical values




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 12. Single carrier W-CDMA ACPR at 10 MHz as a function of output power; typical values




V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz

(3) f = 2700 MHz

Fig 13. Single carrier W-CDMA peak-to-average power ratio as a function of output power; typical values



V_{DS} = 28 V; I_{Dq} = 720 mA.

(1) f = 2500 MHz

(2) f = 2600 MHz


(3) f = 2700 MHz

Fig 14. Single carrier W-CDMA peak output power as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

8. Package outline

Flanged LDMOST ceramic package; 2 mounting holes; 4 leads **SOT1121A**



Dimensions

Unit[1]		A	b	c	D	D_1	e	E	E_1	F	H	H_1	p	Q[2]	q	U_1	U_2	w_1	w_2
mm	max	4.75	3.94	0.18	20.02	19.96		9.53	9.53	1.14	19.94	12.83	3.38	1.70		34.16	9.91		
	nom						8.89								27.94			0.25	0.51
	min	3.45	3.68	0.10	19.61	19.66		9.27	9.27	0.89	18.92	12.57	3.12	1.45		33.91	9.65		
inches	max	0.187	0.155	0.007	0.788	0.786		0.375	0.375	0.045	0.785	0.505	0.133	0.067		1.345	0.39		
	nom						0.35								1.1			0.01	0.02
	min	0.136	0.145	0.004	0.772	0.774		0.365	0.365	0.035	0.745	0.495	0.123	0.057		1.335	0.38		

Note
1. millimeter dimensions are derived from the original inch dimensions.
2. dimension is measured 0.030 inch (0.76 mm) from the body.


sot1121a_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1121A						~~09-10-12~~ 10-02-02

Fig 15. Package outline SOT1121A

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

Earless flanged ceramic package; 4 leads **SOT1121B**



Dimensions

Unit[1]		A	b	c	D	D_1	e	E	E_1	F	H	H_1	Q	U_1	U_2	w_2	w_3	y
mm	max	4.75	3.94	0.18	20.02	19.96		9.53	9.53	1.14	19.94	12.83	1.70	20.70	9.91	0.51	0.25	0.25
	nom						8.89											
	min	3.45	3.68	0.08	19.61	19.66		9.27	9.27	0.89	18.92	12.57	1.45	20.45	9.65			
inches	max	0.187	0.155	0.007	0.788	0.786		0.375	0.375	0.045	0.785	0.505	0.067	0.815	0.39	0.02	0.01	0.01
	nom						0.35											
	min	0.136	0.145	0.003	0.772	0.774		0.365	0.365	0.035	0.745	0.495	0.057	0.805	0.38			

Note
1. millimeter dimensions are derived from the original inch dimensions.
2. dimension is measured 0.030 inch (0.76 mm) from the body.

sot1121b_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1121B						~~09-12-14~~ 12-06-07

Fig 16. Package outline SOT1121B

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

9. Abbreviations

Table 8. Abbreviations

Acronym	Description
3GPP	Third Generation Partnership Project
CCDF	Complementary Cumulative Distribution Function
CW	Continuous Wave
DPCH	Dedicated Physical CHannel
IS-95	Interim Standard 95
ESD	ElectroStatic Discharge
LDMOS	Laterally Diffused Metal Oxide Semiconductor
LDMOST	Laterally Diffused Metal Oxide Semiconductor Transistor
N-CDMA	Narrowband Code Division Multiple Access
PAR	Peak-to-Average power Ratio
RF	Radio Frequency
VSWR	Voltage Standing Wave Ratio
W-CDMA	Wideband Code Division Multiple Access

10. Revision history

Table 9. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLF7G27L-90P_BLF7G27LS-90P#3	20150901	Product data sheet	-	BLF7G27L-90P_BLF7G27LS-90P v.2
Modifications:	• The format of this document has been redesigned to comply with the new identity guidelines of Ampleon. • Legal texts have been adapted to the new company name where appropriate.			
BLF7G27L-90P_BLF7G27LS-90P v.2	20111110	Product data sheet	-	BLF7G27L-90P_BLF7G27LS-90P v.1
BLF7G27L-90P_BLF7G27LS-90P v.1	20101102	Objective data sheet	-	-

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

11. Legal information

11.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.ampleon.com.

11.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

11.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at http://www.ampleon.com/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon' standard warranty and Ampleon' product specifications.

11.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

12. Contact information

For more information, please visit:
http://www.ampleon.com

For sales office addresses, please visit:
http://www.ampleon.com/sales

All information provided in this document is subject to legal disclaimers.
© Ampleon The Netherlands B.V. 2015. All rights reserved.

13. Contents

1	**Product profile**	**1**
1.1	General description	1
1.2	Features and benefits	1
1.3	Applications	1
2	**Pinning information**	**2**
3	**Ordering information**	**2**
4	**Limiting values**	**2**
5	**Thermal characteristics**	**3**
6	**Characteristics**	**3**
7	**Test information**	**3**
7.1	Ruggedness in class-AB operation	3
7.2	Single carrier IS-95	4
7.3	Pulsed CW	6
7.4	Single carrier W-CDMA	7
8	**Package outline**	**9**
9	**Abbreviations**	**11**
10	**Revision history**	**11**
11	**Legal information**	**12**
11.1	Data sheet status	12
11.2	Definitions	12
11.3	Disclaimers	12
11.4	Trademarks	13
12	**Contact information**	**13**
13	**Contents**	**14**

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon The Netherlands B.V. 2015. All rights reserved.

For more information, please visit: http://www.ampleon.com
For sales office addresses, please visit: http://www.ampleon.com/sales

Date of release: 1 September 2015
Document identifier: BLF7G27L-90P_BLF7G27LS-90P#3