Thick Surface Mounts - BRASS "BMA" Series

3/8" or 3/4" hole; 1-1/8"-18 thread; installs from above; can be used for metal thickness up to 1/8"

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*	Type
BMA38**	17'	N/A	None	N/A
BMA-NC**	17'	RG-58/U	None	N/A
BMA	17'	RG-58/U	PL259	Solder
BMANCP	17'	RG-58/U	N	Crimp
BMAPL	17'	RG-58/U	Mini-UHF	Crimp


BMA

For other cable types, lengths or connector configuration options, contact PCTEL Customer Service.

Thick Surface Mounts - BMATM Series

3/8" or 3/4" hole; 1-1/8"-18 thread; thick plate; installs from below; can be used for metal thickness to 3/16"

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*	Type
BMATM-NC	17'	RG-58/U	None	N/A
BMATMML195NC	17'	Pro-Flex™ Plus 195	None	N/A
BMATM	17'	RG-58/U	PL259	Solder
BMATMCP	17'	RG-58/U	PL259	Crimp
BMATMC	17'	RG-58/U	TNC	Crimp
BMATM38	N/A	None	None	N/A


BMATM

For other cable types, lengths or connector configuration options, contact PCTEL Customer Service.

Thick Surface Mounts - K/KE794 Series

3/4" hole for up to 1/2" Thick Roof Thickness

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*
K794	17'	RG-58/U	None
KE794	30'	RG-58/U	None


K794 Series

For other cable types, lengths or connector configuration options, contact PCTEL Customer Service.

* Connectors are shipped loose. Connectors may be attached upon request for an additional charge
** This mount installs from below. For other connector options, please refer to the Mobile Antenna Mounts Configurator Part Number Guide.