

BUK9E08-55B

N-channel TrenchMOS logic level FET

Rev. 03 — 31 May 2010 **Product data sheet**

1. Product profile

1.1 General description

Logic level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology. This product has been designed and qualified to the appropriate AEC standard for use in automotive critical applications.

1.2 Features and benefits

- Low conduction losses due to low on-state resistance
- Q101 compliant
- Suitable for logic level gate drive sources
- Suitable for thermally demanding environments due to 175 °C rating

1.3 Applications

- 12 V and 24 V loads
- Automotive systems
- General purpose power switching
- Motors, lamps and solenoids

1.4 Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
V_{DS}	drain-source voltage	$T_j \geq 25$ °C; $T_j \leq 175$ °C		-	-	55	V
I_D	drain current	$V_{GS} = 5$ V; $T_{mb} = 25$ °C; see Figure 1; see Figure 3	[1]	-	-	75	A
P_{tot}	total power dissipation	$T_{mb} = 25$ °C; see Figure 2		-	-	203	W
Static characteristics							
R_{DSon}	drain-source on-state resistance	$V_{GS} = 10$ V; $I_D = 25$ A; $T_j = 25$ °C		-	6.2	7	mΩ
		$V_{GS} = 5$ V; $I_D = 25$ A; $T_j = 25$ °C; see Figure 11; see Figure 12		-	7.1	8.4	mΩ

Table 1. Quick reference data *...continued*

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Avalanche ruggedness						
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	I_D = 75 A; $V_{sup} \leq$ 55 V; R_{GS} = 50 Ω; V_{GS} = 5 V; $T_{j(init)}$ = 25 °C; unclamped	-	-	352	mJ
Dynamic characteristics						
Q_{GD}	gate-drain charge	V_{GS} = 5 V; I_D = 25 A; V_{DS} = 44 V; T_j = 25 °C; see Figure 13	-	16	-	nC

[1] Continuous current is limited by package.

2. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	G	gate	mb	D
2	D	drain		G
3	S	source		mbb076 S
mb	D	mounting base; connected to drain	1 2 3	

SOT226 (I2PAK)

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BUK9E08-55B	I2PAK	plastic single-ended package (I2PAK); TO-262	SOT226

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
V_{DS}	drain-source voltage	$T_j \geq 25$ °C; $T_j \leq 175$ °C		-	-	55	V
V_{DGR}	drain-gate voltage	R_{GS} = 20 kΩ		-	-	55	V
V_{GS}	gate-source voltage			-15	-	15	V
I_D	drain current	T_{mb} = 100 °C; V_{GS} = 5 V; see Figure 1	[1]	-	-	75	A
		T_{mb} = 25 °C; V_{GS} = 5 V; see Figure 1; see Figure 3	[2]	-	-	110	A
			[1]	-	-	75	A
I_{DM}	peak drain current	T_{mb} = 25 °C; $t_p \leq 10$ µs; pulsed; see Figure 3		-	-	439	A
P_{tot}	total power dissipation	T_{mb} = 25 °C; see Figure 2		-	-	203	W
T_{stg}	storage temperature			-55	-	175	°C
T_j	junction temperature			-55	-	175	°C
Source-drain diode							
I_S	source current	T_{mb} = 25 °C	[2]	-	-	110	A
			[1]	-	-	75	A
I_{SM}	peak source current	$t_p \leq 10$ µs; pulsed; T_{mb} = 25 °C		-	-	439	A
Avalanche ruggedness							
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	I_D = 75 A; $V_{sup} \leq 55$ V; R_{GS} = 50 Ω; V_{GS} = 5 V; $T_{j(init)}$ = 25 °C; unclamped		-	-	352	mJ

[1] Continuous current is limited by package.

[2] Current is limited by power dissipation chip rating.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved



$V_{GS} \geq 5V$

Fig 1. Continuous drain current as a function of mounting base temperature



$$P_{der} = \frac{P_{tot}}{P_{tot(25°C)}} \times 100\,\%$$

Fig 2. Normalized total power dissipation as a function of mounting base temperature



$T_{mb} = 25°C; I_{DM}$ is single pulse

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j\text{-}mb)}$	thermal resistance from junction to mounting base	see Figure 4	-	-	0.74	K/W
$R_{th(j\text{-}a)}$	thermal resistance from junction to ambient	vertical in still air	-	60	-	K/W



Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

6. Characteristics

Table 6. Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = 0.25 mA; V_{GS} = 0 V; T_j = 25 °C	55	-	-	V
		I_D = 0.25 mA; V_{GS} = 0 V; T_j = -55 °C	50	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	I_D = 1 mA; V_{DS} = V_{GS}; T_j = 25 °C; see Figure 10	1.1	1.5	2	V
		I_D = 1 mA; V_{DS} = V_{GS}; T_j = -55 °C; see Figure 10	-	-	2.3	V
		I_D = 1 mA; V_{DS} = V_{GS}; T_j = 175 °C; see Figure 10	0.5	-	-	V
I_{DSS}	drain leakage current	V_{DS} = 55 V; V_{GS} = 0 V; T_j = 175 °C	-	-	500	µA
		V_{DS} = 55 V; V_{GS} = 0 V; T_j = 25 °C	-	0.02	1	µA
I_{GSS}	gate leakage current	V_{DS} = 0 V; V_{GS} = 15 V; T_j = 25 °C	-	2	100	nA
		V_{DS} = 0 V; V_{GS} = -15 V; T_j = 25 °C	-	2	100	nA
R_{DSon}	drain-source on-state resistance	V_{GS} = 4.5 V; I_D = 25 A; T_j = 25 °C	-	-	9.3	mΩ
		V_{GS} = 5 V; I_D = 25 A; T_j = 175 °C; see Figure 11; see Figure 12	-	-	16.8	mΩ
		V_{GS} = 10 V; I_D = 25 A; T_j = 25 °C	-	6.2	7	mΩ
		V_{GS} = 5 V; I_D = 25 A; T_j = 25 °C; see Figure 11; see Figure 12	-	7.1	8.4	mΩ
Dynamic characteristics						
$Q_{G(tot)}$	total gate charge	I_D = 25 A; V_{DS} = 44 V; V_{GS} = 5 V; T_j = 25 °C; see Figure 13	-	45	-	nC
Q_{GS}	gate-source charge		-	9	-	nC
Q_{GD}	gate-drain charge		-	16	-	nC
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = 25 V; f = 1 MHz; T_j = 25 °C; see Figure 14	-	3960	5280	pF
C_{oss}	output capacitance		-	517	620	pF
C_{rss}	reverse transfer capacitance		-	206	282	pF
$t_{d(on)}$	turn-on delay time	V_{DS} = 30 V; R_L = 1.2 Ω; V_{GS} = 5 V; $R_{G(ext)}$ = 10 Ω; T_j = 25 °C	-	29	-	ns
t_r	rise time		-	123	-	ns
$t_{d(off)}$	turn-off delay time		-	131	-	ns
t_f	fall time		-	86	-	ns
L_D	internal drain inductance	from drain lead 6 mm from package to center of die ; T_j = 25 °C	-	4.5	-	nH
		from upper edge of drain mounting base to center of die ; T_j = 25 °C	-	2.5	-	nH
L_S	internal source inductance	from source lead to source bond pad ; T_j = 25 °C	-	7.5	-	nH

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

Table 6. Characteristics *...continued*

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Source-drain diode						
V_{SD}	source-drain voltage	I_S = 25 A; V_{GS} = 0 V; T_j = 25 °C; see Figure 15	-	0.85	1.2	V
t_{rr}	reverse recovery time	I_S = 20 A; dI_S/dt = -100 A/µs; V_{GS} = -10 V; V_{DS} = 30 V; T_j = 25 °C	-	69	-	ns
Q_r	recovered charge		-	72	-	nC



$T_j = 25°C; t_p = 300\mu s$

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values



$T_j = 25°C; I_D = 25A$

Fig 6. Drain-source on-state resistance as a function of gate-source voltage; typical values



$T_j = 25°C; V_{DS} = V_{GS}$

Fig 7. Sub-threshold drain current as a function of gate-source voltage



$T_j = 25°C; V_{DS} = 25V$

Fig 8. Forward transconductance as a function of drain current; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved



$V_{DS} = 25V$

Fig 9. Transfer characteristics: drain current as a function of gate-source voltage; typical values



$I_D = 1mA; V_{DS} = V_{GS}$

Fig 10. Gate-source threshold voltage as a function of junction temperature



$T_j = 25°C$

Fig 11. Drain-source on-state resistance as a function of drain current; typical values



$$a = \frac{R_{DSon}}{R_{DSon(25°C)}}$$

Fig 12. Normalized drain-source on-state resistance factor as a function of junction temperature

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved



$T_j = 25°C; I_D = 25A$

Fig 13. Gate-source voltage as a function of gate charge; typical values



$V_{GS} = 0V; f = 1MHz$

Fig 14. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values



$V_{GS} = 0V$

Fig 15. Source current as a function of source-drain voltage; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

7. Package outline

Plastic single-ended package (I2PAK); low-profile 3-lead TO-262 **SOT226**



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1	b	b_1	c	D max	D_1	E	e	L	L_1	Q
mm	4.5 4.1	1.40 1.27	0.85 0.60	1.3 1.0	0.7 0.4	11	1.6 1.2	10.3 9.7	2.54	15.0 13.5	3.30 2.79	2.6 2.2

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT226		TO-262				~~06-02-14~~ 09-08-25

Fig 16. Package outline SOT226 (I2PAK)

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

8. Revision history

Table 7. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BUK9E08-55B v.3	20100531	Product data sheet	-	BUK95_96_9E08_55B-02
Modifications:	• The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. • Legal texts have been adapted to the new company name where appropriate. • Type number BUK9E08-55B separated from data sheet BUK95_96_9E08_55B-02.			
BUK95_96_9E08_55B-02 (9397 750 12052)	20031013	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

9. Legal information

9.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

9.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

9.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This Nexperia product has been qualified for use in automotive applications. The product is not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on a weakness or default in the customer application/use or the application/use of customer's third party customer(s) (hereinafter both referred to as "Application"). It is customer's sole responsibility to check whether the Nexperia product is suitable and fit for the Application planned. Customer has to do all necessary testing for the Application in order to avoid a default of the Application and the product. Nexperia does not accept any liability in this respect.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding. Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

10. Contact information

For more information, please visit: http://www.nexperia.com

For sales office addresses, please send an email to: salesaddresses@nexperia.com

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

11. Contents

1 Product profile 1
1.1 General description 1
1.2 Features and benefits 1
1.3 Applications 1
1.4 Quick reference data 1
2 Pinning information 2
3 Ordering information 2
4 Limiting values 3
5 Thermal characteristics 5
6 Characteristics 6
7 Package outline 10
8 Revision history 11
9 Legal information 12
9.1 Data sheet status 12
9.2 Definitions 12
9.3 Disclaimers 12
9.4 Trademarks 13
10 Contact information 13

© **Nexperia B.V. 2017. All rights reserved**

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
Date of release: 31 May 2010