

DC - Link Capacitor C44U

GENERAL TECHNICAL DATA

Reference Standards : IEC 61071 , EN 61071

Dielectric : metallized polypropylene film
 Winding : non-inductive type

Case : aluminum case with threaded bolt M12
 Deck : thermosetting resin flame retardant UL94 V0
 high current M6 female terminals

Construction : dry construction, filled by solid resin

IEC climatic category : 40/85/21 according to IEC 68-1
 Operational Temperature : -40 to +85°C
 Storage Temperature : -40 to +95°C

DIMENSIONS (mm)

$\varnothing = 116$	$\varnothing_{\max} = 118$	$H = 270$	$H1 = 276$	$P \text{ term.} = 50$
---------------------	----------------------------	-----------	------------	------------------------

TEST METHODS AND PERFORMANCES

Test voltage terminal to terminal (Utt)	1.5*Un for 10 s at 25°C
Test voltage terminal to case (Utc)	3.2 kV 50Hz for 10 sec.
Life expectancy	100.000 hours @ Un and Ths = 70°C
Failure rate (IEC 61709)	50/10 ⁹ components hour @ Un and Ths = 70°C
Endurance Test (IEC 61071)	500h+500h @ 1.3xUn @ 70°C
Capacitance deviation in temperature range (-25..+85°C)	± 1,5% max on capacitance value at 25°C
Installation	Whatever position

ELECTRICAL CHARACTERISTICS

Code	C44UOGT7200G5SK
Capacitance	2000 μ F
Tolerance	±10 %
Rated Voltage	900 Vdc
Max Irms Current with natural cooling (Ths = 70°C)	100 Arms @40°C ambient temperature and 10kHz 92 Arms @50°C ambient temperature and 10kHz 54 Arms @60°C ambient temperature and 10kHz
Thermal Resistance	1.6 °C/W
dV/dt	5 V/ μ s
Repetitive Peak Current	10000 Apk
ESR	1.5 m Ω (10 kHz)
ESL	≤ 85 nH
Weight	~ 3250 gr
Number of pieces for packing unit	4



