



1. MATERIALS AND FINISHES:
 - SMA STR BHD JACK - BRASS, GOLD PLATING
 - N STR BHD JACK - BRASS, WHITE BRONZE PLATING
 - CABLE - RG 58
2. ELECTRICAL:
 - A. IMPEDANCE: 50 OHM
3. PACKAGING:
 - A. QUANTITY: SINGLE PACK
 - B. MARKING: BAG TO BE MARKED
 - "AMPHENOL RF, 95-902-527-XXX AND DATE CODE

SCALE 0.500



HEAT SHRINK TUBE
TYP(2)



DESIGN REQUIREMENTS:

X FREQUENCY: DC - 3 GHz

X CONTINUITY

□ VSWR: ____ 1 MAX.

X HI-POT: 750 VRMS

INS. LOSS: ---- dB MAX.

☐ OTHER

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp., (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:

<0.5mm = ±0.05mm	[<0.020 = ±0.002]
>0.5 - 6mm = ±0.1mm	[>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm	[>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm	[>1.181 - 4.725 = ±0.012]

ANGLES = $\pm 1^\circ$

MATERIAL

SEE NOTES

ENGINEER
KARTHIK R

DATE
27-FEB-20

T I T L E

SMA STR BHD JACK TO
N STR BHD JACK USING
RG 58 CABLE
VARIOUS LENGTH

SHEET NO. 2 OF 2

SCALE: 1.7:1.0

Amphenol RF

SIZE

DRAWING NO. 95-902-527-XXX

ITEM NO. 95-902-527-XXX

PART NO. 95-902-527-XXX

REV

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

THIRD ANGLE PROJ.

REFERENCE

EAR#
9708

5

4

3

2

1