
DESCRIPTION: DSUB IP67 FLANGE // MALE // COMBO // VERTICAL PIN PCB MOUNT





CONTACT ø AT TERMINATION SIDE
SIGNAL CONTACTS = ø0.65
20 AMP = ø2.80
40 AMP = ø3.75

NOTE:

MATERIAL	
HOUSING	PBT UL94V-0, BLACK
FLANGE	PBT UL94V-0, BLACK
CONTACT	BRASS, PLATING P/N KEY BELOW
SHELL	STEEL, NICKEL
O-RING	SILICONE
SEALING COMPOUND	EPOXY
HARDWARE	BRASS; NICKEL PLATED
ELECTRICAL	
SIGNAL CONTACT RATED CURRENT	5A
POWER CONTACT RATED CURRENT	P/N KEY BELOW
VOLTAGE	1000 VAC 1 MIN
INSULATOR RESISTANCE	5 GOhms MIN.
SIGNAL CONTACT RESISTANCE	10 mOhms MAX.
POWER CONTACT RESISTANCE	2.0 mOhms MAX.
WATER PROOF	IP67
ENVIRONMENT	
OPERATION TEMPERATURE	-25°C TO +85°C

HARDWARE OPTIONS





CDFV7W2113LYYY

SERIES
CDF = COMBO DSUB FLANGE
CONTACT TYPE
V = VERTICAL PCB MOUNT
POSITION
7W2
GENDER
1 = MALE
POWER CONTACT AMPERAGE
2 = 20 AMPS
4 = 40 AMPS
HARDWARE OPTIONS
1 = 4-40 THREADED INSERTS/4-40 JACKSCREWS
5 = 4-40 THREADED BOARD LOCKS &
4-40 JACKSCREWS
CONTACT PLATING OPTIONS
1 = GOLD FLASH
2 = 30u" GOLD PLATING

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL

DATE: 04/20/2020

TOLERANCES
X. ±0.40
.X ±0.30
.XX ±0.20
.XXX ±0.10

NorComp

SCALE: NTS

SHEET 1 OF 2


REV 1

DWG NO. CDFV7W2113LYYY


DESCRIPTION: DSUB IP67 FLANGE // MALE // COMBO // VERTICAL PIN PCB MOUNT

**ø3.20MM HOLES NOT NEEDED FOR "1" HARDWARE OPTION

20 AMP CONFIGURATION



40 AMP CONFIGURATION



RECOMMENDED PCB LAYOUT
*TYPICAL // HOLE SIZE MAY NOT BE SUITABLE FOR YOUR SPECIFIC APPLICATION

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL

DATE: 04/20/2020

TOLERANCES

X.	±0.40
.X	±0.30
.XX	±0.20
.XXX	±0.10

NorComp

SCALE: NTS

SHEET 2 OF 2

REV 1

DWG NO. CDFV7W2113LYYY